

Overview

HP 255 G8 Notebook PC



Left

- | | |
|-------------------------------------|--|
| 1. Internal dual digital microphone | 7. Power indicator LED |
| 2. Webcam LED | 8. Hard drive indicator LED |
| 3. Webcam | 9. SuperSpeed USB Type-C® 5Gbps signaling rate port (Data Transfer Only) |
| 4. Touchpad | 10. HDMI Port (Cable sold separately) |
| 5. Touchpad buttons | 11. RJ-45 / Ethernet port |
| 6. Audio combo jack | 12. Power button |

1. SuperSpeed USB 20Gbps is not available.

Overview



Right

- | | |
|--|--|
| 1. AC Smart Pin Adapter Plug | 3. SuperSpeed USB Type-A 5Gbps signaling rate port |
| 2. SuperSpeed USB Type-A 5Gbps signaling rate port | 4. SD Card slot |
| | 5. Fingerprint Reader (Select models) |

1. SuperSpeed USB 20Gbps is not available.

Overview

At a Glance

- A new compact narrow bezel design with thinner & lighter chassis
- Preinstall with Windows 10 versions or FreeDOS
- Choice of AMD Ryzen™, Athlon™ and AMD APU processors
- Choice of 39.62 cm (15.6") diagonal HD and FHD SVA Anti-Glare WLED or FHD IPS Anti-Glare WLED
- Choice of Integrated AMD Radeon™ Vega Graphics or Radeon™ Graphics
- Security features including Firmware TPM 2.0 and Fingerprint Reader (selected models)
- Weight starting at 3.84 lbs (1.74 kgs)
- MM18 Battery life up to 10 hours and 15 minutes ¹
- Wireless LAN (WLAN) up to 802.11ac or 802.11ax to keep you connected
- One SuperSpeed USB Type-C® 5Gbps signaling rate² (Data Transfer Only), Two SuperSpeed USB Type-A 5Gbps signaling rate²
- Choice of Solid State Drives up to 1 TB and Hard Drive up to 2 TB
- Dual channel DDR4 SODIMM memory up to 16 GB
- HP webcam with dual digital microphone and HD (supporting WDR- Wide Dynamic Range) or VGA camera
- Designed to support HP docking options including HP USB-C/A Universal Dock G2

1. Windows 10 MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

2. SuperSpeed USB Type-A 5Gbps signaling rate

NOTE: See important legal disclosures for all listed specs in their respective feature sections.



Technical Specifications**PRODUCT NAME**HP 255 G8 Notebook PC

OPERATING SYSTEMS**Preinstalled**

Windows 10 Pro 64 – HP recommends Windows 10 Pro ¹
Windows 10 Pro 64 (National Academic only) ²
Windows 10 Home 64 ¹
Windows 10 Home Single Language 64 ¹
FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

Supported Version

HP tested Windows 10, version 1809 on this platform For testing information on newer versions of Windows10, please see: <https://support.hp.com/document/c05195282>.

PROCESSORS

AMD Ryzen™ 5 3500U APU with Radeon™ Vega 8 Mobile Graphics (2.1 GHz base frequency, up to 3.7 GHz burst frequency, 4 MB cache, 4 cores) ^{3,4,5}
AMD Ryzen™ 3 3300U APU with Radeon™ Vega 6 Graphics (2.1 GHz base frequency, up to 3.5 GHz burst frequency, 4 MB cache, 4 cores) ^{3,4,5}
AMD Ryzen™ 3 3250U APU with Radeon™ Graphics (2.6 GHz base frequency, up to 3.5 GHz burst frequency, 4 MB cache, 2 cores) ^{3,4,5}
AMD Athlon™ Gold 3150U APU with Radeon™ Graphics (2.4 GHz base frequency, up to 3.3 GHz burst frequency, 4 MB cache, 2 cores) ^{3,4,5}
AMD Athlon™ Silver 3050U APU with Radeon™ Graphics (2.3 GHz base frequency, up to 3.2 GHz burst frequency, 4 MB cache, 2 cores) ^{3,4,5}
AMD 3020e APU with Radeon™ Graphics (1.2 GHz base frequency, up to 2.6 GHz burst frequency, 4 MB cache, 2 cores) ^{3,4,5}
AMD Ryzen™ 5 5300U APU with AMD Radeon™ Graphics (2.6 GHz base frequency, up to 3.8 GHz burst frequency, 4 MB cache, 4 cores) ^{3,4,5}
AMD Ryzen™ 5 5500U APU with AMD Radeon™ Graphics (2.1 GHz base frequency, up to 4.0 GHz burst frequency, 8 MB cache, 6 cores) ^{3,4,5}
AMD Ryzen™ 7 5700U APU with AMD Radeon™ Graphics (1.8 GHz base frequency, up to 4.3 GHz burst frequency, 8MB cache, 8cores) ^{3,4,5}
AMD Ryzen™ 3 3200U APU with Radeon™ Vega 3 Graphics (2.6 GHz base frequency, up to 3.5 GHz burst frequency, 4MB cache, 2 cores) ^{3,4,5}



Technical Specifications

Processors Family

AMD Ryzen™ 7 Mobile Processors ⁶

AMD Ryzen™ 5 Mobile Processors ⁶

AMD Ryzen™ 3 Mobile Processors ⁶

AMD Athlon™ Mobile Processors ⁶

AMD APU processor ⁶

3. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

4. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.

5. AMD Max Boost frequency performance varies depending on hardware, software and overall system configuration.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

AMD Radeon™ Vega 8 Mobile Graphics

AMD Radeon™ Vega 6 Mobile Graphics

AMD Radeon™ Vega 3 Mobile Graphics

AMD Radeon™ Graphics

Supports

Support HD decode, DX12, HDMI 1.4b ⁷

7. HD content required to view HD images.

DISPLAYS

Non-Touch

39.6 cm (15.6") diagonal, HD (1366 x 768), SVA, Anti-Glare WLED, 250nits, eDP micro-edge, 45% NTSC ^{7,8,9}

39.6 cm (15.6") diagonal, FHD (1920 x 1080), IPS, Anti-Glare WLED, 250nits eDP micro-edge, 45% NTSC ^{7,8,9}

39.6 cm (15.6") diagonal, FHD (1920 x 1080), SVA, Anti-Glare WLED, 250nits eDP micro-edge, 45% NTSC ^{7,8,9}

HDMI

Port supports resolutions up to 1920 x 1080 external resolution @60 Hz

7. HD content required to view HD images.

8. Sold separately or as an optional feature.

9. Resolutions are dependent upon monitor capability, and resolution and color depth settings.



Technical Specifications

STORAGE AND DRIVES

Primary Storage

2 TB 5400 rpm SATA ¹⁰
1 TB 5400 rpm SATA ¹⁰
500 GB 7200 rpm SATA ¹⁰
500 GB 5400 rpm SATA ¹⁰

Primary M.2 Storage

128 GB M.2 SATA-3 TLC Solid State Drive ¹⁰
128 GB PCIe® NVMe™ TLC Solid State Drive ¹⁰
256 GB PCIe® NVMe™ M.2 Value Solid State Drive ¹⁰
512 GB PCIe® NVMe™ M.2 Value Solid State Drive ¹⁰
1TB PCIe® NVMe™ M.2 Value Solid State Drive ¹⁰

Dual Storage

128 GB M.2 SATA-3 TLC Solid State Drive + 1TB 5400rpm SATA ¹⁰
128 GB PCIe® NVMe™ TLC Solid State Drive + 1 TB 5400rpm SATA ¹⁰
256 GB PCIe® NVMe™ M.2 Value Solid State Drive + 1TB 5400rpm SATA ¹⁰

¹⁰. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

MEMORY

Maximum Memory

16 GB DDR4-3200 SDRAM¹¹

Memory

16 GB DDR4-3200 SDRAM (2 X 8 GB) ¹¹
16 GB DDR4-2400 SDRAM (2 X 8 GB) ¹¹
12 GB DDR4-3200 SDRAM (4 GB (1 x 4GB) and 8 GB (1 x 8 GB)) ¹¹
12 GB DDR4-2400 SDRAM (4 GB (1 x 4GB) and 8 GB (1 x 8 GB)) ¹¹
8 GB DDR4-3200 SDRAM (2 x 4 GB) ¹¹
8 GB DDR4-2400 SDRAM (2 x 4 GB) ¹¹
8 GB DDR4-3200 SDRAM (1 x 8 GB) ¹¹
8 GB DDR4-2400 SDRAM (1 x 8 GB) ¹¹
4 GB DDR4-3200 SDRAM (1 x 4 GB) ¹¹
4 GB DDR4-2400 SDRAM (1 x 4 GB) ¹¹

Memory Slots

2 SODIMM (select models)
Support Dual Channel Memory

1 SODIMM



Technical Specifications

Support Single Channel Memory

NOTE: All slots are customer non-accessible / non-upgradeable

11. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Realtek RTL8822CE 802.11ac 2x2 Wi-Fi® + Bluetooth® 5¹²

Realtek RTL8822CE 802.11a/b/g/n/ac (1x1) Wi-Fi® with Bluetooth® 4.2 Combo¹²

Realtek Wi-Fi CERTIFIED 6™ (2x2) and Bluetooth® 5.2 combo¹³

Miracast

Compatible with Miracast-certified devices (For Win10)¹⁴

Ethernet

Realtek 10/100/1000 GbE NIC¹⁵

12. Wi-Fi supporting gigabit speeds (802.11ac) is achievable when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 160MHz channels.

13. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices.

14. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

15. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.



Technical Specifications

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers
Integrated dual digital microphone

Camera

HP TrueVision HD Camera ^{7,8}

Webcam

VGA webcam ⁸

7. HD content required to view HD images.

8. Sold separately or as an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full Size Textured island-style Keyboard

Pointing Device

Touchpad with multi-touch gesture support (PTP certified)

Function Keys

F1 - Open " How to get help in Windows 10" webpage

F2 - Brightness Down

F3 - Brightness Up

F4 - Display Switching

F5 - Blank

F6 - Mute

F7 - Volume Down

F8 -Volume Up

F9 - Previous

F10 - Play/Pause

F11 - Next

F12 - Airplane mode

Technical Specifications

SOFTWARE AND SECURITY

Preinstalled Software

HP Support Assistant ¹⁶
Native Miracast Support ¹⁷
HP documentation
HP Setup Integrated OOBE
HP SSRM
HP Audio Switch
HP JumpStarts
McAfee LiveSafe™ ¹⁵
Xerox® DocuShare® 30 day free trial offer²⁶
HP QuickDrop
HP Smart Support ²⁷

Security Management

Firmware TPM 2.0 ¹⁸
Fingerprint reader (Select models)

15. 30 days free trial

16. HP Support Assistant requires Windows and Internet access.

17. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

18. Firmware TPM is version 2.0, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT)

26. Simply sign up and start using Xerox® DocuShare® Go. No credit card. No obligation. Data will become unavailable unless a subscription is entered before the end of the 30-day free trial period. See visit <http://www.xerox.com/docusharego> for details.

27. HP Smart Support is available to commercial customers through your HP Service Representative and HP Factory Configuration Services; or it can be downloaded at: <http://www.hp.com/smart-support>. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights.

POWER

Power Supply

HP Smart 65 W EM External AC power adapter ¹⁹
HP Smart 45 W External AC power adapter ¹⁹

Primary Battery

HP Long Life 3-cell, 41 Wh Li-ion (Polymer) ^{20, 28}

Power Cord

1m (3.28 feet) length power cord

MM18 Battery life

Up to 10 hours and 15 minutes ²¹



Technical Specifications

Battery Weight

0.19 kg

0.42 lb

19. Availability may vary by country.

20. Battery is internal and not replaceable by customer. Serviceable by warranty.

21. Windows 10 MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

28. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

WEIGHTS & DIMENSIONS

Product Weight ²²

Starting at 3.84 lb

Starting at 1.74 kg

Product Dimensions (w x d x h)

14.09 x 9.53 x 0.78 in

35.8 x 24.2 x 1.99 cm

22. Weight will vary by configuration. Does not include power adapter.

PORTS/SLOTS

Ports

2 SuperSpeed USB Type-A 5Gbps signaling rate²³

1 SuperSpeed USB Type-C® 5Gbps signaling rate²³ (Data Transfer Only)

1 HDMI v1.4b ²⁴

1 RJ-45

1 AC Power

1 Headphone/microphone combo jack

Expansion Slots

Support SD/SDHC/SDXC

1 Multi-format digital media reader

23. SuperSpeed USB 20Gbps is not available

24. HDMI cable sold separately.



Technical Specifications

SERVICE AND SUPPORT

1-year limited warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.²⁵

25. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19.5 V
Average Operating Power	4.1W
Integrated graphics	PCO - AMD Radeon Vega 8 Graphics Dali - AMD Radeon Graphics
Discrete Graphics	N/A (Switchable graphics design)
Max Operating Power	UMA < 45W

Temperature

Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%

Shock

Operating	40 G, 2 ms duration, half-sine
Non-operating	240 G, 2 ms duration, half-sine

Random Vibration

Operating	1.043 grms
Non-operating	3.5 grms

Altitude (unpressurized)

Operating	-15 m to 3048 m (-50 ft to 10000 ft)
Non-operating	-15 m to 12192 m (-50 ft to 40000 ft)

Planned Industry Standard Certifications

UL	Yes
CSA	No
FCC Compliance	Yes
ENERGY STAR®	Yes
EPEAT®	Yes
ICES	Yes
Australia /	Yes
NZ A – Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marketing Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes
UKRSERTCOMPUTER	Yes



Technical Specifications

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

**Panel LCD 15.6 inch FHD
(1920x1080) Anti-Glare
WLED UWVA 45percent cg
250nits eDP 1.2 w/o PSR
slim NWBZ**

Outline Dimensions (W x H x D)	350.96 x 216.75 (max.) x 3.2 (max.) mm
Active Area	344.16 x 193.59 mm
Weight	370g max.
Diagonal Size	15.6"
Surface Treatment	AG
Touch enabled	None
Contrast Ratio	600:1 (typ.)
Refresh Rate	60Hz
Brightness	250nits typ.
Pixel Resolution	
Configuration	1920 x 1080 (FHD)
Interface	eDP 1.2 w/o PSR
LCD Mode	IPS/PLS/AHVA
PPI	142
Viewing Angle	UWVA 85/85/85/85

**Panel LCD 15.6-in FHD
(1920x1080) Anti-Glare
WLED SVA 45percent cg
250nits eDP 1.2 w/o PSR
NWBZ ultraslim**

Outline Dimensions (W x H x D)	350.96 x 216.75 (max.) x 3.2 (max.) mm
Active Area	344.16 x 193.59 mm
Weight	360g max.
Diagonal Size	15.6"
Surface Treatment	AG
Touch enabled	None
Contrast Ratio	300:1 (typ.)
Refresh Rate	60Hz
Brightness	250nits typ.
Pixel Resolution	
Configuration	1920 x 1080 (FHD)
Interface	eDP 1.2 w/o PSR
LCD Mode	TN
PPI	142
Viewing Angle	UWVA 45/45/15/35



Technical Specifications

Panel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslim	Outline Dimensions (W x H x D)	351.03 x 216.75 (max.) x 3.2 (max.) mm
	Active Area	344.23 x 193.54 mm
	Weight	360g max.
	Diagonal Size	15.6"
	Surface Treatment	AG
	Touch enabled	None
	Contrast Ratio	300:1 (typ.)
	Refresh Rate	60Hz
	Brightness	250nits typ.
	Pixel Resolution	
	Configuration	1366 x 768 (HD)
	Interface	eDP 1.2 w/o PSR
	LCD Mode	TN
	PPI	101
	Viewing Angle	UWVA 40/40/15/30



Technical Specifications

STORAGE AND DRIVES*

* For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

HDD 1TB 5400RPM 7mm SATA (HDD 1TB 5400RPM 2.5in)	Drive Weight	0.21 lbs (95 g)
	Capacity	1TB
	Height	0.28 in (7 mm)
	Width	2.75 in (69.85 mm)
	Interface	ATA-8, SATA 3.0
	Performance	
	Maximum Sequential Read	Up to 100 MB/s
	Maximum Sequential Write	Up to 100 MB/s
	Logical Blocks	1,953,525,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	S.M.A.R.T., NCQ, Ultra DMA

HDD 2TB 5400RPM 7mm SATA 2.5in (HDD 2TB 5400RPM SATA 2.5in 2nd)	Drive Weight	0.21 lbs (95 g)
	Capacity	2TB
	Height	Up to 128MB
	Width	0.28 in (7 mm)
	Interface	2.75 in (69.85 mm)
	Performance	
	Maximum Sequential Read	Up to 100 MB/s
	Maximum Sequential Write	Up to 100 MB/s
	Logical Blocks	3,907,029,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	S.M.A.R.T., NCQ, Ultra DMA

HDD 500GB 5400RPM 7mm SATA	Drive Weight	0.21 lbs (95 g)
	Capacity	500GB
	Height	0.28 in (7 mm)
	Width	2.75 in (69.85 mm)
	Interface	ATA-8, SATA 3.0
	Performance	
	Maximum Sequential Read	Up to 100 MB/s
	Maximum Sequential Write	Up to 100 MB/s
	Logical Blocks	976,773,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	S.M.A.R.T., NCQ, Ultra DMA



Technical Specifications

HDD 500GB 7200RPM 7mm SATA (HDD 500GB 7200RPM 2.5in)	Drive Weight	0.21 lbs (95 g)
	Capacity	500GB
	Height	0.28 in (7 mm)
	Width	2.75 in (69.85 mm)
	Interface	ATA-8, SATA 3.0
	Performance	
	Maximum Sequential Read	Up to 120 MB/s
	Maximum Sequential Write	Up to 120 MB/s
	Logical Blocks	976,773,168
	Operating Temperature	32° to 140° F (0° to 60° C) [case temp]
	Features	S.M.A.R.T., NCQ, Ultra DMA
<hr/>		
SSD 128GB 2280 M2 SATA-3 TLC (SSD 128GB 2280 M2 SATA-3 TLC)	Drive Weight	0.01 lb (6 g) ~ 0.02 lb (10 g)
	Capacity	128 GB
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	ATA-8, SATA 3.0
	Performance	
	Maximum Sequential Read	Up to 500 MB/s
	Maximum Sequential Write	Up to 400MB/s
	Logical Blocks	250,069,680
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	DIPM; TRIM; DEVSLP
<hr/>		
SSD 1TB 2280 PCIe NVMe Value (SSD 1TB 2280 PCIe NVMe Value)	Drive Weight	0.01 lb (6 g) ~ 0.02 lb (10 g)
	Capacity	1TB
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3X2
	Performance	
	Maximum Sequential Read	Up to 1500MB/s
	Maximum Sequential Write	Up to 750MB/s
	Logical Blocks	2,000,409,264
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	TRIM, L1.2



Technical Specifications

SSD 256GB 2280 PCIe NVMe Value (SSD 256GB 2280 PCIe NVMe Value)	Drive Weight	0.01 lb (6 g) ~ 0.02 lb (10 g)
	Capacity	256GB
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3X2
	Performance	
	Maximum Sequential Read	Up to 1500MB/s
	Maximum Sequential Write	Up to 750MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	TRIM, L1.2

SSD 512GB 2280 PCIe NVMe Value (SSD 512GB 2280 PCIe NVMe Value)	Drive Weight	0.01 lb (6 g) ~ 0.02 lb (10 g)
	Capacity	512GB
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3X2
	Performance	
	Maximum Sequential Read	Up to 1500MB/s
	Maximum Sequential Write	Up to 750MB/s
	Logical Blocks	1,000,215,216
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	TRIM, L1.2

Technical Specifications

NETWORKING/COMMUNICATIONS

Intel® Wi-Fi 6 AX201 + Bluetooth® 5 (802.11ax 2x2, non-vPro®, supporting gigabit file transfer speeds) non-vPro®^{1,2}	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Features Wi-Fi® 6 technology
	Frequency Band	<ul style="list-style-type: none"> • 802.11b/g/n/ax 2.402 – 2.482 GHz • 802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
	Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz) • 802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, ,80MHz & 160MHz)
	Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Security³	<ul style="list-style-type: none"> • IEEE compliant 64 /128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power⁴	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum



Technical Specifications

	<ul style="list-style-type: none"> • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum • 802.11ax HT40(2.4GHz): +10dBm minimum • 802.11ax VHT160(5GHz): +10dBm minimum 	
Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW 	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity⁵	<ul style="list-style-type: none"> • 802.11b, 1Mbps: -93.5dBm maximum • 802.11b, 11Mbps: -84dBm maximum • 802.11a/g, 6Mbps: -86dBm maximum • 802.11a/g, 54Mbps: -72dBm maximum • 802.11n, MCS07: -67dBm maximum • 802.11n, MCS15: -64dBm maximum • 802.11ac, MCS0: -84dBm maximum • 802.11ac, MCS9: -59dBm maximum • 802.11ax, MCS11(HT40): -59dBm maximum • 802.11ax, MCS11(VHT160): -58.5dBm maximum 	
Antenna type	<p>High efficiency antenna with spatial diversity, mounted in the display enclosure</p> <p>Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications</p>	
Form Factor	PCI-Express M.2 MiniCard with CNVi Interface	
Dimensions	<ol style="list-style-type: none"> 1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm 	
Weight	<ol style="list-style-type: none"> 1. Type 2230: 2.8 g 2. Type 126: 1.3 g 	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	<p>LED Amber – Radio OFF</p> <p>LED Off – Radio ON</p>	



Technical Specifications

- 1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices.
- 2. Wi-Fi supporting gigabit speeds is achievable when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 160MHz channels.
- 3. Check latest software/driver release for updates on supported security features.
- 4. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
- 5. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2/5.0/5.1 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ⁶ 2.17 Mbps BLE: 1 Mbps signaling data rate ⁶ 0.2 Mbps 6. Actual throughput may vary.
Transmit Power	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.	

Technical Specifications

Realtek 802.11a/b/g/n/ac (1x1) Wi-Fi® and Bluetooth® 4.2 Combo¹	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified modules
	Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	Security²	• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power³	• 802.11b : +14dBm minimum • 802.11g : +12dBm minimum • 802.11a : +12dBm minimum • 802.11n HT20(2.4GHz) : +12dBm minimum • 802.11n HT40(2.4GHz) : +12dBm minimum • 802.11n HT20(5GHz) : +10dBm minimum • 802.11n HT40(5GHz) : +10dBm minimum • 802.11ac VHT80(5GHz) : +10dBm minimum



Technical Specifications

Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity⁴	<ul style="list-style-type: none"> • 802.11b, 1Mbps: -93.5dBm maximum • 802.11b, 11Mbps: -84dBm maximum • 802.11a/g, 6Mbps: -86dBm maximum • 802.11a/g, 54Mbps: -72dBm maximum • 802.11n, MCS07: -67dBm maximum • 802.11n, MCS15: -64dBm maximum • 802.11ac, MCS0: -84dBm maximum • 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230 : 2.3 x 22.0 x 30.0 mm
Weight	Type 2230 : 2.8g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (–10° to 70° C) Non-operating –40° to 176° F (–40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF LED Off – Radio ON

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



Technical Specifications

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH)BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

Technical Specifications

Realtek RTL8822CE 802.11ac 2x2 Wi-Fi®+ Bluetooth® 5¹	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified modules
	Frequency Band	802.11b/g/n • 2.402 – 2.482 GHz 802.11a/n/ac • 4.9 – 4.95 GHz (Japan) • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	Security²	• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power³	• 802.11b : +18.5dBm minimum • 802.11g : +17.5dBm minimum • 802.11a : +18.5dBm minimum • 802.11n HT20(2.4GHz) : +15.5dBm minimum • 802.11n HT40(2.4GHz) : +14.5dBm minimum • 802.11n HT20(5GHz) : +15.5dBm minimum • 802.11n HT40(5GHz) : +14.5dBm minimum • 802.11ac VHT80(5GHz) : +11.5dBm minimum



Technical Specifications

Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW 	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity⁴	<ul style="list-style-type: none"> • 802.11b, 1Mbps: -93.5dBm maximum • 802.11b, 11Mbps: -84dBm maximum • 802.11a/g, 6Mbps: -86dBm maximum • 802.11a/g, 54Mbps: -72dBm maximum • 802.11n, MCS07: -67dBm maximum • 802.11n, MCS15: -64dBm maximum • 802.11ac, MCS0: -84dBm maximum • 802.11ac, MCS9: -59dBm maximum 	
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard	
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm	
Weight	1. Type 2230 : 2.8g 2. Type 1216: 1.3g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (-10° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF LED Off – Radio ON	

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



Technical Specifications

HP Integrated Module with Bluetooth® 4.0/4.1/4.2/5.0 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2/5.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

Technical Specifications

POWER

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m	Dimensions (H x W x D)	95.0x40.0x26.5mm
	Weight	unit: 200g +/- 10g
	Input	Input Efficiency 87.74 % at 115 Vac and 88.4 % at 230Vac
		Input frequency range 47 ~ 63 Hz
		Input AC current Max. 1.4 A at 90 Vac
	Output	Output power 45W
		DC output 19.5V
		Hold-up time 5ms at 115 Vac input
		Output current limit <8.0A
	Connector	C6 (3pin/with grounded, with Smart ID DC connector)
	Environmental Design	Operating temperature 32°F to 95°F (0° to 35°C)
		Non-operating (storage) temperature -4°F to 185°F (-20° to 85°C)
		Altitude 0 to 16,400 ft (0 to 5,000 m)
		Humidity 20% to 95%
		Storage Humidity 10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm New EM	Dimensions	102x55x30mm
	Weight	unit: 250g +/- 10g
	Input	Input Efficiency 88.0 % at 115 Vac and 89.0 % at 230Vac
		Input frequency range 47 ~ 63 Hz
		Input AC current Max. 1.7 A at 90 Vac
	Output	Output power 65W
		DC output 19.5V
		Hold-up time 5ms at 115 Vac input
		Output current limit <11.0A
	Connector	C6 (3pin/with grounded, with Smart ID DC connector)
	Environmental Design	Operating temperature 32°F to 95°F (0° to 35°C)
		Non-operating (storage) temperature -4°F to 185°F (-20° to 85°C)
		Altitude 0 to 16,400 ft (0 to 5000m)



Technical Specifications

EMI and Safety Certifications	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.	

Battery HW 3 Cell WHr 41 Long Life -PR+PL Fast Charge (Not Linked)	Dimensions	6.0mm x 186.85mm x 90.2mm	
	Weight	192g	
	Cells/Type	3cell Lithium-Ion Prismatic cell / 496080	
	Energy	Voltage	11.55V
		Amp-hour capacity	3615mAh
		Watt-hour capacity	41Wh
	Temperature	Operating (Charging)	0°C ~ 45°C
		Operating (Discharging)	-10°C ~ 60°C
	Fuel Gauge LED	N/A	
	Warranty	1000 cycles > 65% (at 23 °C)	
	Optional Travel Battery Available	No	

FINGERPRINT READER

Model	Elan eFSA80ST touch sensor
Mobile Voltage Operation	2.65V to 3.6V
Operating Temperature:	32° to 95° F (0° to 35° C)
Current Consumption Image:	50mA peak
Low Latency Wait For Finger	<900 uA
Capture Rate: Image transmitter output frequency	20cm/sec
ESD Resistance	IEC 61000-4-2 (+15KV)
Detection Matrix	508 dpi / 4x4mm sensor area
FRR (False Reject Rate) / FAR (False Acceptance Rate)	FRR ~ 2% @ 1:50K FAR

Technical Specifications

Country of Origin

China



Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part Number
Cases	HP Prelude Pro Top Load	1X645AA
	HP Prelude Pro Backpack	1X644AA
	HP Prelude Top Load 15.6	1E7D7AA
	HP Prelude Backpack 15.6	1E7D6AA
Docking	HP USB-C®/A Universal Dock G2	5TW13AA
	HP 4.5 mm and USB-C® Dock Adapter G2	6LX61AA
Input/Output	HP USB Essential Keyboard/Mouse	H6L29AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP Slim Wireless Keyboard & Mouse	T6L04AA
	HP Wired Desktop 320K Keyboard	9SR37AA
	HP Slim Wireless Keyboard (Link-5)	T6U20AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP Essential USB Mouse	2TX37AA
	HP USB Travel Mouse	G1K28AA
	HP Bluetooth Travel Mouse	6SP30AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP Wired Desktop 320M Mouse	9VA80AA
	HP HDMI to VGA Adapter	H4F02AA
	HP HDMI to DVI	F5A28AA
Power	HP 45W Smart AC Adapter	H6Y88AA
	HP 65W Smart AC Adapter	H6Y89AA
	HP 65W Slim Adapters (w/ detachable DC cable + TIPS)	H6Y82AA
Storage	HP External USB Optical Drive	F2B56AA
Memory	HP 4GB DDR4 3200 Memory	286H5AA
	HP 8GB DDR4 3200 Memory	286H8AA



Summary of Changes

Date of change:	Version History:		Description of change:
December 14, 2020	From V1 to V2	Update	USB Information
February 25, 2021	From V2 to V3	Update	Xerox DocuShare offer value
March 2, 2021	From V3 to V4	Add	Fingerprint reader Spec and updates System Unit and At a Glance
April 20, 2021	From V4 to V5	Update	TechSpecs/Memory Modules
May 6, 2021	From V5 to V6	Add	HP Smart Support
June 14, 2021	From V6 to V7	Add	New WLAN in Networking/Communications section
July 6, 2021	From V7 to V8	Add	Battery disclaimer

Copyright © 2021 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.