
### **Technical Specifications**

#### **HP P22v G4 FHD Monitor**



#### **Front**

OSD Buttons

Power Button (With power light)

### **Technical Specifications**

### **HP P22v G4 FHD Monitor THOR**



- 1. Security Cable Slot
- 2. Power Connector

### Back

- 3. HDMI Port
- 4. VGA Connector

#### **Technical Specifications**

Models: 9TT53AA/9TT53A6/9TT53A7/9TT53AS/9TT53AT/9TT53AV

Panel Specifications Display Size (Diagonal) 21.5-inch

Panel Technology TN **Curved Panel** No **Refresh Rate** 60 Hz **Panel Bit Depth** 8 bit **Aspect Ratio** 16:9 **Brightness - Typical** 250 nits **Static Contrast Ratio** 1000:1 **Static Contrast Ratio - Minimum** 700:1 **Dynamic Contrast Ratio** 8M:1 (min.)

Flicker Free No

**Pixel Pitch** 0.24825 x 0.24825mm

Pixels Per Inch (PPI) 102

Backlight Lamp Life 30 k minimum

(to half brightness - in hours)

Backlight TypeEdge-litScreen TreatmentAnti-glareHardness3HHaze25%Response Time - Typical5ms on/off

Horizontal Viewing Angle 170°

(typical CR>10)

Vertical Viewing Angle (typical CR>10) 160°

Panel Active Area (w x h) 476.64mm x 268.11mm

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage NTSC 72%

**Color Management Calibrated Color Presets** Native

Color Space / Subsampling Support No

RGB Channel Adjust Yes, Gain
Integrated Calibration Instrument No
Standalone / Schedule Calibration No
Scriptable Calibration No

**Default Color Temperature** Neutral (6500K)

Monitor Specifications Bezel Standard

 Color
 Black Head

 Tilt
 -5 to +20°

 Swivel
 No Swivel

 Pivot
 No Pivot

**Height Adjustment Range**No height adjust

**VESA Mounting** 100 mm x 100 mm (bracket included)

Integrated Privacy Filter No

### **Technical Specifications**

Security Lock Ready Standard Security Lock Slot

Detachable Stand Ye

Warranty (number of years) V22 (1/0/0 for AMS ,1/1/0APJ ,3/3/3 for EMEA)

P22v G4(3/3/0 or 3/3/3)

**Low Blue Light Mode** Yes (TÜV certified)

Zero Bright Dot Warranty No

**Touch-Enabled** Not touch-enabled

Multimedia Webcam No integrated webcam

Windows Hello Compatible No

Microphone No Microphone

On Screen Display (OSD)

Native Resolution Full HD (1920 x 1080)\*

\*Apply to high resolution and/or high frame rate displays only.

CONFIRM WITH EPM whether disclaimer applies.

Maximum Resolution 1920 x1080 @ 60Hz

Preset Graphic Modes/Supported 11

Resolutions

Minimum Vertical Scan Rate50 HzMaximum Vertical Scan Rate60 HzMinimum Horizontal Scan Rate30.0 kHzMaximum Horizontal Scan Rate80.0 kHzMaximum pixel clock170 MHzUser Programmable Modes10

**User-Assignable Function Buttons** Yes, 3 buttons

Audio No

**Languages** 10 (English, Spanish, German, French, Italian, Netherlands,

Internal

Portuguese, Japanese, T-Chinese and S-Chinese)

Connector Types HDMI 1 HDMI 1.4

**Power Supply** 

VGA 1 VGA

Power & Operating

Specs Power Source

**Power Source** 100 – 240 VAC 50/60 Hz

Power Consumption - Maximum19 WEnergy Saving/Standby Mode0.5 WPower Consumption - Typical18.5 WPower cable lenght1.9m

**Energy Star Data Operational Mode at 100 VAC** 12.3 W

Operational Mode at 115 VAC 12.34 W
Operational Mode at 230 VAC 12.56 W

EU Energy Efficiency Class (ERP Lot5)

**On-mode Power Consumption** 13 W

**Annual Power Consumption** 19 kWh **Energy Efficiency Class** D

**Operating Conditions Operating Temperature - Celsius** 50 - 350C

### **Technical Specifications**

Operating Temperature - Fahrenheit 410-950FNon-operating Temperature - Celsius  $-40^{\circ}-65^{\circ}C$ Non-operating Temperature -  $-40^{\circ}-149^{\circ}F$ 

**Fahrenheit** 

**Operating Humidity** 20 – 80% Relative Humidity (non-condensing)

Non-operating Humidity 5-95%

 Operating Altitude
 0 - 5,000 m (16,400 ft.)

 Non-operating Altitude
 0 - 12,192 m (40,000 ft.)

Environmental Features and Certifications Mercury-free LED display backlighting Yes

Arsenic-Free Display Glass

Yes, Mercury-free LED backlights

Yes

**Agency Approvals and Certifications** WW application

CE,CB,KC/KCC/NOM/PSB/ICE/TUV-S/ISO 9241-307/ EAC/cTUVus/PSB/ISC/CCC/CEL/CECP/SEPA/TCO/Energy Star/ISC/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/ South Africa/ Ukraine / BIS / GS / Low

Blue Light

Microsoft WHQL Certification Win 10, Win 8, Win 7

**ENERGY STAR® Certified** Yes **EPEAT® Registered** Yes

Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more

5.47 lb

information.

CEL Grade 1

**TCO Certified** Yes

only

Yes (NA sku)

**Recycled Plastics** 

Contains Recycled Plastics 35% recycled ABS

Recyclable Packaging (Box, packing

SmartWay Transport Partnership -NA

materials)

**Product Weight** 

(Head Only)

69.6% Circular packing material

Unit Product/Package Specifications

	<u>metric</u>	<u>imperial</u>
Product Dimensions (Unpacked with stand) (W x D x H)	505×188.95×381.26 mm	19.88×7.44×15.01 in
Product Dimensions (Packed) (W x D x H)	567×120×387mm	19.88×1.65×12.21 in
<b>Display Head Dimensions</b> (Unpacked without stand) (W x D x H)	505×42×310.26 mm	22.32×4.72×15.24 in
Base Area Footprint (w x d mm)	188.95 x 181 mm	7.44 x 7.13 in
Bezel Measurements	top15.97 mm side 24.19 mm bottom 13.17 mm	top 0.63 in side 0.95 in bottom 0.52 in
Product Weight (Unpacked with stand)	2.85 kg	6.28 lb
Product Weight (Packed)	3.79 kg	8.36 lb

2.48 kg



Slip Sheet: L45.28 x W38.19 x

Pallet: L45.28 x W38.19 x

Pallet: 712.09 lb (40' ft)

Slip Sheet: 676.82 lb (40' ft)

76.69 inch (40' ft)

81.38 inch (40' ft)

## QuickSpecs

### **Technical Specifications**

**Pallet Information** 

**Pallet Dimensions** Slip Sheet: L: 1150 x W:

(L x W x H) 970 x H: 1948 mm (40' ft)

Pallet: L: 1150 x W: 970 x

H: 2067 mm (40' ft)

Pallet Total Weight Slip Sheet: 307KG (40' ft)
Pallet: 323KG (40' ft)

Pallet Layers 5 layers per palle (40' ft)

Pallet Product per Layer 16 per layer (slip sheet &

pallet)

**Total Products per Pallet** 80sets per pallet (slip

sheet & pallet)

**Container Load, 20-Foot** 960 sets (slip sheet and

pallet)

**Container Load, 40-Foot** 1920 sets (slip sheet and

pallet)

Container Load, 40-Foot HighQ 2304 sets (slip sheet &

pallet)

What's in the box? VGA cable (1.5m) (Production before Dec'20, Inbound PN -007)

HDMI cable (1.8m) (Production from Dec'20, Inbound PN -A07)

DOC Kit (includes Product Notice, warranty, QSP)

Power cord (1.9m)

Note: China continue ship with VGA cable, no HDMI cable.

User Guide and Warranty Languages **User Guide Languages** English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish

**Warranty Languages** English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

Copyright © 2020 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

### Summary

Change Log				
February 23, 2021	V1 to V2	Update	What's in the box? Section	
March 10, 2021	V2 to V3	Update	EU Energy Efficiency Class	
	V3 to V4			

