

Overview

HP ProBook x360 11 G3 EE Notebook PC



Left

- | | | | |
|----|---|-----|--|
| 1. | Internal microphones (2) | 7. | Volume button |
| 2. | User-facing webcam LED | 8. | Power button |
| 3. | User-facing 720p webcam | 9. | Headphone / Microphone combo jack |
| 4. | ClickPad | 10. | USB 3.1 Gen 1 port |
| 5. | World-facing 5 megapixels webcam (Select models only) | 11. | Security lock slot (Nano lock sold separately) |
| 6. | World-facing webcam LED (Select models only) | | |

Overview



1. Power connector
2. Ethernet (RJ-45) port
3. HDMI port (Cable not included)

Right

4. USB 3.1 Gen 1 port
5. USB Type-C™ (Data and Power in-out)
6. Micro SD card reader

Overview

AT A GLANCE

- Starting at 2.97 lbs (1.35 kg) non-touch and 3.17 lbs (1.44 kg) touch
- Less than 20 mm (0.79 inch), this flexible 360° hinge converts to laptop, tablet, tent, or stand mode easily
- Passed MIL-STD 810G testing¹ with rugged features such as co-molded rubber trim, spill- and pick-resistant keyboard, and Corning® Gorilla® Glass 3 touch screen
- Optional dual camera system for project-based learning
- Optional HP Active Pen provides an authentic digital inking experience
- Pre-installed with Windows 10 Pro 64, Windows 10 Pro 64 (National Academic), Windows 10 Home 64, or Windows 10 Pro in S mode 64
- Powered by Intel® Celeron® N4000, Intel® Celeron® N4100 or Intel® Pentium® N5000 processors
- Choice of 29.4cm (11.6 inch) diagonal HD UWVA slim LED touch screen (1366 x 768), 29.4 cm (11.6 inch) diagonal HD SVA anti-glare slim LED non-touch (1366 x 768) or 29.4 cm (11.6 inch) diagonal HD SVA slim LED touch screen (1366 x 768) displays
- 64 GB eMMC or up to 256 GB SATA-3 Solid State Drive storage options
- Up to 8 GB system memory for enhanced memory management
- Reliable connectivity with choice of Intel® Dual Band Wireless-AC 9260 802.11a/b/g/n/ac (2x2) WiFi and Bluetooth® 5.0 Combo WLAN or Realtek RTL8822BE 802.11a/b/g/n/ac (2x2) WiFi and Bluetooth® 4.2 Combo WLAN for learning and collaboration beyond the classroom
- Built-in ports include: Ethernet (RJ-45), USB 3.1 Gen 1, USB Type-C™, and HDMI 2.0a port for connecting to high-resolution displays
- Enhanced security TPM 2.0 discrete chip
- Battery life Up to 16hrs and 30 mins for SSD
- Battery life Up to 16hrs and 50 mins for eMMC

1. MIL STD 810G testing is pending and is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Damage under the MIL STD test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Technical Specifications

PRODUCT NAME

HP ProBook x360 11 G3 EE Notebook PC

OPERATING SYSTEM

Preinstalled

Windows® 10 Pro 64¹
Windows® 10 Pro 64 (National Academic License)²
Windows® 10 Home 64¹
Windows® 10 Home Single Language 64¹
Windows 10 Pro in S mode 64³
Windows 10 Pro in S mode 64 (National Academic only)^{2,3}

Note: In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>.

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.
2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information
3. Windows 10 Pro in S mode 64 works exclusively with apps from the Windows store. Some accessories and apps compatible with Windows 10 may not work, and performance may vary. Certain default settings, features, and apps cannot be changed. Easily switch to Windows 10 Pro configuration (fee applies) Learn more at Microsoft.com/Windows10S.

PROCESSORS

Intel® Pentium® Silver N5000 with Intel® UHD Graphics 605 (1.1 GHz base frequency, up to 2.7 GHz burst frequency, 4 MB cache, 4 cores)^{4,5,6}

Intel® Celeron® N4100 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.4 GHz burst frequency, 4 MB cache, 4 cores)^{4,5,6}

Intel® Celeron® N4000 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz burst frequency, 4 MB cache, 2 cores)^{4,5,6}

Processors Family

Intel® Celeron® processor (N4000 is Windows 10 only)⁶

Intel® Celeron® processor (N4100 is Windows 10 only)⁶

Intel® Pentium® silver processor (N5000 is Windows 10 only)⁶

4. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.



Technical Specifications

5. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
6. NOTE: In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

Intel® UHD Graphics 605 (for Pentium)⁷

Intel® UHD Graphics 600 (for Celeron)⁷

7. HD content required to view HD images.

NOTE: View processor section for details.

DISPLAY

Internal

Non-Touch

29.46 cm (11.6") diagonal HD SVA eDP anti-glare LED-backlit slim, 220 cd/m², 67% sRGB (1366 x 768)

Touch

29.46 cm (11.6") diagonal HD IPS eDP LED-backlit touch screen with HD camera, 220 cd/m², 67% sRGB (1366 x 768)

29.46 cm (11.6") diagonal HD SVA eDP LED-backlit touch screen with HD camera, 220 cd/m², 67% sRGB (1366 x 768)

HDMI²

Port supports resolutions up to 3840 x 2160 external resolution @60 Hz

7. HD content required to view HD images.
8. Resolutions are dependent upon monitor capability, and resolution and color depth settings.
9. Touchscreen is an optional feature that must be configured at purchase.

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.



Technical Specifications

STORAGE AND DRIVES

Primary Storage

M.2 (NGFF) 2280 Solid State Drive

128 GB SATA-3 TLC Solid State Drive^{10,11}

256 GB SATA-3 TLC Solid State Drive^{10,11}

eMMC Configurations

64 GB eMMC¹⁰

10. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

11. Not available with eMMC storage.

MEMORY

Standard

Maximum Memory

8 GB DDR4-2400 SDRAM¹²

Memory

4 GB DDR4-2400 SDRAM (on-board)¹²

8 GB DDR4-2400 SDRAM (on-board)¹²

12. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

Broadband Wireless (WWAN)^{1,2,3}

WLAN

Intel® Dual Band Wireless-AC 9260 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, non-vPro™¹³

Realtek RTL8822BE 802.11ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo¹³

Miracast

Miracast Support¹⁵

Ethernet

Realtek RTL8111HSH-CG 10/100/1000 GbE NIC¹⁴

13. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

14. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

15. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.



Technical Specifications

AUDIO/MULTIMEDIA

Audio

HP Audio

2 Integrated stereo speakers

Camera

User-facing 720p HD camera^{7,16}

Located on display

Webcam

World-facing 5 MP secondary camera^{7,9,16}

Located on keyboard deck (option only available with touch display configurations)

NOTE: Both webcams are fix focus.

- 7. HD content required to view HD images.
- 9. Sold separately or as an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS/PEN

Keyboard

Full-sized keyboard, spill and pick resistant

Pointing Device

Clickpad with multi-touch gesture support, taps enabled as default

Default on: 2-finger scroll, pinch

Support Windows 10 modern Trackpad gestures

Function Keys

F1 - Blank

F2 - ClickPad Enable/Disable

F3 - Sleep

F4 - Display Switching

F5 - Audio Mute/Unmute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute/Unmute

F9 - Brightness Down

F10 - Brightness Up

F11 - Blank

F12 - Wireless On/Off

Pen

Optional HP Active Pen⁹



Technical Specifications

Sensors

Accelerometer
Magnetometer
Gyroscope

9.Sold separately or as an optional feature.

SOFTWARE AND SECURITY

BIOS

HP BIOSphere Gen4¹⁷
HP DriveLock & Automatic DriveLock¹⁸
BIOS Update via Network
Secure Erase¹⁹
Absolute Persistence Module²⁰
Pre-boot Authentication
HP Wireless Wakeup

Software

HP Native Miracast Support¹⁵
HP Connection Optimizer
HP 3D DriveGuard
HP Hotkey Support - CMIT
HP Jumpstart
HP Support Assistant²²
HP Noise Cancellation Software
HP School Pack
HP Host Based MAC Address Manager
Buy Office (sold separately)

Manageability Features

HP Driver Packs²⁴
HP System Software Manager (SSM)
HP BIOS Config Utility (BCU)
HP Client Catalog
HP Manageability Integration Kit Gen2²⁵
Ivanti Management Suite²⁶

Client Security Software

- HP Client Security Suite Gen3²⁷ including:
 - HP Security Manager (including Credential Manager, HP Password Manager²⁸, HP Spare Key)
 - HP Device Access Manager³⁰
 - HP Power On Authentication

Windows Defender³¹

Security Management



Technical Specifications

Secure Erase¹⁹

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)³²

SATA 0,1 port disablement (viaBIOS)

RAID configurations³³

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

15. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

17. HP BIOSphere Gen4 requires Intel(R) or AMD 8th Gen processors. Features may vary depending on the platform and configurations.

18. HP Drive Lock & Automatic Drive Lock is not supported on NVMe drives

19. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method.

20. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

21. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hp.com/go/eprintcenter). Print times and connection speeds may vary.

22. HP Support Assistant requires Windows and Internet access.

24. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

25. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.

26. Ivanti Management Suite subscription required.

27. HP Client Security Suite Gen 3 requires Windows and Intel® or AMD 8th generation processors.

28. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.

30. HP Device Access Manager requires HP Client Security Suite Gen4

31. Windows Defender Opt in and internet connection required for updates.

32. Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).

33. RAID configuration is optional and does require a second hard drive.

POWER

Power Supply

HP Smart 45 W External AC power adapter³⁴

HP Smart 65 W EM External AC power adapter³⁴

HP Smart 45 W USB Type-C™ adapter³⁴

Primary Battery

HP Long Life 3-cell, 48 Wh Li-ion (90% in 90 minutes)^{35,36}



Technical Specifications

Power Cord

3-wire plug - 1m

Battery life

Up to 16hrs and 30 mins for SSD³⁷

Up to 16hrs and 50 mins for eMMC³⁷

NOTE: Battery is internal and not replaceable by customer.

34. Availability may vary by country.
35. Battery is internal and not replaceable by customer. Serviceable by warranty.
36. Recharges the battery up to 90% within 90 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 90% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.
37. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

ENVIRONMENTAL

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- EPEAT® Silver registered in the United States. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.
- TCO Certified 5.0.

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Sort idle)	4.19 W	4.27 W	4.15 W
Normal Operation (Long idle)	1.48 W	1.51 W	1.45 W
Sleep	0.34 W	0.37 W	0.34 W
Off	0.25 W	0.30 W	0.25 W



Technical Specifications

Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	14 BTU/hr	15 BTU/hr	14 BTU/hr
Normal Operation (Long idle)	5 BTU/hr	5 BTU/hr	5 BTU/hr
Sleep	1 BTU/hr	1 BTU/hr	1 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

*Note: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WA} , bels)	Sound Pressure (L _{pAm} , decibels)
Typically Configured – Idle	2.5	16
Fixed Disk – Random writes	2.5	16

Longevity and Upgrading Upgradeable features and/or components contained in the product may include:

- AC Adapter
- Pen

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Batteries This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:
Mercury greater the 1ppm by weight
Cadmium greater than 20ppm by weight

Battery size: CR2032 (coin cell)
Battery type: Lithium



Technical Specifications

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680.1 (EPEAT) standard at the Silver level, see <http://www.epeat.net>
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product contains 2.5% post-consumer recycled plastic (by wt.)
- This product is 97.6% recycle-able when properly disposed of at end of life.

Packaging Materials

External:	PAPER/Corrugated	237 g
Internal:	PLASTIC/Polyethylene Expanded - EPE	27 g
	PLASTIC/Polyethylene low density – LDPE	13 g
	PLASTIC/Polypropylene - PP	3 g

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>:

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)



Technical Specifications

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf

and <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

WEIGHTS & DIMENSIONS

Product Weight

Starting at 2.97 lb (non-touch); Starting at 3.17 lb (touch)³⁸

Starting at 1.35 kg (non-touch); Starting at 1.44 kg (touch)³⁸

Product Dimensions (w x d x h)

11.8 x 8.11 x 0.78 in

30 x 20.59 x 1.99 cm

³⁸. Weight will vary by configuration.

PORTS/SLOTS



Technical Specifications

Ports

- 2 USB 3.1 Gen 1
- 1 USB Type-C™ (Data transfer, power delivery)
- 1 HDMI 2.0a³⁹
- 1 AC power
- 1 RJ-45
- 1 headphone/microphone combo jack

Expansion Slots

- 1 multi-format digital media reader
- Supports SD, SDHC, SDXC

39. HDMI cable sold separately.

NOTE: All cables are sold separately.

SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.⁴⁰

40. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	Win 10
Integrated graphics	Yes
Max Operating Power	UMA < 45W

Temperature

Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

Shock

Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine

Random Vibration

Operating	0.75 grms
Non-operating	1.50 grms

Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry Standard

Certifications

UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR 7.0®	Yes ⁴¹
EPEAT® 2019	Yes, Silver in U.S. ⁴²
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes
UKRSERTCOMPUTER	Yes



Technical Specifications

41. Configurations of the HP ProBook x360 11 G3 is ENERGY STAR® qualified are identified as HP ProBook x360 11 G3 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

42. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Panel LCD 11.6 HD AG WLED SVA 45% cg 220 nits eDP Slim	Outline Dimensions (W x H x D)	278.5 x 168.5 mm(max)
	Active Area	256.125 x 144 mm
	Weight	210g max
	Diagonal Size	11.6 (inch)
	Thickness	3.0 mm (max)
	Interface	eDP1.2
	Surface Treatment	Anti-glare
	Touch Enabled	None
	10 Touch Points	Yes
	Contrast Ratio	400:1 (typical)
	Refresh Rate	60Hz
	Brightness	220 nit typical (panel only)
	Pixel Resolution	1366x768 (HD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	45%
	Color Depth	6 bits
	Viewing Angle	SVA 45/45/15/35
Panel LCD 11.6 HD AG WLED SVA 45% cg 220 nits eDP Slim	Outline Dimensions (W x H x D)	278.5 x 168.5 mm(max)
	Active Area	256.125 x 144 mm
	Weight	210g max
	Diagonal Size	11.6 (inch)
	Thickness	3.0 mm (max)
	Interface	eDP1.2
Panel LCD 11.6 HD AG WLED SVA 45% cg 220 nits eDP Slim	Surface Treatment	BrightView Glass



Technical Specifications

Touch Enabled	Yes
Contrast Ratio	400:1 (typical)
Refresh Rate	60Hz
Brightness	220 nit typical (panel only)
Pixel Resolution	1366x768 (HD)
Format	RGB
Backlight	LED
Color Gamut Coverage	45%
Color Depth	6 bits
Viewing Angle	SVA 45/45/15/35

Panel LCD 11.6 inch HD AG WLED UWVA 50 percent cg 220 nits eDP slim **Outline Dimensions** 278.5 x 168.5 mm(max)

Active Area	256.125 x 144 mm
Weight	200g max
Diagonal Size	11.6 (inch)
Thickness	3.2 mm max
Interface	eDP1.2
Surface Treatment	BrightView Glass
Touch Enabled	Yes
Contrast Ratio	800:1 (typical)
Refresh Rate	60Hz
Brightness	220 nit typical (panel only)
Pixel Resolution	1366x768 (HD)
Format	RGB
Backlight	LED
Color Gamut Coverage	50%
Color Depth	6 bits
Viewing Angle	UWVA 85/85/85/85

STORAGE AND DRIVES

eMMC 64 GB M0-276 MMCv5.0	Drive Weight	0.2 g	
	Height	1.4 mm	
	Width	11.5 x 13 mm	
	Interface	MMC optical	
	Seek Time	Sequential Read	Sequential Write
		Up to 250 MB/s	Up to 70 MB/s
	Logical Blocks	32 GB (31,268,536,320 Bytes)/64 GB (62,537,072,640 Bytes)	
	Operating Temperature	0 to 70	
	Security Features	HS400	



Technical Specifications

128 GB 2280 M2 SATA-3 TLC Solid State Drive	Form Factor	M.2 2280	
	Capacity	128 GB	
	NAND Type	TLC	
	Height	0.09 in (2.3 mm)	
	Width	0.87 in (22 mm)	
	Weight	0.02 lb (10 g)	
	Interface	ATA-8, SATA 3.0	
	Seek Time	Sequential Read	Sequential Write
		Up To 520 MB/s	Up To 450 MB/s
	Logical Blocks	250,069,680	
256 GB 2280 M2 SATA-3 TLC Solid State Drive	Form Factor	M.2 2280	
	Capacity	256GB	
	NAND Type	TLC	
	Height	0.09 in (2.3 mm)	
	Width	0.87 in (22 mm)	
	Interface	0.02 lb (10 g)	
	Seek Time	Sequential Read	Sequential Write
		Up To 540 MB/s	Up To 515 MB/s
	Logical Blocks	500,118,192	
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]	
	Features	DIPM; TRIM; DEVSLP	

NETWORKING/COMMUNICATIONS

Realtek 802.11a/b/g/n/ac (2x2) WiFi and Bluetooth® 4.2 Combo	Wireless LAN	IEEE 802.11a
	Standards	IEEE 802.11b
		IEEE 802.11g
		IEEE 802.11n
		IEEE 802.11ac
		Wi-Fi certified
	Interoperability Frequency Band	802.11b/g/n
		•2.402 – 2.482 GHz
		802.11a/n
		•4.9 – 4.95 GHz (Japan)
		•5.15 – 5.25 GHz
		•5.25 – 5.35 GHz
		•5.47 – 5.725 GHz
		•5.825 – 5.850 GHz



Technical Specifications

Data Rates	<ul style="list-style-type: none"> •802.11b: 1, 2, 5.5, 11 Mbps •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) •802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> •IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only •AES-CCMP: 128 bit in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •IEEE 802.11i •Cisco Certified Extensions, all versions through CCX4 and CCX Lite •WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +14dBm minimum • 802.11g: +12dBm minimum • 802.11a: +12dBm minimum • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> •Transmit mode 2.0 W •Receive mode 1.6 W •Idle mode (PSP) 180 mW (WLAN Associated) •Idle mode 50 mW (WLAN unassociated) •Connected Standby 10mW •Radio disabled 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum



Technical Specifications

Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure	
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard	
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm	
Weight	Type 2230: 2.8g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON	
	<ol style="list-style-type: none">1. Check latest software/driver release for updates on supported security features.2. Maximum output power may vary by country according to local regulations.3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).	
HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology		
Bluetooth Specification	4.0/4.1/4.2 Compliant	
Frequency Band	2402 to 2480 MHz	
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)	
Data Rates and Throughput	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)	
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.	
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW	
Electrical Interface	USB 2.0 compliant	
Bluetooth Software Supported	Microsoft Windows Bluetooth Software	
Link Topology		
Power Management	Microsoft Windows ACPI, and USB Bus Support	
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark	
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance	



Technical Specifications

**Intel Thunder Peak 9260
802.11a/b/g/n/ac (2x2)
WiFi and Bluetooth® 5.0
Combo¹ Non-vPro**

Wireless LAN Standards

Interoperability Frequency Band

Data Rates

Modulation

Security³

LE Link Layer Ping
LE Dual Mode
LE Link Layer
LE Low Duty Cycle Directed Advertising
LE L2CAP Connection Oriented Channels
Train Nudging & Interlaced Scan
BT4.2 ESR08 Compliance
LE Secure Connection- Basic/Full
LE Privacy 1.2 –Link Layer Privacy
LE Privacy 1.2 –Extended Scanner Filter Policies
LE Data Packet Length Extension
FAX Profile (FAX)
Basic Imaging Profile (BIP)2
Headset Profile (HSP)
Hands Free Profile (HFP)
Advanced Audio Distribution Profile (A2DP)

IEEE 802.11a
IEEE 802.11b
IEEE 802.11g
IEEE 802.11n
IEEE 802.11ac
IEEE 802.11d
IEEE 802.11e
IEEE 802.11h
IEEE 802.11i
IEEE 802.11k
IEEE 802.11r
IEEE 802.11v
Wi-Fi certified
802.11b/g/n
•2.402 – 2.482 GHz

802.11a/n/ac
•4.9 – 4.95 GHz (Japan)
•5.15 – 5.25 GHz
•5.25 – 5.35 GHz
•5.47 – 5.725 GHz
•5.825 – 5.850 GHz
•802.11b: 1, 2, 5.5, 11 Mbps
•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)
•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)

Direct Sequence Spread Spectrum
BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
•IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only



Technical Specifications

	<ul style="list-style-type: none"> • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management
Receiver Sensitivity³	802.11 compliant power saving mode 802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230: 2.8g 2. Type 126: 1.3g
Operating Voltage	3.3v +/- 9%



Technical Specifications

Temperature	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Amber – Radio OFF; LED White – Radio ON	
<div>1. Check latest software/driver release for updates on supported security features.</div> <div>2. Maximum output power may vary by country according to local regulations.</div> <div>3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</div>		
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology		
Bluetooth Specification	4.0/4.1/4.2/5.0 Compliant	
Frequency Band	2402 to 2480 MHz	
Number of Available Channels	Legacy: 0~79 (1 MHz/CH)	
	BLE: 0~39 (2 MHz/CH)	
Data Rates and Throughput	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps	
	BLE: 1 Mbps data rate; throughput up to 0.2 Mbps	
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels	
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)	
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.	
Power Consumption	Peak (Tx) 330 mW	
	Peak (Rx) 230 mW	
	Selective Suspend 17 mW	
Electrical Interface	USB 2.0 compliant	
Bluetooth Software Supported	Microsoft Windows Bluetooth Software	
Link Topology		
Power Management	Microsoft Windows ACPI, and USB Bus Support	
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	
Power Management Certifications	ETS 300 328, ETS 300 826	
	Low Voltage Directive IEC950	
	UL, CSA, and CE Mark	
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance	
	LE Link Layer Ping	
	LE Dual Mode	
	LE Link Layer	
	LE Low Duty Cycle Directed Advertising	
	LE L2CAP Connection Oriented Channels	
	Train Nudging & Interlaced Scan	
	BT4.2 ESR08 Compliance	
	LE Secure Connection- Basic/Full	
	LE Privacy 1.2 –Link Layer Privacy	
	LE Privacy 1.2 –Extended Scanner Filter Policies	



Technical Specifications

LE Data Packet Length Extension
FAX Profile (FAX)
Basic Imaging Profile (BIP)2
Headset Profile (HSP)
Hands Free Profile (HFP)
Advanced Audio Distribution Profile (A2DP)

POWER

HP 45W Smart AC adapter	Dimensions (H x W x D)	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)
	Weight	0.386 lb (175g) max
	Input	90 to 265 VAC
	Input Efficiency	87.74% at 115Vac and 88.4% at 230Vac
	Input frequency range	47 to 63 Hz
	Input AC current	1.4 A at 90 VAC
	Output	Output power 45W
		DC output 19.5V
		Hold-up time 5ms at 115 VAC input
		Output current protection <8.0A
	Connector	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	Environmental Design	Operating temperature 32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature -4° to 185° F (-20° to 85° C)
		Altitude 0 to 16,400 ft (0 to 5000m)
		Humidity 20% to 95%
HP 65W EM Smart AC adapter		Storage Humidity 10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives
		Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV;
		Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.
		MTBF - over 200,000 hours at 25°C ambient condition.
	Dimensions	102x55x30mm
	Weight	270g +/- 10g
	Input	Input Efficiency 87% min at 115V/230V
		Input frequency range 47 to 63 Hz
		Input AC current 1.7 A at 90 VAC and maximum load
	Output	DC output 65W(19.5V/3.33A)
		Hold-up time 5 msec at 115 VAC input
		Output current limit <11A, Over voltage protection- 29V max automatic shutdown



Technical Specifications

	Connector	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	Environmental Design	Operating temperature 0° to 35° C
		Non-operating (storage) temperature -20° to 85° C
		Altitude 0 to 5,000 m
		Humidity 0% to 95%
	EMI and Safety Certifications	Storage Humidity 0% to 95%
		CE Mark - EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.
HP 45W USB type C Straight 1.8m AC Adapter	Dimensions	94.0mm*40.0mm*26.5mm
	Weight	192.5g +/-10%
	Input	Input Efficiency Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%
		Input frequency range 47 ~ 63Hz
		Input AC current Max. 1.4 A at 90 Vac
	Output	Output power 5V/15W 9V/27W 12V/36W 15V/45W
		DC output 5V/9V/12V/15V
		Hold-up time 5ms at 115 Vac input
		Output current limit <5.0A
		Connector USB Type-C
	Environmental Design	Operating temperature 32°F to 95° F (0° to 35° C)
		Non-operating (storage) temperature 4°F to 185° F (-20° to 85° C)
		Altitude 0 to 16,400 ft (0 to 5000m)
		Humidity 20% to 95%
		Storage Humidity 10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives
		Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.
		MTBF - over 200,000 hours at 25°C ambient condition.



Technical Specifications

HP 3-cell Long Life Li-Ion (48 WHr)	Dimensions (H x W x L)	7.3*94*184.47mm (0.287*3.7*7.263 inch)
	Weight	0.215kg
	Cells/Type	3cell Lithium-Ion Prismatic cell / 596080 3cell Lithium-Ion Polymer cell / 606072
	Voltage	11.4V
	Amp-hour capacity	4.212Ah
	Watt-hour capacity	48Wh
	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 122° F (-10° to 60° C)
	Optional Travel Battery Available	No

COUNTRY OF ORIGIN

China



Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part Number
Cases	HP Essential Top Load Case	H2W17AA#xxx
	HP Essential Backpack	H1D24AA
	HP Slim Ultrabook Top Load	F3W15AA
	HP Slim Ultrabook Backpack	F3W16AA
	HP Black 11.6 Always On Case	2MY57AA
	HP Slim Ultrabook Messenger	F3W14AA
Docking	HP USB-C Universal Dock	1MK33AA
	HP USB Travel Dock	TOK30AA
	HP 3005pr USB3 Port Replicator	Y4H06AA
	HP USB-C Universal Dock w/4.5mm Adapter	2UF95AA
	HP USB-C Universal Dock NF	3DV65AA
	HP USB-C Travel Dock	TOK29AA
Input/Output	HP Comfort Grip Wireless Mouse	H2L63AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP HDMI to VGA Adapter	H4F02AA
	HP Slim USB Keyboard & Mouse Bundle	T6T83AA#xxx
	HP USB Premium Mouse	1JR32AA
	HP Wireless Premium Mouse	1JR31AA
	HP Essential USB Mouse	2TX37AA#xxx
	HP USB Travel Mouse	G1K28AA
	HP Slim Bluetooth Mouse	F3J92AA#xxx
	HP Slim Wireless keyboard and mouse	T6L04AA#xxx
	HP USB-C to USB 3.0 Adapter	N2Z63AA#xxx
	HP USB-C to 3 and 4.5mm Adapter	N2Z65AA#xxx
	HP USB-C to RJ45 Adapter	V7W66AA#xxx
	HP Stereo USB Headset	T1A67AA
	HP Stereo 3.5mm Headset	T1A66AA
	HP Active Pen with Spare Tips	1FH00AA#xxx
	HP Active Pen Nib Set	3RV57AA
Power	HP 45W Smart AC Adapter 4.5mm	H6Y88AA#xxx
	HP 45W USB-C Power Adapter	1HE07AA#xxx
	HP 65W USB-C Power Adapter	1HE08AA#xxx
	HP Notebook Powerbank	N9F71AA#xxx
Storage	HP External USB Optical Drive	F2B56AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
Displays	HP ProDisplay P240VA 23.8-inch Monitor	N3H13AA
	HP ProDisplay P232 23-inch Monitor	K7X31AA
	HP EliteDisplay E243m 23.8-inch Collaboration Monitor	1FH48AA
	HP EliteDisplay E230t 23-Inch Touch Monitor	W2Z50AA
	HP EliteDisplay S14 14-inch USB-C Portable Monitor	3HX46AA



Summary of Changes

Date of change:	Version History:		Description of change:
April 15, 2019	V1 to V2	Added	Environmental tab and 10 touch points to display section
June 12, 2019	V2 to V3	Updated	EPEAT
September 10, 2019	V3 to V4	Updated	Longevity and Upgrading of Environmental section

Copyright © 2019 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Celeron and Pentium are trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

