

Overview

HP ProBook 430 G7 Notebook PC



Left

- | | |
|--|---|
| 1. Internal Microphones (2) | 7. SD Card Reader |
| 2. Webcam (Optional) | 8. Thermal Vent |
| 3. Privacy Shutter (Only available with webcam) | 9. USB 3.1 Gen 1 port |
| 4. Webcam LED | 10. Standard Security Lock Slot (Lock sold separately) |
| 5. Clickpad | 11. Power Button |
| 6. Hard Drive LED | |



Overview



Right

- | | |
|--|---|
| 1. Power Connector | 5. USB 3.1 Gen 1 Port |
| 2. USB Type-C™ 3.1 Gen 1 Port | 6. Headphone/Microphone Combo Jack |
| 3. Ethernet Port (RJ-45) | 7. HP Fingerprint Sensor (select models) |
| 4. HDMI Port (Cable not included) | |



Overview

At a Glance

- Preinstall Windows 10 or FreeDOS
- Choice of 10th generation Intel® Core™ i7, i5, i3 processors
- Display include your choice of 33.8 cm (13.3") diagonal HD, Ultra Wide Viewing Angle FHD, Touch or Non-Touch screen, And Privacy Panel option
- Integrated Intel® UHD Graphics, Premium
- Enhanced security features including TPM2.0, HP Sure Sense, HP Sure Start Gen5, HP BIOSphere, Hardware enforced Firmware Protection, optional Fingerprint Sensor⁴ (select models), optional IR camera, and optional Privacy Panel
- Passed 19 MIL-STD 810H testing¹
- Weight starting at 3.28 lbs (1.49 kgs)³
- HP Long-Life Rechargeable battery, with HP Fast Charge Technology recharges 50% in 30 minutes²
- Supports wireless LAN and wireless WAN options for connectivity on the go
- Up to 512 GB Solid State Drives or 1 TB Hard Drive
- Up to 32 GB total system memory
- 720p HD webcam, IR camera for face authentication with Windows Hello
- Spill-resistant and optional backlit Keyboard, and Clickpad with multi-touch gestures enabled, taps enabled as default

1. MIL STD 810H testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Damage under the MIL STD test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

3. Does not include power adapter.

4. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



Technical Specifications

PRODUCT NAME

HP ProBook 430 G7 Notebook PC

OPERATING SYSTEMS

Preinstalled

Windows 10 Pro 64¹
Windows 10 Pro 64 (National Academic only)²
Windows 10 Home 64¹
Windows 10 Home Single Language 64¹
Windows 10 Pro (Windows 10 Enterprise available with a Volume Licensing Agreement)¹
FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

PROCESSORS

Intel® Core™ i7-10510U processor with Intel® UHD Graphics, Premium (1.8 GHz base frequency, up to 4.9 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{3,4 5,6,7}

Intel® Core™ i5-10210U processor with Intel® UHD Graphics, Premium (1.6 GHz base frequency, up to 4.2 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)^{3,4 5,6,7}

Intel® Core™ i3-10110U processor with Intel® UHD Graphics, Premium (2.1 GHz base frequency, up to 4.1 GHz with Intel® Turbo Boost Technology, 4 MB L3 cache, 2 cores)^{3,4 5,6,7}

Processors Family

10th Generation Intel® Core™ i7 processor (i7-1050U)⁷

10th Generation Intel® Core™ i5 processor (i5-10210U)⁷

10th Generation Intel® Core™ i3 processor (i3-10110U)⁷

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

6. Max Boost clock frequency performance varies depending on hardware, software and overall system configuration.

7. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.



Technical Specifications

CHIPSET

Integrated with processor

GRAPHICS

Integrated

Intel® UHD Graphics, Premium⁸

Supports

Support HD decode, DX12, HDMI 1.4b

8. HD content required to view HD images.

DISPLAYS

Internal

Non-Touch

33.8 cm (13.3") diagonal HD SVA eDP anti-glare Ultraslim, 220 nits, 45% NTSC for two WLAN antennas

(1366 x 768)^{8,10}

33.8 cm (13.3") diagonal HD SVA eDP anti-glare Ultraslim, 220 nits, 45% NTSC for HD camera and two WLAN antennas

(1366 x 768)^{8,10}

33.8 cm (13.3") diagonal HD SVA eDP anti-glare Ultraslim, 220 nits, 45% NTSC for HD+IR camera and two WLAN antennas

(1366 x 768)^{8,10}

33.8 cm (13.3") diagonal HD SVA eDP anti-glare Ultraslim, 220 nits, 45% NTSC for HD camera, WWAN and two WLAN

antennas (1366 x 768)^{8,10}

33.8 cm (13.3") diagonal FHD IPS eDP anti-glare slim, 250 nits, 45% NTSC for HD camera and two WLAN antennas

(1920 x 1080)^{8,10}

33.8 cm (13.3") diagonal FHD IPS eDP anti-glare slim, 250 nits, 45% NTSC for HD+IR camera and two WLAN antennas

(1920 x 1080)^{8,10}

33.8 cm (13.3") diagonal FHD IPS eDP anti-glare slim, 250 nits, 45% NTSC for HD camera, WWAN and two WLAN antennas

(1920 x 1080)^{8,10}

33.8 cm (13.3") diagonal FHD IPS eDP + PSR anti-glare flat with HP Sure View Integrated Privacy Screen, 1000 nits, 72% NTSC for HD camera and two WLAN antennas (1920 x 1080)^{8,10,11*}

Touch

33.8 cm (13.3") diagonal HD SVA eDP ultraslim touch screen, 220 nits, 45% NTSC for HD camera and two WLAN antennas

(1366 x 768)^{8,9,10}

33.8 cm (13.3") diagonal FHD SVA eDP slim touch screen, 250 nits, 45% NTSC for HD camera and two WLAN antennas

(1920 x 1080)^{8,9,10}

33.8 cm (13.3") diagonal FHD SVA eDP slim touch screen, 250 nits, 45% NTSC for HD camera, WWAN and two WLAN

antennas (1920 x 1080)^{8,9,10}

HDMI

Supports resolutions up to 4K 30Hz

Display Size

13.3"

33.8 cm (13.3")

8. HD content required to view HD images.



Technical Specifications

9. Sold separately or as an optional feature.

10. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

11. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

*Touch-enabled display and Sure View privacy panel will lower actual brightness

Docking station model	Total number of supported displays (incl. the notebook display)	Max. resolutions supported	Dock Connectors	Technical limitations
HP Thunderbolt Dock 120W G2	3	Dual 4k @60Hz	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP USB-C Dock G4	3	Dual 2K @ 60Hz Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP USB-C Universal Dock	3	Dual 4K @ 60Hz Single 5K @ 60Hz	2xDP	
HP USB-C Travel Dock	2	Single 2K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 4K @ 30Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C/A Universal Dock G2	3	Dual 2.5K @ 60Hz	2xDP, 1xHDMI	
HP USB-C Dock G5	3	Dual 2.5K @ 60Hz or 4K @ 60Hz + FHD @ 60Hz	2xDP, 1xHDMI	

STORAGE AND DRIVES

Primary Storage

500 GB 7200 rpm SATA¹²

1 TB 5400 rpm SATA¹²

Primary M.2 Storage

128 GB M.2 SATA TLC Solid State Drive¹²

256 GB PCIe® NVMe™ M.2 Value Solid State Drive¹²

256 GB Intel® PCIe® NVMe™ QLC M.2 SSD with 16 GB Intel® Optane™ memory H10^{12,13,14}

512 GB PCIe® NVMe™ M.2 TLC Solid State Drive¹²

512 GB PCIe® NVMe™ M.2 Value Solid State Drive¹²

512 GB Intel® PCIe® NVMe™ QLC M.2 SSD with 32 GB Intel® Optane™ memory H10^{12,13,14}



Technical Specifications

12. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.
13. Intel® Optane™ memory system acceleration does not replace or increase the DRAM in your system. Requires 8th Gen or higher Intel® Core™ processor, BIOS version with Intel® Optane™ supported, Windows 10 64-bit, and an Intel® Rapid Storage Technology (Intel® RST) driver.
14. Intel® Optane™ memory H10 only for Intel® PCIe® NVMe™ QLC M.2 SSD.

NOTE: PCIe SSD not available for Celeron

MEMORY

Maximum Memory

32 GB DDR4-2666 SDRAM¹⁵

Memory

32 GB DDR4-2666 SDRAM (2 x 16 GB)¹⁵

16 GB DDR4-2666 SDRAM (1 x 16 GB)¹⁵

12 GB DDR4-2666 SDRAM (4 GB and 8 GB) (1 x 8 GB)¹⁵

8 GB DDR4-2666 SDRAM (1 x 8 GB)¹⁵

8 GB DDR4-2666 SDRAM (2 x 4 GB)¹⁵

4 GB DDR4-2666 SDRAM (1 x 4 GB)¹⁵

Memory Slots

2 SODIMM

Both slots are customer accessible / upgradeable

DDR4 PC4 SODIMMS (Comet Lake runs at 2666)

Supports Dual Channel Memory

15. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Realtek 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 5 Combo¹⁶

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 5 Combo, non-vPro™¹⁶

Intel® Dual Band Wi-Fi 6 AX201 802.11a/b/g/n/ac/ax (2x2) WLAN and Bluetooth® 5 Combo, non-vPro™¹⁶

WWAN

Intel® XMM™ 7360 LTE-Advanced (Cat9)¹⁷

Ethernet

Realtek 10/100/1000 GbE NIC¹⁸

16. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported. Wi-Fi® supporting gigabit speeds is achievable when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 160 MHz channels.



Technical Specifications

17. WWAN module is optional, must be configured at the factory and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

18. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers

Integrated microphone (Mono or Dual Array)

Speaker Power

2W/4ohm Per speaker

Camera

720p HD Camera⁸

720p HD Camera + IR Camera^{8,9}

8. HD content required to view HD images.

9. Sold separately or as an optional feature.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium Keyboard, spill resistant with optional backlit function

Pointing Device

Clickpad with multi-touch gesture support

Function Keys

ESC: system information

F1 - Display Switching

F2 - Blank or SureView On/Off

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute

F9 - Blank or Backlit Toggle

F10 - numlk

F11 - Wireless

F12 - Sleep

Hidden Function Keys

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock



Technical Specifications

SOFTWARE AND SECURITY

BIOS

HP BIOSphere Gen5¹⁹

HP Drive Lock & Automatic Drive Lock²⁰

BIOS Update via Network

Master Boot Record Security

Power On Authentication

Secure Erase²¹

Absolute Persistence Module²²

Pre-boot Authentication

Software

HP Connection Optimizer

HP Image Assistant

HP Hotkey Support

HP JumpStart

HP Support Assistant²³

HP Noise Cancellation Software

Buy Office (Sold separately)

Manageability Features

HP Driver Packs²⁴

HP System Software Manager (SSM)

HP BIOS Config Utility (BCU)

HP Client Catalog

HP Manageability Integration Kit Gen3²⁵

Client Security Software

HP Client Security Manager Gen5²⁶

HP Fingerprint Sensor (select models)²⁷

Windows Defender²⁸

Security Management

Pre-boot Authentication

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)

USB enable/disable (via BIOS)

Power-on password (via BIOS)

Setup password (via BIOS)

Support for chassis padlocks and cable lock devices

HP Sure Click²⁹

HP Sure Start Gen5³⁰



Technical Specifications

HP Sure Sense³¹

- 19. HP BIOSphere Gen5 is available on select HP Pro and Elite PCs. See product specifications for details. Features may vary depending on the platform and configurations.
- 20. HP Drive Lock & Automatic Drive Lock is not supported on NVMe drives
- 21. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.
- 22. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
- 23. HP Support Assistant requires Windows and Internet access.
- 24. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
- 25. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.
- 26. HP Client Security Manager Gen5 requires Windows and is available on the select HP Pro and Elite PCs. See product specifications for details.
- 27. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.
- 28. Windows Defender Opt in and internet connection required for updates.
- 29. HP Sure Click is available on select HP platforms and supports Microsoft® Internet Explorer, Google Chrome, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode. Check <http://h20195.www2.hp.com/v2/GetDocument.aspx?docname=4AA7-0922ENW> for all compatible platforms as they become available.
- 30. HP Sure Start Gen5 is available on select HP PCs with Intel processors. See product specifications for availability.
- 31. HP Sure Sense requires Windows 10. See product specifications for availability.

POWER

- HP Smart 65 W External AC power adapter³²
- HP Smart 65 W EM External AC power adapter³²
- HP Smart 65 W USB Type-C™ adapter³²
- HP Smart 45 W External AC power adapter³²
- HP Smart 45 W USB Type-C™ adapter³²

Primary Battery

HP Long Life 3-cell, 45 Wh Li-ion³³

Battery Life

Up to 15 hours and 15 minutes³⁴

Power Cord

- 3-wire plug - 1m³²
- 3-wire plug - 1.8m³²
- 2-wire plug - 1m³²
- Duckhead power cord- 1m³²
- Duckhead power cord- 1.8m³²



Technical Specifications

Battery Weight

0.49 lb

0.22 kg

32. Availability may vary by country.

33. Battery is internal and not replaceable by customer. Serviceable by warranty.

34. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.28 lbs (Non-touch); Starting at 3.7 lbs (Touch)³⁵

Starting at 1.49 kg (Non-touch); Starting at 1.68 kg (Touch)³⁵

Does not include power adapter.

Product Dimensions (w x d x h)

12.15 x 9.09 x 0.71 in

30.85 x 23.1 x 1.8 cm

35. Weight will vary by configuration.

PORTS/SLOTS

Ports

1 USB 3.1 Type-C™ Gen 1 (Power delivery, DisplayPort™)

1 USB 3.1 Gen 1

1 USB 3.1 Gen 1 (Powered port)

1 HDMI 1.4 b³⁶

1 RJ-45

1 AC power

1 Headphone/Microphone Combo Jack

1 Standard Security Lock

Expansion Slots

1 SD

Supports SD, SDHC, SDXC

36. HDMI cable sold separately.



Technical Specifications

SERVICE AND SUPPORT

HP Services offers 3-year and 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life Batteries which will have same 1-year or 3-year limited warranty as the platform. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.³⁷

37. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

ENVIRONMENTAL & INDUSTRY

Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none">• IT ECO declaration• US ENERGY STAR®• EPEAT® Gold registered in the United States. Based on US EPEAT registration according to IEEE 1680.1-2018 EPEAT. Status varies by country. See http://www.epeat.net for more information.		
System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.		
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	4.28 W	4.30 W	4.23 W
Normal Operation (Long idle)	2.89 W	2.41 W	3.02 W
Sleep	0.55 W	0.58 W	0.55 W
Off	0.29 W	0.31 W	0.28 W
	Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.		
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	15 BTU/hr	15 BTU/hr	15 BTU/hr
Normal Operation (Long idle)	10 BTU/hr	8 BTU/hr	10 BTU/hr
Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr
	Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.		
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)	Sound Pressure (L _{pAm} , decibels)	
Typically Configured – Idle	2.5	14	
Fixed Disk – Random writes	3.6	27	
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include: <ul style="list-style-type: none">• 3 USB ports• 1 PC card slot (type I/II)• 1 ExpressCard/54 slot• 1 IEEE 1394 Port• 2 SODIMM memory slots• Optional expansion base docking station• 1 multi-bay II storage port		



Technical Specifications

	<ul style="list-style-type: none"> • Interchangeable HDD <p>Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.</p>		
Batteries	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater than 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		
Additional Information	<ul style="list-style-type: none"> • This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. • This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. • This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). • This product is in compliance with the IEEE 1680.1 (EPEAT) standard at the <Silver> level, see www.epeat.net • Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043. • This product contains 10.1% post-consumer recycled plastic (by wt.) • This product is 96.7% recycle-able when properly disposed of at end of life. 		
Packaging Materials	External:	PAPER/Corrugated	230 g
		PAPER/Paper	51 g
	Internal:	PLASTIC/Polyethylene Expanded - EPE	62 g
		PLASTIC/Polyethylene low density - LDPE	9 g
Material Usage	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):</p> <ul style="list-style-type: none"> • Asbestos • Certain Azo Colorants • Certain Brominated Flame Retardants – may not be used as flame retardants in plastics • Cadmium • Chlorinated Hydrocarbons • Chlorinated Paraffins • Formaldehyde • Halogenated Diphenyl Methanes • Lead carbonates and sulfates • Lead and Lead compounds • Mercuric Oxide Batteries • Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. • Ozone Depleting Substances • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyl Ethers (PBBEs) • Polybrominated Biphenyl Oxides (PBBOs) 		



Technical Specifications

	<ul style="list-style-type: none"> • Polychlorinated Biphenyl (PCB) • Polychlorinated Terphenyls (PCT) • Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. • Radioactive Substances • Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
<i>Packaging Usage</i>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> • Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. • Eliminate the use of ozone-depleting substances (ODS) in packaging materials. • Design packaging materials for ease of disassembly. • Maximize the use of post-consumer recycled content materials in packaging materials. • Use readily recyclable packaging materials such as paper and corrugated materials. • Reduce size and weight of packages to improve transportation fuel efficiency. • Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
<i>End-of-life Management and Recycling</i>	<p>HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<i>HP Inc. Corporate Environmental Information</i>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</p> <p>Eco-label certifications http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</p> <p>ISO 14001 certificates: http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</p>



Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	Win 10
Integrated graphics	Yes
Max Operating Power	UMA < 45W

Temperature

Operating	32° to 95° F (0° to 35° C) (Not writing optical)
Non-operating	41° to 95° F (5° to 35° C) (Writing optical)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

Random Vibration

Operating	0.75 grms
Non-operating	1.50 grms

Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

Planned Industry Standard Certifications

UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR®	Selected models⁴⁰
EPEAT®	EPEAT® 2019 Gold in U.S.⁴¹
ICES	Yes
Australia	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes
UKRSERTCOMPUTER	Yes



Technical Specifications

40. Configurations of the HP ProBook 430 G7 that are ENERGY STAR® certified² are identified as HP ProBook 430 G7 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

41. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Panel LCD 13.3 inch diagonal FHD (1920 x 1080) Anti-Glare WLED UWVA 45% NTSC 250 nits eDP 1.2 w/o PSR slim NWBZ	Outline Dimensions (W x H x D) Active Area Weight Diagonal Size Thickness Interface Surface Treatment Touch Enabled Contrast Ratio Refresh Rate Brightness Pixel Resolution Backlight Format of LCD Pixel Arrangement Color Gamut Coverage Color Depth Viewing Angle	300.56 x 187.77 mm (max) (w/ PCB & w/o bracket) 293.76 x 165.24 mm (typ.) 260 g (max) 13.3 inch 3.0 mm (max) eDP 1.2 (2 lane) Anti-Glare No 600:1 (typ.) 60 Hz 250 nits (typ.) 1920 x 1080 (FHD) LED RGB 45% of NTSC 6 bits UWVA 85/85/85/85
---	--	--

Panel LCD 13.3 inch diagonal FHD (1920 x 1080) Anti-Glare WLED UWVA 45% NTSC 250 nits eDP 1.2 w/o PSR slim NWBZ	Outline Dimensions (W x H x D) Active Area Weight Diagonal Size Thickness Interface Surface Treatment Touch Enabled Contrast Ratio Refresh Rate Brightness Pixel Resolution Backlight Format of LCD Pixel Arrangement	300.56 x 187.77 mm (max) (w/ PCB & w/o bracket) 293.76 x 165.24 mm (typ.) 260 g (max) 13.3 inch 3.0 mm (max) eDP 1.2 (2 lane) Anti-Glare Yes 600:1 (typ.) 60 Hz 250 nits (typ.) 1920 x 1080 (FHD) LED RGB
---	--	--



Technical Specifications

Panel LCD 13.3 inch diagonal HD (1366 x 768) Anti-Glare WLED SVA 45% NTSC 220 nits eDP slim NB non-touch	Color Gamut Coverage	45% of NTSC
	Color Depth	6 bits
	Viewing Angle	UWVA 85/85/85/85
	Outline Dimensions (W x H x D)	300.56 x 187.77 max. (w/ PCB & w/o bracket)
	Active Area	293.83 x 165.20 typ.
	Weight	<260 max.
	Diagonal Size	13.3 (inch)
	Thickness	3.0 mm max.
	Interface	eDP 1.2 (2 lanes)
	Surface Treatment	Anti-glare
Panel LCD 13.3 inch diagonal HD (1366 x 768) Anti-Glare WLED SVA 45% NTSC 220 nits eDP slim NB	Touch Enabled	No
	Contrast Ratio	300:1 (typ)
	Refresh Rate	60 Hz
	Brightness	220 nits typical (Panel Only)
	Pixel Resolution	1366 x 768 (HD)
	Backlight	LED
	Format of LCD Pixel Arrangement	RGB
	Color Gamut Coverage	45% of NTSC
	Color Depth	6 bits (Hi FRC @ system GFX output 8bits)
	Viewing Angle	SVA 45/45/15/30
Panel LCD 13.3 inch diagonal HD (1366 x 768) Anti-Glare WLED SVA 45% NTSC 220 nits eDP slim NB	Outline Dimensions (W x H x D)	300.56 x 187.77 max. (w/ PCB & w/o bracket)
	Active Area	293.83 x 165.20 typ.
	Weight	<260 max.
	Diagonal Size	13.3 (inch)
	Thickness	3.0 mm max.
	Interface	eDP 1.2 (2 lanes)
	Surface Treatment	Anti-Glare
	Touch Enabled	Yes
	Contrast Ratio	300:1 (typ)
	Refresh Rate	60 Hz
Panel LCD 13.3 inch FHD (1920 x 1080) Anti-Glare WLED UWVA 72% NTSC 1000 nits eDP 1.4+PSR2 flat Privacy NWBZ	Brightness	220 nits typical (Panel Only)
	Pixel Resolution	1366 x 768 (HD)
	Backlight	LED
	Format of LCD Pixel Arrangement	RGB
	Color Gamut Coverage	45% of NTSC
	Color Depth	6 bits (Hi FRC @ system GFX output 8bits)
	Viewing Angle	SVA 45/45/15/30
	Outline Dimensions (W x H x D)	299.06 x 186.54 mm (max)
	Active Area	293.76 x 165.24 mm (typ.)
	Weight	255 g (max)
Panel LCD 13.3 inch FHD (1920 x 1080) Anti-Glare WLED UWVA 72% NTSC 1000 nits eDP 1.4+PSR2 flat Privacy NWBZ	Diagonal Size	13.3 inch



Technical Specifications

<i>Thickness</i>	3.0 mm (max)
<i>Interface</i>	eDP 1.4 + PSR2 (4 lane)
<i>Surface Treatment</i>	Anti-Glare
<i>Touch Enabled</i>	No
<i>Contrast Ratio</i>	2000:1 (typ.)
<i>Refresh Rate</i>	60 Hz
<i>Brightness*</i>	1000 nits
<i>Pixel Resolution</i>	1920 x 1080 (FHD)
<i>Backlight</i>	LED
<i>Format of LCD Pixel Arrangement</i>	RGB
<i>Color Gamut Coverage</i>	72% of NTSC
<i>Color Depth</i>	8 bit
<i>Viewing Angle</i>	UWVA 85/85/85/85

***Touch-enabled display and Sure View privacy panel will lower actual brightness**

STORAGE AND DRIVES

500 GB 7200 rpm SATA Hard Drive	<i>Drive Weight</i>	0.20 lbs (92 g) ~ 0.21 lbs (95 g)
	<i>Rotation speed</i>	7200 rpm
	<i>Cache Buffer</i>	Up to 32 MB
	<i>Height</i>	0.28 in (7 mm)
	<i>Width</i>	2.75 in (69.85 mm)
	<i>Interface</i>	ATA-8, SATA 3.0
	<i>Transfer Rate</i>	600 MB/s
	<i>Seek Time</i>	Single Track 2 ~ 1.5 ms; Average 11 ~ 13 ms; Maximum 18 ~ 22 ms
	<i>Logical Blocks</i>	976,773,168
	<i>Operating Temperature</i>	32° to 140° F (0° to 60° C) [top cover temp]
<i>Security Features</i>		ATA Security
<i>Features</i>		S.M.A.R.T., NCQ, Ultra DMA

1 TB 5400 rpm SATA Hard Drive	<i>Drive Weight</i>	0.21 lbs (94 g)
	<i>Rotation speed</i>	5400 rpm
	<i>Cache Buffer</i>	Up to 32 MB
	<i>Height</i>	0.28 in (7.2 mm)
	<i>Width</i>	2.75 in (69.85 mm)
	<i>Interface</i>	ATA-8, SATA 3.0
	<i>Transfer Rate</i>	600 MB/s
	<i>Seek Time</i>	Single Track 2 ms Average 12 ~ 13 ms Maximum 18 ~ 22 ms
	<i>Logical Blocks</i>	1,953,525,168



Technical Specifications

<i>Operating Temperature</i>	32° to 140° F (0° to 60° C) [top cover temp]
<i>Security Features</i>	ATA Security
<i>Features</i>	S.M.A.R.T., NCQ, Ultra DMA

SSD 128 GB 2280 M2 SATA-3 TLC	<i>Form Factor</i>	M.2 2280
	<i>Capacity</i>	128 GB
	<i>NAND Type</i>	TLC
	<i>Height</i>	0.09 in (2.3 mm)
	<i>Width</i>	0.87 in (22 mm)
	<i>Weight</i>	0.02 lb (10 g)
	<i>Interface</i>	ATA-8, SATA 3.0
	<i>Maximum Sequential Read</i>	Up To 520 MB/s
	<i>Maximum Sequential Write</i>	Up To 450 MB/s
	<i>Logical Blocks</i>	250,069,680
	<i>Operating Temperature</i>	32° to 158°F (0° to 70°C) [ambient temp]
	<i>Features</i>	DIPM; TRIM; DEVSLP

256 GB 2280 PCIe NVMe Value Solid State Drive	<i>Form Factor</i>	M.2 2280
	<i>Capacity</i>	256 GB
	<i>NAND Type</i>	TLC
	<i>Height</i>	0.09 in (2.3 mm)
	<i>Width</i>	0.87 in (22 mm)
	<i>Interface</i>	PCIe NVMe Gen3
	<i>Maximum Sequential Read</i>	Up To 1700 MB/s
	<i>Maximum Sequential Write</i>	Up to 1300 MB/s
	<i>Logical Blocks</i>	500,118,192
	<i>Operating Temperature</i>	32° to 158°F (0° to 70°C) [ambient temp]
	<i>Features</i>	TRIM; L1.2

512 GB 2280 M2 PCIe NVMe TLC Solid State Drive	<i>Form Factor</i>	M.2 2280
	<i>Capacity</i>	512 GB
	<i>NAND Type</i>	TLC
	<i>Height</i>	0.09 in (2.3 mm)
	<i>Width</i>	0.87 in (22 mm)
	<i>Interface</i>	PCIe NVMe Gen3X4
	<i>Maximum Sequential Read</i>	Up To 2600 MB/s
	<i>Maximum Sequential Write</i>	Up To 1400 MB/s
	<i>Logical Blocks</i>	1,000,215,216

**Not all configuration components are available in all regions/countries.
c06424515 — DA 16517 - Worldwide — Version 9 — May 26, 2020**



Technical Specifications

<i>Operating Temperature</i>	32° to 158°F (0° to 70°C) [ambient temp]
<i>Features</i>	TRIM; L1.2

<i>512 GB 2280 PCIe NVMe Value Solid State Drive</i>	<i>Form Factor</i>	M.2 2280
	<i>Capacity</i>	512 GB
	<i>NAND Type</i>	Value
	<i>Height</i>	0.09 in (2.3 mm)
	<i>Width</i>	0.87 in (22 mm)
	<i>Interface</i>	PCIe NVMe Gen3X4
	<i>Maximum Sequential Read</i>	Up To 1500 ~ 1700 MB/s
	<i>Logical Blocks</i>	1,000,215,216
	<i>Operating Temperature</i>	32° to 158°F (0° to 70°C) [ambient temp]
	<i>Features</i>	ATA Security, TRIM; L1.2

NETWORKING/COMMUNICATIONS

<i>Realtek RTL8822CE</i>	<i>Wireless LAN Standards</i>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
<i>802.11 a/b/g/n/ac (2 x 2)</i>		
<i>Wi-Fi® and Bluetooth® 5</i>		
	<i>Interoperability</i>	Wi-Fi® certified
	<i>Frequency Band</i>	• 802.11b/g/n 2.402 – 2.482 GHz • 802.11a/n/ac 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
	<i>Data Rates</i>	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz & 80MHz)
	<i>Modulation</i>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	<i>Security³</i>	• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only



Technical Specifications

	<ul style="list-style-type: none"> • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power ²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
Power Management	ACPI compliant power management 802.11 compliant power saving mode
Receiver Sensitivity ⁴	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard with CNVi Interface
Dimensions	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230: 2.8 g 2. Type 126: 1.3 g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)



Technical Specifications

LED Activity

LED Amber – Radio OFF
LED White – Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2/5.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate¹ 2.17 Mbps BLE: 1 Mbps signaling data rate¹ 0.2 Mbps 1. Actual throughput may vary.
Transmit Power	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Power Management Certifications	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

- 1. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices**
- 2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.**
- 3. Check latest software/driver release for updates on supported security features.**



Technical Specifications

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Intel® 9560 802.11a/b/g/n/ac (2 x 2) Wi-Fi® and Bluetooth® 5.0 Combo ¹ non-vPro	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi® certified
	Frequency Band	<ul style="list-style-type: none"> • 802.11b/g/n 2.402 – 2.482 GHz • 802.11a/n/ac 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
	Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	Security ³	<ul style="list-style-type: none"> • IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power ²	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum



Technical Specifications

<i>Power Consumption</i>	<ul style="list-style-type: none"> • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW 	
<i>Power Management</i>	ACPI compliant power management 802.11 compliant power saving mode	
<i>Receiver Sensitivity⁴</i>	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum	
<i>Antenna type</i>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications	
<i>Form Factor</i>	PCI-Express M.2 MiniCard with CNVi Interface	
<i>Dimensions</i>	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm	
<i>Weight</i>	1. Type 2230: 2.8 g 2. Type 126: 1.3 g	
<i>Operating Voltage</i>	3.3v +/- 9%	
<i>Temperature</i>	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
<i>Humidity</i>	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
<i>Altitude</i>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<i>LED Activity</i>	LED Amber – Radio OFF LED Off – Radio ON	

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

<i>Bluetooth Specification</i>	4.0/4.1/4.2/5.0 Compliant
<i>Frequency Band</i>	2402 to 2480 MHz
<i>Number of Available Channels</i>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<i>Signaling Data Rate</i>	Legacy: 3 Mbps signaling data rate ¹ 2.17 Mbps BLE: 1 Mbps signaling data rate ¹ 0.2 Mbps 1. Actual throughput may vary.
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)



Technical Specifications

<i>Transmit Power</i>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
<i>Power Consumption</i>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<i>Bluetooth Software Supported</i>	Microsoft Windows Bluetooth Software
<i>Power Management Certifications</i>	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<i>Power Management Certifications</i>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<i>Bluetooth Profiles Supported</i>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

- 1. Wireless access point and Internet service is required. Availability of public wireless access point is limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices**
- 2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.**
- 3. Check latest software/driver release for updates on supported security features.**
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).**

Intel® Wi-Fi 6 AX201 and Bluetooth® 5 (802.11 a/b/g/n/ac/ax 2 x 2, non-vPro, supporting gigabit file transfer speeds) non-vPro

IEEE 802.11a
IEEE 802.11b
IEEE 802.11g
IEEE 802.11n
IEEE 802.11ac
IEEE 802.11ax
IEEE 802.11d
IEEE 802.11e
IEEE 802.11h
IEEE 802.11i
IEEE 802.11k
IEEE 802.11r



Technical Specifications

<i>Interoperability</i>	IEEE 802.11v
<i>Frequency Band</i>	Wi-Fi® certified <ul style="list-style-type: none"> • 802.11b/g/n/ax 2.402 – 2.482 GHz • 802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
<i>Data Rates</i>	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz) • 802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
<i>Modulation</i>	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
<i>Security³</i>	<ul style="list-style-type: none"> • IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • WAPI
<i>Network Architecture</i>	Ad-hoc (Peer to Peer)
<i>Models</i>	Infrastructure (Access Point Required)
<i>Roaming</i>	IEEE 802.11 compliant roaming between access points
<i>Output Power²</i>	<ul style="list-style-type: none"> • 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum • 802.11n HT20(5GHz): +15.5dBm minimum • 802.11n HT40(5GHz): +14.5dBm minimum • 802.11ac VHT80(5GHz): +11.5dBm minimum • 802.11ac VHT160(5GHz): +11.5dBm minimum • 802.11ax HT40(2.4GHz): +10dBm minimum • 802.11ax VHT160(5GHz): +10dBm minimum
<i>Power Consumption</i>	<ul style="list-style-type: none"> • Transmit mode: 2.0 W • Receive mode: 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode: 50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
<i>Power Management</i>	ACPI compliant power management 802.11 compliant power saving mode
<i>Receiver Sensitivity⁴</i>	<ul style="list-style-type: none"> • 802.11b, 1Mbps: -93.5dBm maximum • 802.11b, 11Mbps: -84dBm maximum • 802.11a/g, 6Mbps: -86dBm maximum

Technical Specifications

	<ul style="list-style-type: none"> • 802.11a/g, 54Mbps: -72dBm maximum • 802.11n, MCS07: -67dBm maximum • 802.11n, MCS15: -64dBm maximum • 802.11ac, MCS0: -84dBm maximum • 802.11ac, MCS9: -59dBm maximum • 802.11ax, MCS11(HT40): -59dBm maximum • 802.11ax, MCS11(VHT160): -58.5dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure
Form Factor	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Dimensions	PCI-Express M.2 MiniCard with CNVi Interface
Weight	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Operating Voltage	1. Type 2230: 2.8 g 2. Type 126: 1.3 g
Temperature	3.3v +/- 9%
Humidity	Operating 14° to 158° F (–10° to 70° C) Non-operating –40° to 176° F (–40° to 80° C)
Altitude	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
LED Activity	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
	LED Amber – Radio OFF LED Off – Radio ON

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1 Wireless Technology

Bluetooth Specification	4.0/4.1/4.2/5.0/5.1 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ 2.17 Mbps BLE: 1 Mbps signaling data rate ¹ 0.2 Mbps 1. Actual throughput may vary.
Transmit Power	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.
Power Consumption	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950



Technical Specifications

Bluetooth Profiles Supported

UL, CSA, and CE Mark

BT4.1-ESR 5/6/7 Compliance
LE Link Layer Ping
LE Dual Mode
LE Link Layer
LE Low Duty Cycle Directed Advertising
LE L2CAP Connection Oriented Channels
Train Nudging & Interlaced Scan
BT4.2 ESR08 Compliance
LE Secure Connection- Basic/Full
LE Privacy 1.2 –Link Layer Privacy
LE Privacy 1.2 –Extended Scanner Filter Policies
LE Data Packet Length Extension
FAX Profile (FAX)
Basic Imaging Profile (BIP)2
Headset Profile (HSP)
Hands Free Profile (HFP)
Advanced Audio Distribution Profile (A2DP)

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported. Wi-Fi® supporting gigabit speeds is achievable when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 160 MHz channels.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Realtek RTK8111HSH
 10/100/1000 Integrated
 NIC

Connector
 System Interface
 Ethernet Features

RJ-45
PCIe + SMBus
10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)
100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)
1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)
Auto-Negotiation (Automatic Speed Selection)
Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
ACPI compliant – multiple power modes
Situation-sensitive features reduce power consumption
Advanced link down power saving for reducing link down power consumption
TCP/IP/UDP Checksum Offload (configurable)
Protocol Offload (ARP & NS)
Large send offload and Giant send offload
Receiving Side Scaling
Jumbo Frame 9K
Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)
PXE 2.1 Remote Boot

Power Management

Performance Features

Manageability



Technical Specifications

		Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status Auto MDI/MDIX Crossover cable detection
	<i>Management Interface</i>	
<hr/>		
Intel® XMM™ 7360 LTE-Advanced CAT9 ¹	Technology/Operating bands	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 1400 (Band 11), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1400 (Band 21), 850 (Band 26), 700 (Band 28), 700 (Band 29 RX only), 2300 (Band 30), 1700/2100 (Band 66). TDD LTE: 2600 (Band 38), 1900 (Band 39), 2400 (Band 40), 2500 (Band 41). HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8) MHz
	Wireless protocol standards	3GPP Release 11 LTE Specification CAT.9, DL 60MHz BW throughput up to 450Mbps; UL 20MHz throughput up to 50Mbps WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification
	GPS	Standalone, A-GPS (MS-A, MS-B)
	GPS bands	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	Maximum data rates	LTE: 450 Mbps (Download), 50 Mbps (Upload) DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload) HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)
	Maximum output power	LTE: 23 dBm HSPA+: 23.5 dBm
	Maximum power consumption	LTE: 1,200 mA (peak); 900 mA (average) HSPA+: 1,100 mA (peak); 800 mA (average)
	Form Factor	M.2, 3042-S3 Key B
	Weight	5.8 g
	Dimensions (Length x Width x Thickness)	42 x 30 x 2.3 mm
	1. WWAN module is optional, must be configured at the factory and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.	

POWER

HP 45 W Smart AC Adapter	Dimensions (H x W x D)	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)
	Weight	0.386 lb (175g) max Not including power cord. Power cord varies by country.
	Input	90 to 265 VAC
	Input Efficiency	87.74% at 115 V and 88.4% at 230 V



Technical Specifications

Output	Input frequency range	47 to 63 Hz
	Input AC current	1.4 A at 90 V
	Output power	45W
	DC output	19.5V
	Hold-up time	5 msec at 115 V input
	Output current limit	<8.0A
Connector	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords	
Environmental Design	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5,000 m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.	

HP 65 W Smart AC Adapter

Dimensions	90 x 51 x 28.5 mm	
Weight	220 g +/- 10 g Not including power cord. Power cord varies by country.	
Output	Input Efficiency	88.0 % at 115 V and 89.0 % at 230 V
	Input frequency range	47 to 63 Hz
	Input AC current	1.7 A at 90 VAC
	Output power	65 W
	DC output	19.5 V
	Hold-up time	5 ms at 115 VAC input
Connector	Output current limit	<11.0 A
	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords	
Environmental Design	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%



Technical Specifications

EMI and Safety Certifications

CE Mark - full compliance with LVD and EMC directives* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.

HP 65 W EM Smart AC adapter

Dimensions

102 x 55 x 30 mm

Weight

270 g +/- 10 g

Not including power cord. Power cord varies by country.

Input Efficiency **87% min at 115 V/230 V**

Input frequency range **47 to 63 Hz**

Input AC current **1.7 A at 90 V and maximum load**

DC output **65 W (19.5 V/3.33 A)**

Hold-up time **5 msec at 115 VAC input**

Output current limit **<11A, Over voltage protection- 29 V max automatic shutdown**

Connector

4.5 mm Barrel Type, 3 pin/grounded, mates with interchangeable cords

Environmental Design

Operating temperature **0° to 35° C**

Non-operating (storage) temperature **-4° F to 185° F (-20° to 85° C)**

Altitude **0 to 5,000 m**

Humidity **0% to 95%**

Storage Humidity **0% to 95%**

EMI and Safety Certifications

CE Mark - EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.

AC Adapter 65 Watt nPFC USB type C

Dimensions

74 x 74 x 28.5 mm

Weight

245 g +/- 10 g

Not including power cord. Power cord varies by country.

Input Efficiency **81.5% min at 115 Vac/ 230Vac @ 5V/3A
86.7% min at 115 Vac/ 230Vac @ 9V/3A
88% min at 115 Vac/ 230Vac @ 10V/5A
88% min at 115 Vac/ 230Vac @ 12V/5A
89% min at 115 Vac/ 230Vac @ 15V/4.33A
89% min at 115 Vac/ 230Vac @ 20V/3.25A**

Input frequency range **47 ~ 63 Hz**

Input AC current **1.7 A at 90 VAC and maximum load**

Output power **65 W**



Technical Specifications

	DC output	5V/9V/10V/12V/15V/20V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<8.0A
Connector	Type C	
Environmental Design	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	5% to 95%
	Storage Humidity	5% to 95%
EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.	

AC Adapter 45 Watt nPFC USB type C	Dimensions	62.0 x 62.0 x 28.5 mm
	Weight	220 g +/- 10 g Not including power cord. Power cord varies by country.
	Input Efficiency	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:5V : 81.5%9V : 86.7%10V : 87.5%12V : 87.8%15V : 87.8%20V : 87.8%
	Input frequency range	47 ~ 63Hz
	Input AC current	Max. 1.4 A at 90 Vac
	Output power	5V/15W 9V/27W 10V/37.5W 12V/45W 15V/45W 20V/45W
	DC output	5V / 9V / 10V / 12V / 15V / 20V
	Hold-up time	5ms at 115 Vac input
	Output current limit	<5.0A
Connector	Type C	
Environmental Design	Operating temperature	32°F to 95°F (0° to 35°C)
	Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
	Altitude	0 to 16,400 ft (0 to 5000m)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%



Technical Specifications

EMI and Safety Certifications

CE Mark - full compliance with LVD and EMC directives* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.

3 Cell WHr 45 Long Life - Polymer HP Fast Charge Technology¹

Dimensions	6.0. x 184.7 x 88.9 mm
Weight	0.22 kg (0.48 lb)
Cells/Type	3cell Lithium-Ion
Voltage	11.55 V
Amp-hour capacity	3.900 Ah
Watt-hour capacity	45 Wh
Operating (Charging)	32° to 113° F (0° to 45° C)
Operating (Discharging)	14° to 122° F (-10° to 60° C)
Optional Travel Battery Available	No

1. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

FINGERPRINT READER

Model	Synaptics Validity VFS7604 touch sensor
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	0~60°C
Current Consumption Image	100mA Max
Low Latency Wait for Finger	260 uA
ESD Resistance	IEC 61000-4-2 4B (+/-15KV)
Detection Matrix	363 dpi / 7.4 x 6 mm sensor area
FRR (False Reject Rate) / FAR (False Acceptance Rate)	FRR <1% @ 1:50K FAR

Country of Origin

China



Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part Number
Cases	HP Essential Top Load Case	H2W17AA
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP Essential Messenger Case (up to 17.3")	H1D25AA
Docking	HP USB-C Mini Dock	1PM64AA
	HP USB-C Universal Dock	1MK33AA
	HP USB-C Dock G4	3FF69AA
	HP Thunderbolt Dock 120W G2	2UK37AA
	HP TB Dock G2 w/ Combo Cable	3TR87AA
	HP TB Dock 120W G2 w/Audio	3YE87AA
	HP TB Dock 120W G2 Cable	3XB94AA
	HP TB Dock G2 Combo Cable	3XB96AA
	HP TB Dock G2 Audio Module	3AQ21AA
	HP USB-C/A Universal Dock G2	5TW13AA
	HP USB-C Dock G5	5TW10AA
	HP E223d Docking Monitor	5VT82A8/5VT82AA
	HP E243d Docking Monitor	1TJ76AA
	HP E273d Docking Monitor	5WN63A8 5WN63AA
	HP EliteDisplay E244d Monitor	6PA50A8/6PA50AA
	HP EliteDisplay E274d Monitor	6PA56A8/6PA56AA
Input/Output	HP USB Essential Keyboard and Mouse	H6L29AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP HDMI to DVI Adapter	F5A28AA
	HP Elite USB-C Hub	4WX89AA
	HP USB-C Travel Hub	Z9G82AA
Memory	4GB 2666MHz DDR4	4VN05AA
	8GB 2666MHz DDR4	4VN06AA
	16GB 2666MHz DDR4	4VN07AA
Power	HP 45W Smart AC Adapter 4.5mm	H6Y88AA
	45W Smart Power Adapter 2 prong -4.5mm (Japan only)	L6F60AA
	65W Smart Power Adapter (w/ 4.5mm to 7.5mm DC dongle)	H6Y89AA
	HP 65W Slim AC Adapter	H6Y82AA
	HP 65W USB-C Slim Power Adapter	3PN48AA
	HP 65W USB-C Power Adapter	1HE08AA
	HP 45W USB-C Power Adapter	1HE07AA



Options and Accessories (sold separately and availability may vary by country)

	HP Power Bank	N9F71AA#xxx
	HP USB-C Power Bank	2NA10AA#xxx
Storage	HP External USB Optical Drive	F2B56AA
	HP 128 GB M.2 SATA-3	2JB95AA
	1TB 7200rpm 9.5mm SATA HDD	L3M56AA
	HP 500GB 7200rpm HDD	F3B97AA
	HP 256GB TLC PCI-e 3x4 NVMe SSD (2280)	1FU87AA
	HP 512GB TLC PCI-e 3x4 NVMe SSD (2280)	1FU88AA
Security	HP Combination Lock	T0Y15AA
	HP Essential Keyed Cable lock 12.3mm	T0Y14AA
	HP Keyed Cable Lock 10mm	T1A62AA
UCC	HP Conferencing Keyboard	K8P74AA
	HP UC Speaker Phone	4VW02AA
	HP Wired Headset	K7V17AA



Summary of Changes

<i>Date of change:</i>	<i>Version History:</i>		<i>Description of change:</i>
October 30, 2019	V1 to V2	Updated	Battery Life
November 5, 2019	V2 to V3	Updated	UHD Graphics and added Environmental tab
February 12, 2020	V3 to V4	Added	HP Sure Sense
February 27, 2020	V4 to V5	Updated	Copyright and footnote for fingerprint sensor.
March 2, 2020	V5 to V6	Updated	Call out numbers, Webcam and Privacy Shutter
March 6, 2020	V6 to V7	Updated	Display Section
April 22, 2020	V7 to V8	Updated	Networking / Communications section
May 26, 2020	V8 to V9	Updated	Military Standards Information / Ethernet network

Copyright © 2020 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel®, Core® and Intel vPro™ are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.

