

### Overview

### HP ProBook 445 14 inch G10 Notebook PC



1. Internal Microphones (2)

2. Webcam LED (Optional)

3. HD or 5MP Camera

4. Camera Shutter (Only available with webcam)

5. IR Camera LED (Optional)

#### Left

6. Clickpad

7. SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1)

8. Ethernet Port (RJ-45)

9. Nano Security Lock Slot (Lock sold separately)

### Overview



- |   |   |
|---|---|
| <b>1.</b> Speakers  | <b>6.</b> SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1) |
| <b>2.</b> Power Button Key  | <b>7.</b> HDMI 2.1 Port (Cable not included)                              |
| <b>3.</b> Power Connector   | <b>8.</b> Audio Combo Jack  |
| <b>4.</b> SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) | <b>9.</b> Nano SIM Slot (Select models)                                   |
| <b>5.</b> SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1)                     | <b>10.</b> Touch Fingerprint Sensor (Select models)                       |

#### Right

### Overview

#### At a Glance

- Preinstalled with Windows 11 versions or FreeDOS
- Choice of AMD Barcelo™ 7000 series mobile processors, R7, R5 and R3
- Integrated AMD Radeon™ graphics
- Choice of 35.6 cm (14.0") diagonal HD, Ultra Wide Viewing Angle FHD, FHD Touch Screen and Low Blue Light option
- Choice of primary solid state drives up to 1TB, 2nd SSD 128GB/256GB (Optional)
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 32 GB
- Optimize your video calls with a 5MP+IR camera, HD camera and temporal noise reduction that adjusts to the lighting in your environment. New 5MP Camera (Optional) with HP Auto frame allows you around a little without losing viewers' attention.
- Supports wireless options for connectivity on the go including gigabit-speed up to Wi-Fi 6E and CAT16 4G/LTE WWAN (Optional)
- HP Wolf Security for business standard security including HP Sure Start, HP Sure Run, HP Sure Recover and HP Sure Click.
- Features redesigned quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Pass MIL-STD 810H tests<sup>1</sup>
- Battery options 42.75 Wh and 51.3 Wh
- Battery life up to 17 hours 45 minutes with the optional 51.3Whr battery
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support HP docking options including the HP Universal Dock G5
- Synchronized hinge allows the EliteBook to ProBook to open to 177° +/- 3° without lifting the keyboard and offers visibility from multiple angles.

1. MIL-STD 810GH is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

## Technical Specifications

### PRODUCT NAME

HP ProBook 445 14 inch G10 Notebook PC

### OPERATING SYSTEMS

#### Preinstalled

Windows 11 Pro <sup>1</sup>  
 Windows 11 Pro Education <sup>1</sup>  
 Windows 11 Home - HP recommends Windows 11 Pro for business <sup>1</sup>  
 Windows 11 Home Single Language - HP recommends Windows 11 Pro for business <sup>1</sup>  
 Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>  
 Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade) <sup>2</sup>  
 FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

2. This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

### PROCESSORS

| Processor <sup>3,4,5,6</sup> | Cores | Threads | L3 Cache | Max Boost Frequency <sup>5</sup> | Base Frequency |
|------------------------------|-------|---------|----------|----------------------------------|----------------|
| AMD Ryzen™ 7-7730U           | 8     | 16      | 16MB     | 4.50GHz                          | 2.00GHz        |
| AMD Ryzen™ 5-7530U           | 6     | 12      | 16MB     | 4.50GHz                          | 2.00GHz        |
| AMD Ryzen™ 3-7330U           | 4     | 8       | 8MB      | 4.30GHz                          | 2.30GHz        |

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. AMD Max Burst frequency performance varies depending on hardware, software and overall system configuration.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

### Technical Specifications

#### CHIPSET

Chipset is integrated with processor

#### GRAPHICS

##### Integrated

AMD Radeon™ Graphics <sup>7</sup>

##### Supports

Support HD decode, DX12, HDMI 2.1

[7.HD content required to view HD images.](#)

#### DISPLAY

##### Non-Touch

35.6 cm (14") diagonal FHD UWVA eDP anti-glare Low Blue Light, bent, 400 nits, 100% sRGB for 5MP + IR camera (1920 x 1080) with HP Eye Ease <sup>7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare Low Blue Light, bent, 400 nits, 100% sRGB for HD Webcam (1920 x 1080) with HP Eye Ease <sup>7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, bent, 250 nits, 45% NTSC for 5MP+IR camera (1920 x 1080) <sup>7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD camera for WWAN (1920 x 1080) <sup>7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD Webcam (1920 x 1080) <sup>7,8</sup>

35.6 cm (14") diagonal FHD UWVA eDP 1.2 w/o PSR anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1920 x 1080) <sup>7,8</sup>

35.6 cm (14") diagonal HD SVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD Webcam (1366 x 768) <sup>7,8</sup>

35.6 cm (14") diagonal HD SVA eDP 1.2 w/o PSR anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1366 x 768) <sup>7,8</sup>

##### Touch

35.6 cm (14") diagonal FHD UWVA eDP 1.2 w/o PSR anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD camera for WWAN Touch on Panel (1920 x 1080) <sup>7,8,9,10</sup>

35.6 cm (14") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD Webcam Touch on Panel (1920 x 1080) <sup>7,8,9,10</sup>

##### DisplayPort™ 1.4

Supports resolutions up to 4096 x 2304 @ 60Hz

##### Display Size (Diagonal)

14"

35.56 cm (14") Diagonal

[7. HD content required to view HD images.](#)

[8. HDMI cable sold separately](#)

[9. Resolutions are dependent upon monitor capability, and resolution and color depth settings.](#)

[10. Actual brightness will be lower with touchscreen or HP Sure View.](#)

## Technical Specifications

### DOCKING (Sold Separately)

|                                 |                              |
|---------------------------------|------------------------------|
| <b>Docking station model #1</b> | HP Thunderbolt 120W G4 Dock  |
| <b>Docking station model #2</b> | HP Thunderbolt 280W G4 Dock  |
| <b>Docking station model #3</b> | HP USB-C G5 Dock             |
| <b>Docking station model #4</b> | HP USB-C/A Universal G2 Dock |
| <b>Docking station model #5</b> | HP USB-C G5 Essential Dock   |

For additional aftermarket options and docking specs please see page 40.

### STORAGE AND DRIVES

#### Primary M.2 Storage

- 1 TB PCIe® Gen4x4 NVMe™ M.2 Solid State Drive <sup>11,13</sup>
- 512 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>11</sup>
- 256 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>11</sup>
- 128 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>11</sup>

#### Secondary M.2 Storage (Optional)

- 256 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>11,12</sup>
- 128 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>11,12</sup>

11. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

12. Secondary SSD slot (M.2 2230 form factor; Optional) is used for data storage only, not used for OS deployment.

13. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

### MEMORY

#### Maximum Memory

32 GB DDR4-3200 SDRAM <sup>14</sup>

#### Memory

- 32 GB DDR4-3200 SDRAM (2 x 16 GB) <sup>14</sup>
- 16 GB DDR4-3200 SDRAM (1 x 16 GB) <sup>14</sup>
- 16 GB DDR4-3200 SDRAM (2 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (1 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (2 x 4 GB) <sup>14</sup>
- 4 GB DDR4-3200 SDRAM (1 x 4 GB) <sup>14</sup>

#### Memory Slots

2 SODIMM

Both slots are accessible / upgradeable by IT or self-maintainers only.

DDR4 PC4 SODIMMS, system runs at 3200

Supports Dual Channel Memory

14. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

### Technical Specifications

---

#### NETWORKING/COMMUNICATIONS

##### WLAN

Realtek 8852CE Wi-Fi 6E + Bluetooth® 5.3 M.2 2230 PCI-e+USB WW WLAN Wireless Card <sup>15</sup>  
Mediatek RZ616 Wi-Fi 6E + Bluetooth® 5.3 M.2 2230 PCI-e+USB WW WLAN Wireless Card <sup>15</sup>

##### WWAN

Intel® XMM™ 7560 R+ LTE-Advanced Pro WWAN <sup>16</sup>

##### Miracast

Native Miracast Support <sup>17</sup>

##### Ethernet

Realtek RTL8111HSH 10/100/1000 Integrated NIC <sup>18</sup>

15. Wi-Fi 6E requires a Wi-Fi 6E router, and Windows 11, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

16. WWAN module is an optional feature, requires factory configuration and requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

17. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

18. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

---

#### AUDIO/MULTIMEDIA

##### Audio

2 Integrated stereo speakers  
Integrated microphone (Dual Array)

##### Speaker Power

2W/4ohm per speaker

##### Camera

Dual Array Digital Microphone HD USB2 Wide Field of View Integrated Camera <sup>7</sup>  
Dual Array Digital Microphone 5MP USB2 Infrared Wide Field of View Integrated Camera <sup>19</sup>  
5 MP + IR camera for face authentication with Windows Hello

7. HD content required to view HD images.

19. Sold separately or as an optional feature.

### Technical Specifications

#### **KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS**

##### **Keyboard**

HP Premium Keyboard, full-size, spill resistant and optional Durakeys and backlit

##### **Pointing Device**

Clickpad with multi-touch gesture support

##### **Function Keys**

F1 - Display Switching

F2 - Blank or SureView On/Off

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute

F9 - Blank or Backlit Toggle

F10 - Insert

F11 - Wireless

F12 - Programmable key

##### **Hidden Function Keys**

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock

---



### Technical Specifications

#### SOFTWARE AND SECURITY

##### Preinstalled Software

###### Software

HP Quick Drop <sup>20</sup>  
HP PC Hardware Diagnostics Windows  
myHP  
HP Smart Support [download] <sup>21</sup>  
HP Services Scan<sup>22</sup>  
HP Connection Optimizer  
HP Hotkey Support  
HP Support Assistant <sup>23</sup>  
HP Notifications  
HP Privacy Settings  
HP Power Manager <sup>24</sup>  
Buy Microsoft Office (Sold separately)

##### Manageability Features

HP Image Assistant Gen5 (download)  
HP Manageability Integration Kit (download) <sup>25</sup>  
HP Client Management Script Library (download)  
HP Driver Packs (download)  
HP Cloud Recovery <sup>26</sup>  
HP Client Catalog (download)  
HP Connect<sup>27</sup>

##### Security Management

HP Wolf Security of Business <sup>28</sup> includes:  
HP Sure Click <sup>29</sup>  
HP Sure Sense <sup>30</sup>  
HP Sure Run Gen5 <sup>31</sup>  
HP Sure Recover Gen5 <sup>32</sup>  
HP Sure Start Gen6 <sup>33</sup>  
HP Tamper Lock  
HP Sure Admin <sup>34</sup>  
HP Client Security Manager Gen7 <sup>35</sup>

##### BIOS

HP BIOSphere Gen6 <sup>36</sup>  
HP Secure Erase <sup>37</sup>  
Absolute Persistence Module <sup>38</sup>  
HP DriveLock & Automatic DriveLock  
BIOS Update via Network  
HP Wake on WLAN  
HP Fingerprint Sensor <sup>39</sup>  
Secured-Core PC Enable<sup>40</sup>  
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

##### IPv6 Support

Yes

## Technical Specifications

**FirstNet Certified:**

Yes

**The BIOS on this notebook implements ISO/IEC 19678:2015 guidelines (formerly NIST 800-147).**

UEFI version: 2.7

Class: Class 3

20. HP Quick Drop requires Internet access and Windows 10 or higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

21. HP Smart Support automatically collects the telemetry necessary upon initial boot of the product to deliver device-level configuration data and health insights and is available preinstalled on select products, thru HP Factory Configuration Services; or it can be downloaded. For more information about how to enable HP Smart Support or for download, please visit <http://www.hp.com/smart-support>.

22. HP Services Scan is provided with Windows Update on select products and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. HP TechPulse is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements or to disable this feature, please visit <http://www.hpdaas.com/requirements>. Not applicable in China.

23. HP Support Assistance requires Windows and Internet Access

24. HP Power Manager requires Windows 10 and higher and can be downloaded from the Microsoft Store

25. HP Manageability Integration Kit can be downloaded from

<http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.

26. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, wired network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/document/c05115630>.

27. HP Connect is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.

28. HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.

29. HP Sure Click requires Windows 10 Pro or higher or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

30. HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.

31. HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.

32. HP Sure Recover Gen5 with Embedded Reimaging is an optional feature which requires Windows 10 and higher must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module

33. HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher

34. HP Sure Admin requires Windows 10 or higher, HP BIOS, HP Manageability Integration Kit from

<http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store

35. HP Client Security Manager Gen7 requires Windows and is available on the select HP Elite and Pro PCs.

36. HP BIOSphere Gen6 features may vary depending on the platform and configuration.

37. HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

38. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited,

## Technical Specifications

check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit:

<https://www.absolute.com/about/legal/agreements/absolute/>

39. HP Fingerprint sensor is an optional feature that must be configured at purchase.

40. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.

## POWER

### Power Supply

AC Adapter 45 Watt nPFC Standard USB Type C® Straight 1.8m <sup>41</sup>

AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>41</sup>

AC Adapter 45 Watt Smart nPFC Standard C8 for 2 prong Barrel 4.5mm Right Angle <sup>41</sup>

AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m <sup>41</sup>

AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm <sup>41</sup>

AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m <sup>41</sup>

### Battery

HP Long Life 3-cell, 42.75 Wh polymer <sup>42,43</sup>

HP Long Life 3-cell, 51.3 Wh polymer <sup>42,43</sup>

### Power Cord

3-wire plug - 1m

2-wire plug - 1m

### Battery Life

Up to 14 hours 15 minutes with 42.75Whr battery (HP Long Life 3-Cell, 42.75Whr Polymer, UMA graphics, AMD R7, display set to 200 nits, 2\*4G memory, 256G SSD) <sup>44</sup>

Up to 17 hours 45 minutes with 51.3Whr battery (HP Long Life 3-Cell, 51.3Whr Polymer, UMA graphics, AMD R7, display set to 200 nits, 2\*4G memory, 256G SSD) <sup>44</sup>

### Battery Weight

HP Long Life 3-cell - 42.75 Wh Polymer - .40 lb

HP Long Life 3-cell - 51.3 Wh Polymer - .45 lb

HP Long Life 3-cell - 42.75 Wh Polymer - 181.83 g

HP Long Life 3-cell - 51.3 Wh Polymer - 203.56 g

41. Availability may vary by country.

42. Battery is internal and not replaceable by customer. Serviceable by warranty.

43. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

44. Windows MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

### Technical Specifications

#### WEIGHTS & DIMENSIONS

**Product Weight - 42.75 Wh**

Starting at 3.05 lb <sup>45</sup>

Starting at 1.385 kg<sup>45</sup>

**Product Weight - 51.3 Wh**

Starting at 3.10 lb <sup>45</sup>

Starting at 1.405 kg <sup>45</sup>

**Product Dimensions (W x D x H)**

12.67 x 8.42 x 0.78 in

32.19 x 21.39 x 1.99 cm

**Packaging Dimensions (W x D x H) <sup>46</sup>**

12"-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

45. Weight will vary by configuration. Does not include power adapter.

46. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details.

---

#### PORTS/SLOTS

1 SuperSpeed USB Type-C<sup>®</sup> 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

3 SuperSpeed USB Type-A 5Gbps signaling rate port (USB 3.2 Gen 1)

1 HDMI 2.1 <sup>47</sup>

1 RJ-45

1 Headphone/microphone combo jack

1 AC power

1 Nano SIM slot for WWAN (optional)

47. HDMI cable sold separately

---

### Technical Specifications

#### **SERVICE AND SUPPORT**

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for HP Long Life batteries which will follow the one or three year warranty of the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>48</sup>

48. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit [www.hp.com/go/cpc](http://www.hp.com/go/cpc). HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---

## Technical Specifications

### SYSTEM UNIT

#### Stand-Alone Power Requirements

##### (AC Power)

|                           |                              |
|---------------------------|------------------------------|
| Nominal Operating Voltage | 19V                          |
| Average Operating Power   | 7.52W (Idle)                 |
| Integrated graphics       | Yes (AMD Radeon™ Graphics)   |
| Discrete Graphics         | N/A                          |
| Max Operating Power       | Discrete < 65W<br>UMA < 45W" |

#### Temperature

|               |                               |
|---------------|-------------------------------|
| Operating     | 32° to 95° F (0° to 35° C)    |
| Non-operating | -4° to 140° F (-20° to 60° C) |

#### Relative Humidity

|               |  |
|---------------|--|
| Operating     | 10% to 90%, non-condensing                                 |
| Non-operating | 5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature |

#### Shock

|               |                        |
|---------------|------------------------|
| Operating     | 40 G, 2 ms, half-sine  |
| Non-operating | 200 G, 2 ms, half-sine |

#### Random Vibration

|               |             |
|---------------|-------------|
| Operating     | 1.043 grams |
| Non-operating | 3.5 grams   |

#### Altitude (unpressurized)

|               |                                       |
|---------------|---------------------------------------|
| Operating     | -50 to 10,000 ft (-15.24 to 3,048 m)  |
| Non-operating | -50 to 40,000 ft (-15.24 to 12,192 m) |

#### Planned Industry Standard

##### Certifications

|                          |  |
|--------------------------|--|
| Regulatory Model Number  | HSN-Q34C-4   |
| CSA/UL 62368-1           | Yes  |
| ENERGY STAR®             | Yes <sup>49</sup>  |
| EPEAT®                   | EPEAT® Gold in the United States <sup>50</sup>           |
| FCC/ICES/CISPR/VCCI      | Yes  |
| CE MARKING               | Yes  |
| GS Mark                  | Yes  |
|                          | Related commodity should comply with ISO 9241 Standards. |
| China CCC/SRRC           | Yes  |
| Taiwan BSMI/NCC          |  |
| Korea KCC/KC/KES         | Yes  |
| Ukraine NSoC/TEC         | Yes  |
| EAEU Compliance          | Yes  |
| Saudi Arabian Compliance | Yes  |
| TCO                      | Yes  |
| Low Blue Light           | Yes  |
| WW RoHS                  | Yes  |

### Technical Specifications

49. Configurations of the HP ProBook 445 14 inch G10 Notebook PC that are ENERGY STAR® qualified are identified as HP ProBook 445 14 inch G10 Notebook PC ENERGY STAR on HP websites and on <http://www.energystar.gov>.

50. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

#### DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

**NOTE:** All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

|   |   |   |
|---|---|---|
| <b>Panel LCD 14 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent Touch on Panel NWBZ</b> | <b>Outline Dimensions (W x H x D)</b>                       | 316.170 x 186.400 mm (max) (w/ PCB)               |
|   | <b>Active Area</b>  | 309.370 x 174.020 mm (typ.)                       |
|   | <b>Weight</b>   | 305 g (max)                                       |
|   | <b>Diagonal Size</b>  | 14.0 (inch)                                       |
|   | <b>Surface Treatment</b>                                    | Anti-Glare On-cell                                |
|   | <b>Touch Enabled</b>  | Yes <sup>1</sup>                                  |
|   | <b>Contrast Ratio</b>                                       | 600:1 (typ.)                                      |
|   | <b>Refresh Rate</b>   | 60 Hz   |
|   | <b>Brightness</b>   | 250 nits  |
|   | <b>Pixel Resolution - Format</b>                            | 1920 x 1080 (FHD)                                 |
|   | <b>Backlight</b>  | LED   |
|   | <b>Pixel Resolution</b>                                     | RGB Stripe  |
|   | <b>Color Gamut Coverage</b>                                 | NTSC 45%  |
|   | <b>Color Depth</b>  | 6 bits (Hi FRC supportive w/ condition to enable) |
|   | <b>Viewing Angle</b>  | UWVA 85/85/85/85                                  |
|   | <b>Low Blue Light</b>                                       | No  |
|   | <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.3W max./2.8W max.                               |

|   |                                   |                    |
|---|-----------------------------------|--------------------|
| <b>14.0 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2X 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel</b> | <b>Outline Dimensions (W x H)</b> | 315.10 x 184.90 mm |
|   | <b>Active Area</b>                | 309.37 x 174.02 mm |
|   | <b>Weight</b>                     | 230g max           |
|   | <b>Diagonal Size</b>              | 14                 |
|   | <b>Surface Treatment</b>          | Anti-Glare         |
|   | <b>Touch Enabled</b>              | No                 |
|   | <b>Contrast Ratio</b>             | 1200:1 (typ)       |
|   | <b>Refresh Rate</b>               | 60Hz               |
|   | <b>Brightness</b>                 | 400 (typ)          |
|   | <b>Pixel Resolution - Format</b>  | 1920 x 1080 (FHD)  |
|   | <b>Backlight</b>                  | WLED               |
|   | <b>Pixel Resolution</b>           | RGB                |

### Technical Specifications

|   |                      |
|---|----------------------|
| <b>Color Gamut Coverage</b>                                 | sRGB100%             |
| <b>Color Depth</b>  | 8 bits               |
| <b>Viewing Angle</b>  | UWVA 89/89/89/89     |
| <b>Low Blue Light</b>                                       | Yes                  |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 1.23 W max/1.5 W max |

|  |                                   |   |
|--|-----------------------------------|---|
| <b>Panel LCD 14-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent</b> | <b>Outline Dimensions (W x H)</b> | 316.170 x 186.400 mm (max) (w/ PCB)               |
|  | <b>Active Area</b>                | 309.370 x 174.020 mm (typ.)                       |
|  | <b>Weight</b>                     | 300 g (max)                                       |
|  | <b>Diagonal Size</b>              | 14.0 (inch)                                       |
|  | <b>Surface Treatment</b>          | Anti-Glare  |
|  | <b>Touch Enabled</b>              | No  |
|  | <b>Contrast Ratio</b>             | 600:1 (typ.)                                      |
|  | <b>Refresh Rate</b>               | 60 Hz   |
|  | <b>Brightness</b>                 | 250 nits  |
|  | <b>Pixel Resolution - Format</b>  | 1920 x 1080 (FHD)                                 |
|  | <b>Backlight</b>                  | LED   |
|  | <b>Pixel Resolution</b>           | RGB Stripe  |
|  | <b>Color Gamut Coverage</b>       | NTSC 45%  |
|  | <b>Color Depth</b>                | 6 bits (Hi FRC supportive w/ condition to enable) |
| <b>Viewing Angle</b>   | UWVA 85/85/85/85                  |   |
| <b>Low Blue Light</b>  | No                                |   |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b>  | 2.205W Max/2.716W Max             |   |

|   |                                   |                             |
|---|-----------------------------------|-----------------------------|
| <b>Panel LCD 14-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ bent</b> | <b>Outline Dimensions (W x H)</b> | 316.110 x 186.370 mm (max)  |
|   | <b>Active Area</b>                | 309.400 x 173.950 mm (typ.) |
|   | <b>Weight</b>                     | 300 g (max)                 |
|   | <b>Diagonal Size</b>              | 14.0 (inch)                 |
|   | <b>Surface Treatment</b>          | Anti-Glare                  |
|   | <b>Touch Enabled</b>              | No                          |
|   | <b>Contrast Ratio</b>             | 300:1 (typ.)                |
|   | <b>Refresh Rate</b>               | 60 Hz                       |
|   | <b>Brightness</b>                 | 250 nits                    |
|   | <b>Pixel Resolution - Format</b>  | 1366 x 768 (HD)             |
|   | <b>Backlight</b>                  | LED                         |
|   | <b>Pixel Resolution</b>           | RGB Stripe                  |
|   | <b>Color Gamut Coverage</b>       | NTSC 45%                    |



### Technical Specifications

|   |                        |
|---|------------------------|
| <b>Color Depth</b>  | 6 bits                 |
| <b>Viewing Angle</b>  | SVA 45/45/15/35        |
| <b>Low Blue Light</b>                                       | No                     |
| <b>Power Consumption (W, EBL@ 150nits max/ 200nits max)</b> | 2.52W max./ 2.86W max. |

---

### Technical Specifications

#### STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

|                                       |                                 |                    |
|---------------------------------------|---------------------------------|--------------------|
| <b>SSD 128GB 2230 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2230           |
|                                       | <b>Capacity</b>                 | 128GB              |
|                                       | <b>NAND Type</b>                | QLC                |
|                                       | <b>Interface</b>                | PCIe NVMe          |
|                                       | <b>Minimum Sequential Read</b>  | 2000 MB/s ± 10%    |
|                                       | <b>Minimum Sequential Write</b> | 600 MB/s ± 10%     |
|                                       | <b>Logical Blocks</b>           | 250,069,680        |
|                                       | <b>Features</b>                 | Pyrite; TRIM; L1.2 |

|                                       |                                 |                    |
|---------------------------------------|---------------------------------|--------------------|
| <b>SSD 256GB 2230 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2230           |
|                                       | <b>Capacity</b>                 | 256 GB             |
|                                       | <b>NAND Type</b>                | QLC                |
|                                       | <b>Interface</b>                | PCIe NVMe          |
|                                       | <b>Minimum Sequential Read</b>  | 2000 MB/s ± 10%    |
|                                       | <b>Minimum Sequential Write</b> | 900 MB/s ± 10%     |
|                                       | <b>Logical Blocks</b>           | 500,118,192        |
|                                       | <b>Features</b>                 | Pyrite; TRIM; L1.2 |

|                                       |                                 |                    |
|---------------------------------------|---------------------------------|--------------------|
| <b>SSD 256GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280           |
|                                       | <b>Capacity</b>                 | 256GB              |
|                                       | <b>NAND Type</b>                | QLC                |
|                                       | <b>Interface</b>                | PCIe NVMe          |
|                                       | <b>Minimum Sequential Read</b>  | 2000 MB/s ± 10%    |
|                                       | <b>Minimum Sequential Write</b> | 900 MB/s ± 10%     |
|                                       | <b>Logical Blocks</b>           | 500,118,192        |
|                                       | <b>Features</b>                 | Pyrite; TRIM; L1.2 |

|                                       |                                 |                    |
|---------------------------------------|---------------------------------|--------------------|
| <b>SSD 512GB 2280 PCIe NVMe Value</b> | <b>Form Factor</b>              | M.2 2280           |
|                                       | <b>Capacity</b>                 | 512GB              |
|                                       | <b>NAND Type</b>                | QLC                |
|                                       | <b>Interface</b>                | PCIe NVMe          |
|                                       | <b>Minimum Sequential Read</b>  | 2200 MB/s ± 10%    |
|                                       | <b>Minimum Sequential Write</b> | 1000 MB/s ± 10%    |
|                                       | <b>Logical Blocks</b>           | 1,000,215,216      |
|                                       | <b>Features</b>                 | Pyrite; TRIM; L1.2 |

### Technical Specifications

|  |                                 |                        |
|--|---------------------------------|------------------------|
| <b>SSD 1 TB 2280 PCIe NVMe Value<sup>1</sup></b> | <b>Form Factor</b>              | M.2 2280               |
|  | <b>Capacity</b>                 | 1TB                    |
|  | <b>NAND Type</b>                | TLC                    |
|  | <b>Interface</b>                | PCIe NVMe Gen4X4       |
|  | <b>Minimum Sequential Read</b>  | 3200 MB/s ± 10%        |
|  | <b>Minimum Sequential Write</b> | 2700 MB/s ± 10%        |
|  | <b>Logical Blocks</b>           | 2,000,409,264          |
|  | <b>Features</b>                 | Pyrite 2.0; TRIM; L1.2 |

1. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).

## Technical Specifications

## NETWORKING/COMMUNICATIONS

|  |  |   |
|--|--|---|
| <b>Realtek RTL8852CE<br/>802.11ax 2x2 Wi-Fi 6E +<br/>Bluetooth® 5.3 Wireless<br/>Card (802.11ax 2x2,<br/>supporting gigabit data<br/>rate)<sup>1</sup></b> | <b>Wireless LAN Standards</b>          | IEEE 802.11a<br>IEEE 802.11b<br>IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.11ac<br>IEEE 802.11ax<br>IEEE 802.11d<br>IEEE 802.11e<br>IEEE 802.11h<br>IEEE 802.11i<br>IEEE 802.11k  |
|  | <b>Interoperability</b>                | Wi-Fi certified   |
|  | <b>Frequency Band</b>                  | <ul style="list-style-type: none"> <li>•802.11b/g/n/ax<br/>2.402 – 2.482 GHz</li> <li>•802.11a/n/ac/ax<br/>5.15 – 5.25 GHz<br/>5.25 – 5.35 GHz<br/>5.47 – 5.725 GHz<br/>5.825 – 5.850 GHz</li> </ul>  |
|  | <b>Data Rates</b>                      | <ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz &amp; 160MHz)</li> <li>• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz &amp; 160MHz)</li> </ul>                               |
|  | <b>Modulation</b>                      | Direct Sequence Spread Spectrum<br>OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM  |
|  | <b>Security<sup>2</sup></b>            | <ul style="list-style-type: none"> <li>• IEEE and Wi-Fi certified 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 (personal) certification</li> <li>• WPA3-Enterprise</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> <li>• EAP</li> </ul> |
|  | <b>Network Architecture<br/>Models</b> | Ad-hoc (Peer to Peer)<br>Infrastructure (Access Point Required)   |
|  | <b>Roaming</b>                         | IEEE 802.11 compliant roaming between access points   |
|  | <b>Output Power<sup>3</sup></b>        | <ul style="list-style-type: none"> <li>• 802.11b : +17dBm minimum</li> <li>• 802.11g : +16dBm minimum</li> <li>• 802.11a : +17dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> </ul>   |

### Technical Specifications

|   |   |                  |                               |                      |                                |
|---|---|------------------|-------------------------------|----------------------|--------------------------------|
|   | <ul style="list-style-type: none"> <li>• 802.11n HT40(5GHz) : +13dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE40(2.4GHz) : +12dBm minimum</li> <li>• 802.11ax HE80(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(5GHz) : +10dBm minimum</li> <li>• 802.11ax HE80(6GHz) : +10dBm minimum</li> <li>• 802.11ax HE160(6GHz) : +10dBm minimum</li> </ul>  |                  |                               |                      |                                |
| <b>Power Consumption</b>                | <ul style="list-style-type: none"> <li>• Transmit mode :2.5 W</li> <li>• Receive mode :2 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode :50 mW (WLAN unassociated)</li> <li>• Connected Standby/Modern Standby: 10mW</li> <li>• Radio disabled: 8 mW</li> </ul>   |                  |                               |                      |                                |
| <b>Power Management</b>                 | ACPI and PCI Express compliant power management<br>802.11 compliant power saving mode   |                  |                               |                      |                                |
| <b>Receiver Sensitivity<sup>4</sup></b> | <ul style="list-style-type: none"> <li>•802.11b, 1Mbps : -93.5dBm maximum</li> <li>•802.11b, 11Mbps : -84dBm maximum</li> <li>•802.11a/g, 6Mbps : -86dBm maximum</li> <li>•802.11a/g, 54Mbps : -72dBm maximum</li> <li>•802.11n, MCS07 : -67dBm maximum</li> <li>•802.11n, MCS15 : -64dBm maximum</li> <li>•802.11ac, MCS0(VHT80) : -84dBm maximum</li> <li>•802.11ac, MCS9(VHT80) : -59dBm maximum</li> <li>•802.11ac, MCS9(VHT160) : -58.5dBm maximum</li> <li>•802.11ax, MCS11(HE40): -57dBm maximum</li> <li>•802.11ax, MCS11(HE80): -54dBm maximum</li> <li>•802.11ax, MCS11(HE160): -53.5dBm maximum</li> </ul> |                  |                               |                      |                                |
| <b>Antenna type</b>                     | High efficiency antenna with spatial diversity, mounted in the display enclosure<br>Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications   |                  |                               |                      |                                |
| <b>Form Factor</b>                      | PCI-Express M.2 MiniCard  |                  |                               |                      |                                |
| <b>Dimensions</b>                       | <ol style="list-style-type: none"> <li>1. Type 2230 : 2.3 x 22.0 x 30.0 mm</li> <li>2. Type 1216: 1.67 x 12.0 x 16.0 mm</li> </ol>  |                  |                               |                      |                                |
| <b>Weight</b>                           | <ol style="list-style-type: none"> <li>1. Type 2230 : 2.8g</li> <li>2. Type 126: 1.3g</li> </ol>  |                  |                               |                      |                                |
| <b>Operating Voltage</b>                | 3.3v +/- 9%   |                  |                               |                      |                                |
| <b>Temperature</b>                      | <table border="0"> <tr> <td><b>Operating</b></td> <td>14° to 158° F (-10° to 70° C)</td> </tr> <tr> <td><b>Non-operating</b></td> <td>-40° to 176° F (-40° to 80° C)</td> </tr> </table>  | <b>Operating</b> | 14° to 158° F (-10° to 70° C) | <b>Non-operating</b> | -40° to 176° F (-40° to 80° C) |
| <b>Operating</b>                        | 14° to 158° F (-10° to 70° C)   |                  |                               |                      |                                |
| <b>Non-operating</b>                    | -40° to 176° F (-40° to 80° C)  |                  |                               |                      |                                |
| <b>Humidity</b>                         | <table border="0"> <tr> <td><b>Operating</b></td> <td>10% to 60% (non-condensing)</td> </tr> <tr> <td><b>Non-operating</b></td> <td>5% to 95% (non-condensing)</td> </tr> </table>  | <b>Operating</b> | 10% to 60% (non-condensing)   | <b>Non-operating</b> | 5% to 95% (non-condensing)     |
| <b>Operating</b>                        | 10% to 60% (non-condensing)   |                  |                               |                      |                                |
| <b>Non-operating</b>                    | 5% to 95% (non-condensing)  |                  |                               |                      |                                |
| <b>Altitude</b>                         | <table border="0"> <tr> <td><b>Operating</b></td> <td>0 to 10,000 ft (3,048 m)</td> </tr> <tr> <td><b>Non-operating</b></td> <td>0 to 50,000 ft (15,240 m)</td> </tr> </table>  | <b>Operating</b> | 0 to 10,000 ft (3,048 m)      | <b>Non-operating</b> | 0 to 50,000 ft (15,240 m)      |
| <b>Operating</b>                        | 0 to 10,000 ft (3,048 m)  |                  |                               |                      |                                |
| <b>Non-operating</b>                    | 0 to 50,000 ft (15,240 m)   |                  |                               |                      |                                |
| <b>LED Activity</b>                     | N/A   |                  |                               |                      |                                |

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card



## Technical Specifications

|   |  |
|---|--|
| <b>Bluetooth Specification</b>                    | 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant  |
| <b>Frequency Band</b>                             | 2402 to 2480 MHz   |
| <b>Number of Available Channels</b>               | Legacy : 0~79 (1 MHz/CH)<br>BLE : 0~39 (2 MHz/CH)  |
| <b>Signaling Data Rate</b>                        | Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps<br>BLE : 1 Mbps data rate; throughput up to 0.2 Mbps<br>Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels<br>Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)   |
| <b>Transmit Power</b>                             | The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.  |
| <b>Power Consumption</b>                          | Peak (Tx): 330 mW<br>Peak (Rx): 230 mW<br>Selective Suspend: 17 mW   |
| <b>Bluetooth Software Supported Link Topology</b> | Microsoft Windows Bluetooth Software   |
| <b>Power Management Certifications</b>            | Microsoft Windows ACPI, and USB Bus Support  |
| <b>Power Management Certifications</b>            | FCC (47 CFR) Part 15C, Section 15.247 & 15.407   |
| <b>Power Management Certifications</b>            | ETS 300 328<br>Low Voltage Directive<br>CE Mark  |
| <b>Bluetooth Profiles Supported</b>               | BT4.1-ESR 5/6/7 Compliance<br>LE Link Layer Ping<br>LE Dual Mode<br>LE Link Layer<br>LE Low Duty Cycle Directed Advertising<br>LE L2CAP Connection Oriented Channels<br>Train Nudging & Interlaced Scan<br>BT4.2 ESR08 Compliance<br>LE Secure Connection- Basic/Full<br>LE Privacy 1.2 –Link Layer Privacy<br>LE Privacy 1.2 –Extended Scanner Filter Policies<br>LE Data Packet Length Extension<br>FAX Profile (FAX)<br>Basic Imaging Profile (BIP)2<br>Headset Profile (HSP)<br>Hands Free Profile (HFP)<br>Advanced Audio Distribution Profile (A2DP)<br>BT5.2<br>ESR9/10 Compliance<br>LE Advertisement Extensions<br>Channel Selection Algo<br>Limited High Duty Cycle Non-Connectable Advertising<br>2Mbps LE<br>LE Long Range |

### Technical Specifications

Windows BT profiles support  
 BT5.3  
 Periodic Advertisement interval  
 Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

**Mediatek RZ616 Wi-Fi 6E + Bluetooth® 5.3 Wireless Card (802.11ax 2x2, supporting gigabit data rate) <sup>1</sup>**

|                               |   |
|-------------------------------|---|
| <b>Wireless LAN Standards</b> | IEEE 802.11a<br>IEEE 802.11b<br>IEEE 802.11g<br>IEEE 802.11n<br>IEEE 802.11ac<br>IEEE 802.11ax<br>IEEE 802.11d<br>IEEE 802.11e<br>IEEE 802.11h<br>IEEE 802.11i<br>IEEE 802.11j<br>IEEE 802.11k<br>IEEE 802.11mc<br>IEEE 802.11r<br>IEEE 802.11v<br>IEEE 802.11w   |
| <b>Interoperability</b>       | Wi-Fi certified   |
| <b>Frequency Band</b>         | •802.11b/g/n/ax<br>2.402 – 2.482 GHz<br>•802.11a/n/ac/ax<br>5.15 – 5.25 GHz<br>5.25 – 5.35 GHz<br>5.47 – 5.725 GHz<br>5.825 – 5.850 GHz<br>5.925 – 7.125 GHz  |
| <b>Data Rates</b>             | • 802.11b: 1, 2, 5.5, 11 Mbps<br>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps<br>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps<br>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)<br>• 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz)<br>• 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz & 160MHz) |
| <b>Modulation</b>             | Direct Sequence Spread Spectrum   |



### Technical Specifications

|   |  |
|---|--|
|   | OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM  |
| <b>Security<sup>2</sup></b>             | <ul style="list-style-type: none"> <li>• IEEE and Wi-Fi certified 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• WPA3 (personal) certification</li> <li>• IEEE 802.11i</li> <li>• WAPI</li> </ul>  |
| <b>Network Architecture Models</b>      | Ad-hoc (Peer to Peer)<br>Infrastructure (Access Point Required)  |
| <b>Roaming</b>                          | IEEE 802.11 compliant roaming between access points  |
| <b>Output Power<sup>3</sup></b>         | <p>2.4GHz (MIMO, typical):</p> <ul style="list-style-type: none"> <li>• 802.11b : +18dBm</li> <li>• 802.11g : +16.5dBm</li> <li>• 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm</li> <li>• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm</li> </ul> <p>5GHz (MIMO, typical):</p> <ul style="list-style-type: none"> <li>• 802.11a : +13dBm</li> <li>• 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm</li> <li>• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm</li> <li>• 802.11ac/ax (VHT80/HE80) : +11.5dBm</li> <li>• 802.11ax HE160 : +11.5dBm</li> </ul> <p>6GHz LPI mode (MIMO, typical)::</p> <ul style="list-style-type: none"> <li>• 802.11a : 0dBm</li> <li>• 802.11ax HE20 : +1dBm</li> <li>• 802.11ax HE40 : +4dBm</li> <li>• 802.11ax HE80 : +7dBm</li> <li>• 802.11ax HE160 : +7.5dBm</li> </ul> |
| <b>Power Consumption</b>                | <ul style="list-style-type: none"> <li>• Transmit mode :2.5 W</li> <li>• Receive mode :2 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode :50 mW (WLAN unassociated)</li> <li>• Connected Standby/Modern Standby: 10mW</li> <li>• Radio disabled: 8 mW</li> </ul>  |
| <b>Power Management</b>                 | ACPI and PCI Express compliant power management<br>802.11 compliant power saving mode  |
| <b>Receiver Sensitivity<sup>4</sup></b> | <p>2.4GHz (SISO):</p> <ul style="list-style-type: none"> <li>• 802.11b, 11Mbps : -82dBm maximum</li> <li>• 802.11g, 54Mbps : -71 dBm maximum</li> <li>• 802.11n, MCS7 : -64dBm maximum</li> <li>• 802.11ac, MCS9 : -52dBm maximum</li> <li>• 802.11ax, MCS11(HT40): -49dBm maximum</li> </ul> <p>5GHz (SISO):</p> <ul style="list-style-type: none"> <li>• 802.11a, 54Mbps : -71 dBm maximum</li> <li>• 802.11n, MCS07 : -64dBm maximum</li> <li>• 802.11ac, MCS9 : -52dBm maximum</li> <li>• 802.11ax, MCS11(HE80/HE160): -46dBm maximum</li> </ul>   |



## Technical Specifications

## 6GHz (SISO):

- 802.11a, 54Mbps : -71dBm maximum
- 802.11n, MCS7 : -64dBm maximum
- 802.11ac, MCS9 : -52dBm maximum
- 802.11ax, MCS11 (HE160): -46dBm maximum

**Antenna type**

High efficiency antenna with spatial diversity, mounted in the display enclosure

Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications

**Form Factor**

PCI-Express M.2 MiniCard

**Dimensions**

1. Type 2230 : 2.3 x 22.0 x 30.0 mm
2. Type 1216: 1.67 x 12.0 x 16.0 mm

**Weight**

1. Type 2230 : 2.8g
2. Type 126: 1.3g

**Operating Voltage**

3.3v +/- 9%

**Temperature**

**Operating** 14° to 158° F (-10° to 70° C)

**Non-operating** -40° to 176° F (-40° to 80° C)

**Humidity**

**Operating** 10% to 60% (non-condensing)

**Non-operating** 5% to 95% (non-condensing)

**Altitude**

**Operating** 0 to 10,000 ft (3,048 m)

**Non-operating** 0 to 50,000 ft (15,240 m)

**LED Activity**

N/A

**HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card****Bluetooth Specification**

4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant

**Frequency Band**

2402 to 2480 MHz

**Number of Available Channels**

Legacy : 0~79 (1 MHz/CH)

BLE : 0~39 (2 MHz/CH)

**Signaling Data Rate**

Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps

BLE : 1 Mbps data rate; throughput up to 0.2 Mbps

Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

**Transmit Power**

The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.

**Power Consumption**

Peak (Tx): 330 mW

Peak (Rx): 230 mW

Selective Suspend: 17 mW

**Bluetooth Software Supported Link Topology**

Microsoft Windows Bluetooth Software

**Power Management**

Microsoft Windows ACPI, and USB Bus Support

**Certifications**

FCC (47 CFR) Part 15C, Section 15.247 & 15.407

**Power Management Certifications**

ETS 300 328

Low Voltage Directive

## Technical Specifications

### Bluetooth Software Supported

CE Mark

BT4.1-ESR 5/6/7 Compliance

LE Link Layer Ping

LE Dual Mode

LE Link Layer

LE Low Duty Cycle Directed Advertising

LE L2CAP Connection Oriented Channels

Train Nudging & Interlaced Scan

BT4.2 ESR08 Compliance

LE Secure Connection- Basic/Full

LE Privacy 1.2 –Link Layer Privacy

LE Privacy 1.2 –Extended Scanner Filter Policies

LE Data Packet Length Extension

FAX Profile (FAX)

Basic Imaging Profile (BIP)2

Headset Profile (HSP)

Hands Free Profile (HFP)

Advanced Audio Distribution Profile (A2DP)

BT5.2

ESR9/10 Compliance

LE Advertisement Extensions

Channel Selection Algo

Limited High Duty Cycle Non-Connectable Advertising

2Mbps LE

LE Long Range

Windows BT profiles support

BT5.3

Periodic Advertisement interval

Encryption key size control enhancements

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Technical Specifications

|   |  |  |
|---|--|--|
| <b>Intel® XMM™ 7560 R+<br/>LTE-Advanced Pro<sup>1</sup></b> | <b>Technology/Operating<br/>bands</b>              | FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3),<br>1700/2100 (Band 4), 850 (Band 5), 2600 (Band 7), 900 (Band 8), 700<br>(Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700<br>(Band 17 lower), 850 (Band 18 lower), 850 (Band 19 upper), 800<br>(Band 20), 1900 (Band 25), 850 (Band 26), 700 (Band 28), 700 (Band<br>29 RX only), 2300 (Band 30), 1700/2100 (Band 66), 600 (band 71).      |
|   | <b>Wireless protocol standards</b>                 | TDD LTE: 2100 (Band 34), 2600 (Band 38), 1900 (Band 39), 2400<br>(Band 40), 2500 (Band 41), 3500 (Band 42), 3700 (Band 43), 3700<br>(band 48), 5200 (Band 46 RX only) MHz;<br>HSPA+: 2100 (Band 1), 1900 (Band 2), 1700/2100 (Band 4),<br>850 (Band 5), 900 (Band 8) MHz<br>3GPP Release 12 LTE Specification DL-CAT.16, DL 100MHz BW<br>throughput up to 978Mbps; UL-CAT.13 40MHz throughput up to<br>150Mbps |
|   | <b>GPS<br/>GPS bands</b>                           | WCDMA R99, 3GPP Release 5, 6, 7 and 8 UMTS Specification<br>Standalone GPS/Beidou/Glonass, A-GPS (MS-A, MS-B)<br>1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou<br>1561.098 MHz   |
|   | <b>Maximum data rates</b>                          | LTE: 978 Mbps (Download), 150 Mbps (Upload)<br>DC-HSPA+: 42 Mbps (Download), 5.76 Mbps (Upload)<br>HSPA+: 21Mbps (Download), 5.76 Mbps (Upload)  |
|   | <b>Maximum output power</b>                        | LTE: 23 dBm in all band except B41<br>LTE B41 HPUE = 26dBm<br>HSPA+: 23.5 dBm  |
|   | <b>Maximum power<br/>consumption</b>               | LTE: 1,200 mA (peak); 900 mA (average)<br>HSPA+: 1,100 mA (peak); 800 mA (average)   |
|   | <b>Form Factor</b>                                 | M.2, 3042-S3 Key B   |
|   | <b>Weight</b>                                      | 6 g  |
|   | <b>Dimensions<br/>(Length x Width x Thickness)</b> | 42 x 30 x 2.3 mm   |
|   | <b>embedded eSIM</b>                               | Support  |

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

### Technical Specifications

|  |                             |  |
|--|-----------------------------|--|
| <b>Realtek RTL8111HSH<br/>10/100/1000 Integrated<br/>NIC</b> | <b>Connector</b>            | RJ-45  |
|  | <b>System Interface</b>     | PCIe + SMBus   |
|  | <b>Data rates supported</b> | 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)<br>100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)<br>1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)<br>Auto-Negotiation (Automatic Speed Selection)<br>Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s       |
|  | <b>IEEE Compliance</b>      | IEEE 802.1p QoS (Quality of Service) Support<br>IEEE 802.1q VLAN support<br>IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)<br>IEEE 802.3az EEE (Energy Efficient Ethernet)  |
|  | <b>Performance</b>          | TCP/IP/UDP Checksum Offload (configurable)<br>Protocol Offload (ARP & NS)<br>Large send offload and Giant send offload<br>Receiving Side Scaling<br>Jumbo Frame 9K   |
|  | <b>Power consumption</b>    | Cable Disconnection: 25mW<br>100Mbps Full Run: 450mW<br>1000bp Full Run: 1000mW<br>WoL Enable(S3/S4/S5): 50mW<br>WoL Disable(S3/S4/S5): 25mW   |
|  | <b>Power Management</b>     | ACPI compliant – multiple power modes<br>Situation-sensitive features reduce power consumption<br>Advanced link down power saving for reducing link down power consumption   |
|  | <b>Management Interface</b> | Auto MDI/MDIX Crossover cable detection  |
|  | <b>IT Manageability</b>     | Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)<br>PXE 2.1 Remote Boot<br>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))<br>Comprehensive diagnostic and configuration software suite<br>Virtual Cable Doctor for Ethernet cable status |

### Technical Specifications

#### POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

|   |                                      |  |
|---|--------------------------------------|--|
| <b>AC Adapter 45 Watt nPFC Standard USB Type C® Straight 1.8m</b> | <b>Weight</b>                        | 0.44 lb (200 g) max (Not including power cord. Power cord varies by country.)  |
|   | <b>Input</b>                         | 100 ~ 240VAC   |
|   | <b>Input Efficiency</b>              | Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V : 81.5%<br>9V : 86.7%<br>12V : 87.4%<br>15V : 87.8%  |
|   | <b>Input frequency range</b>         | 47 ~ 63Hz  |
|   | <b>Input AC current</b>              | Max. 1.4 A at 90 Vac   |
|   | <b>Output</b>                        | <b>Output power</b><br>5V/15W<br>9V/27W<br>12V/36W<br>15V/45W  |
|   |                                      | <b>DC output</b><br>5V/9V/12V/15V  |
|   |                                      | <b>Hold-up time</b><br>100% load 5ms at 115 Vac input  |
|   |                                      | <b>Output current limit</b><br><5.0A   |
|   | <b>Connector</b>                     | USB Type-C®  |
|   | <b>Environmental Design</b>          | <b>Operating temperature</b><br>32°F to 95°F (0°to 35°C)<br><b>Non-operating (storage) temperature</b><br>-4°F to 185°F (-20°to 85°C)<br><b>Altitude</b><br>0 to 16,400 ft (0 to 5000m)<br><b>Humidity</b><br>20% to 95%<br><b>Storage Humidity</b><br>10% to 95%  |
|   | <b>EMI and Safety Certifications</b> | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, USB-IF, Ukraine(CoC+DoC+RoHS+ECO) |

### Technical Specifications

|   |   |   |  |
|---|---|---|--|
| <b>AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b> | <b>Weight</b>   | 0.44 lb (200 g) max (Not including power cord. Power cord varies by country.) |  |
|   | <b>Input</b>  | 100 ~ 240VAC  |  |
|   | <b>Output</b>   | <b>Input Efficiency</b>   | 87.74 % at 115 Vac and 88.4 % at 230Vac                          |
|   |   | <b>Input frequency range</b>  | 47 ~ 63 Hz   |
|   |   | <b>Input AC current</b>   | Max. 1.4 A at 90 Vac   |
|   |   | <b>Output power</b>   | 45W  |
|   |   | <b>DC output</b>  | 19.5V  |
|   | <b>Connector</b>  | <b>Hold-up time</b>   | 100% load 5ms at 115 Vac input/80% load<br>10ms at 115 Vac input |
|   |   | <b>Output current limit</b>   | <8.0A  |
|   | <b>Environmental Design</b>   | <b>Connector</b>  | 4.5mm Barrel Type  |
| <b>Operating temperature</b>  |   | <b>Operating temperature</b>  | 32°F to 95°F (0°to 35°C)   |
|   |   | <b>Non-operating (storage) temperature</b>                                    | -4°F to 185°F (-20°to 85°C)                                      |
| <b>Altitude</b>   |   | 0 to 16,400 ft (0 to 5000m)   |  |
| <b>Humidity</b>   |   | 20% to 95%  |  |
| <b>EMI and Safety Certifications</b>  | <b>Storage Humidity</b>   | 10% to 95%  |  |
|   | CE Mark - full compliance with LVD and EMC directives   |   |  |
|   | Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1  |   |  |
|   | Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC |   |  |

|   |                               |   |   |                             |
|---|-------------------------------|---|---|-----------------------------|
| <b>AC Adapter 65 Watt nPFC Standard USB Type C® Straight 1.8m</b> | <b>Dimensions (H x W x D)</b> | 3.543 x 2.008 x 1.122 in (9.0x5.1x2.85cm)                                     |   |                             |
|   | <b>Weight</b>                 | 0.53 lb (240 g) max (Not including power cord. Power cord varies by country.) |   |                             |
|   | <b>Input</b>                  | <b>Input</b>  | 100 ~ 240VAC  |                             |
|   |                               | <b>Input Efficiency</b>   | Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V: 81.5%<br>9V: 86.7%<br>12V: 88%<br>15V: 88%<br>20V: 89% |                             |
|   | <b>Output</b>                 | <b>Input frequency range</b>  | 47 ~ 63 Hz  |                             |
|   |                               | <b>Input AC current</b>   | Max. 1.6 A at 90 Vac  |                             |
|   |                               | <b>Output power</b>   | <b>Output power</b>   | 5V/15W<br>9V/27W<br>12V/60W |

### Technical Specifications

|                                      |  |  |
|--------------------------------------|--|--|
|                                      |  | 15V/60W<br>20V/65W   |
|                                      | <b>DC output</b>                           | 5V/9V/12V/15V/20V  |
|                                      | <b>Hold-up time</b>                        | 100% load 5ms at 115 Vac input   |
|                                      | <b>Output current limit</b>                | <8.0A  |
| <b>Connector</b>                     |  | USB TYPE C®  |
| <b>Environmental Design</b>          | <b>Operating temperature</b>               | 32°F to 95°F (0° to 35°C)  |
|                                      | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C)   |
|                                      | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)  |
|                                      | <b>Humidity</b>                            | 20% to 95%   |
|                                      | <b>Storage Humidity</b>                    | 10% to 95%   |
| <b>EMI and Safety Certifications</b> |  | CE Mark - full compliance with LVD and EMC directives<br>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL 62368-1<br>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC |

|  |  |   |
|--|--|---|
| <b>AC Adapter 65 Watt Smart nPFC EM Barrel 4.5mm</b> | <b>Dimensions (H x W x D)</b>              | 4.016 x 2.165 x 1.181 in (10.2x5.5x3cm)   |
|  | <b>Weight</b>                              | 0.58 lb (265 g) max (Not including power cord. Power cord varies by country.)     |
|  | <b>Input</b>                               | 100 ~ 240VAC  |
|  | <b>Input Efficiency</b>                    | 88.0 % at 115 Vac and 89.0 % at 230Vac  |
|  | <b>Input frequency range</b>               | 47 ~ 63 Hz  |
|  | <b>Input AC current</b>                    | Max. 1.7 A at 90 Vac  |
|  | <b>Output</b>                              | <b>Output power</b> 65W   |
|  |  | <b>DC output</b> 19.5V  |
|  |  | <b>Hold-up time</b> 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input |
|  |  | <b>Output current limit</b> <11.0A  |
| <b>Connector</b>                                     |  | 4.5mm Barrel Type   |
| <b>Environmental Design</b>                          | <b>Operating temperature</b>               | 32°F to 95°F (0° to 35°C)   |
|  | <b>Non-operating (storage) temperature</b> | -4°F to 185°F (-20° to 85°C)  |
|  | <b>Altitude</b>                            | 0 to 16,400 ft (0 to 5000m)   |
|  | <b>Humidity</b>                            | 20% to 95%  |
|  | <b>Storage Humidity</b>                    | 10% to 95%  |

### Technical Specifications

|   |  |
|---|--|
| <b>EMI and Safety Certifications</b>  | <p>CE Mark - full compliance with LVD and EMC directives</p> <p>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1</p> <p>Agency approvals - C-UL-US, TUV/GS, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, BIS, UKCA DoC</p>   |
| <hr/>   |  |
| <b>AC Adapter 65 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.8m</b> | <p><b>Dimensions (H x W x D)</b> 3.543 x 2.008 x 1.122 in (9.0x5.1x2.85cm)</p> <p><b>Weight</b> 0.55 lb (250 g) max (Not including power cord. Power cord varies by country.)</p> <p><b>Input</b> 100 ~ 240VAC</p> <p><b>Input Efficiency</b> 88.0 % at 115 Vac and 89.0 % at 230Vac</p> <p><b>Input frequency range</b> 47 ~ 63 Hz</p> <p><b>Input AC current</b> Max. 1.7 A at 90 Vac</p> <p><b>Output</b></p> <p><b>Output power</b> 65W</p> <p><b>DC output</b> 19.5V</p> <p><b>Hold-up time</b> 100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input</p> <p><b>Output current limit</b> &lt;11.0A</p> <p><b>Connector</b> 4.5mm Barrel Type</p> <p><b>Environmental Design</b></p> <p><b>Operating temperature</b> 32°F to 95°F (0°to 35°C)</p> <p><b>Non-operating (storage) temperature</b> -4°F to 185°F (-20°to 85°C)</p> <p><b>Altitude</b> 0 to 16,400 ft (0 to 5000m)</p> <p><b>Humidity</b> 20% to 95%</p> <p><b>Storage Humidity</b> 10% to 95%</p> <p><b>EMI and Safety Certifications</b></p> <p>CE Mark - full compliance with LVD and EMC directives</p> <p>Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1</p> <p>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC</p> |



### Technical Specifications

|  |   |   |  |
|--|---|---|--|
| <b>HP 65W Slim USB-C Straight AC Power Adapter</b> | <b>Dimensions (H x W x D)</b>   | 3.819 x 2.106 x 0.827 in (9.7x5.35x2.1 cm)                                    |  |
|  | <b>Weight</b>   | 0.49 lb (220 g) max (Not including power cord. Power cord varies by country.) |  |
|  | <b>Input</b>  | 100 ~ 240VAC  |  |
|  | <b>Output</b>   | <b>Input Efficiency</b>   | Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:<br>5V : 81.5%<br>9V : 86.7%<br>12V : 88.0%<br>15V : 89.0%<br>20V : 89.0% |
|  |   | <b>Input frequency range</b>  | 47-63Hz  |
|  |   | <b>Input AC current</b>   | Max. 1.6 A at 90 Vac   |
|  |   | <b>Output power</b>   | 5V/15W<br>9V/27W<br>12V/60W<br>15V/65W<br>20V/65W  |
|  |   | <b>DC output</b>  | 5V/9V/12V/15V/20V  |
|  |   | <b>Hold-up time</b>   | 100% load 5ms at 115 Vac input   |
|  | <b>Connector</b>  | <b>Output current limit</b>   | < 8.0A   |
|  |   | USB Type-C®   |  |
| <b>Environmental Design</b>                        | <b>Operating temperature</b>  | 32°F to 95°F (0°to 35°C)  |  |
|  | <b>Non-operating (storage) temperature</b>  | -4°F to 185°F (-20°to 85°C)   |  |
|  | <b>Altitude</b>   | 0 to 16,400 ft (0 to 5000m)   |  |
|  | <b>Humidity</b>   | 20% to 95%  |  |
|  | <b>Storage Humidity</b>   | 10% to 95%  |  |
| <b>EMI and Safety Certifications</b>               | <p>CE Mark - full compliance with LVD and EMC directives</p> <p>Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL 62368-1</p> <p>Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, Ukraine (CoC+DoC+RoHS+ECO)</p> |   |  |

### Technical Specifications

|  |                    |  |                               |
|--|--------------------|--|-------------------------------|
| <b>RH 42Whr Long Life<br/>Polymer Fast Charge 3<br/>cell Battery<sup>1</sup></b> | <b>Weight</b>      | 0.18 kg (0.397 lb)                       |                               |
|  | <b>Cells/Type</b>  | 3 cell Lithium-Ion Polymer cell / 545974 |                               |
|  | <b>Energy</b>      | <b>Voltage</b>                           | 11.4V                         |
|  |                    | <b>Amp-hour capacity</b>                 | 3.752Ah                       |
|  |                    | <b>Watt-hour capacity<sup>1</sup></b>    | 42.75Wh                       |
|  | <b>Temperature</b> | <b>Operating (Charging)</b>              | 32° to 113° F (0° to 45° C)   |
|  |                    | <b>Operating (Discharging)</b>           | 14° to 122° F (-10° to 60° C) |
| <b>Optional Travel Battery Available</b>   |                    | No                                       |                               |

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

|  |                    |   |                               |
|--|--------------------|---|-------------------------------|
| <b>RH 51Whr Long Life<br/>Polymer Fast Charge 3<br/>cell Battery<sup>1</sup></b> | <b>Weight</b>      | 0.2025 kg (0.446 lb)                    |                               |
|  | <b>Cells/Type</b>  | 3cell Lithium-Ion Polymer cell / 566075 |                               |
|  | <b>Energy</b>      | <b>Voltage</b>                          | 11.58V                        |
|  |                    | <b>Amp-hour capacity</b>                | 4.431Ah                       |
|  |                    | <b>Watt-hour capacity<sup>1</sup></b>   | 51.3Wh                        |
|  | <b>Temperature</b> | <b>Operating (Charging)</b>             | 32° to 113° F (0° to 45° C)   |
|  |                    | <b>Operating (Discharging)</b>          | 14° to 122° F (-10° to 60° C) |
| <b>Optional Travel Battery Available</b>   |                    | No                                      |                               |

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

### Technical Specifications

#### AUDIO

|                                   |  |
|-----------------------------------|--|
| <b>HD Stereo Codec</b>            | ALC3247-CG   |
| <b>Audio I/O Ports</b>            | Headset: CTIA only and Headphone-out   |
| <b>Internal Speaker Amplifier</b> | ALC 3247 has Embedded Class-D 2W Stereo Amplifier  |
| <b>Multi-streaming Capable</b>    | Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behavior   |
| <b>Sampling</b>                   | streams to be sent to/from the front and rear jacks or integrated speaker.   |
| <b>Wavetable Syntheses</b>        | Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz: External MIC/internal MIC 16bit,48000Hz: External SPK/Internal SPK |
| <b>Analog Audio</b>               | Support 3.5mm Headset: CTIA only and Headphone-out   |
| <b># of Channels on Line-Out</b>  | N/A  |
| <b>Internal Speaker</b>           | Yes  |

#### FINGERPRINT READER

|                                    |                             |
|------------------------------------|-----------------------------|
| <b>Sensor vendor</b>               | ELAN 80ST                   |
| <b>Sensor type</b>                 | Capacitive                  |
| <b>DPI resolution</b>              | 508 DPI                     |
| <b>Scan area</b>                   | 80x80 pixels                |
| <b>False Rejection Rate</b>        | <3%                         |
| <b>False Acceptance Rate</b>       | < 0.001%                    |
| <b>Mobile Voltage Operation</b>    | 2.7~3.6V                    |
| <b>Operating Temperature</b>       | -20°C - +80°C               |
| <b>Current Consumption</b>         | 35mA peak                   |
| <b>Image</b>                       |                             |
| <b>Low Latency Wait For Finger</b> | 900uA                       |
| <b>Capture Rate</b>                | Capture Rate: 50 frame/sec  |
| <b>ESD Resistance</b>              | IEC 61000-4-2 4B (+15KV)    |
| <b>Detection Matrix</b>            | 508 dpi / 4x4mm sensor area |

### Technical Specifications

#### ENVIRONMENTAL DATA

|  |  |                     |                     |
|--|--|---------------------|---------------------|
| <b>Eco-Label Certifications &amp; declarations</b>                         | <p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• US Federal Energy Management Program (FEMP)</li> <li>• EPEAT® Gold See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> <li>• TCO Certified</li> <li>• China Energy Conservation Program (CECP)</li> <li>• China State Environmental Protection Administration (SEPA)</li> <li>• Taiwan Green Mark</li> <li>• Korea Eco-label</li> <li>• Japan PC Green label*</li> </ul> |                     |                     |
| <b>Sustainable Impact Specifications</b>                                   | <ul style="list-style-type: none"> <li>• <a href="http://hp.com">Product Carbon Footprint (hp.com)</a></li> <li>• Ocean-bound plastic in Speaker</li> <li>• 10% post-consumer recycled plastic</li> <li>• 50% recycled metal</li> <li>• Low halogen</li> <li>• Outside Box and corrugated cushions are 100% sustainably sourced and recyclable</li> <li>• Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable</li> <li>• Bulk packaging available</li> </ul>   |                     |                     |
| <b>System Configuration</b>  | <p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.</p>   |                     |                     |
| <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b> | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b> |
| Normal Operation (Sort idle)   | 4.84   | 5.08                | 5.02                |
| Normal Operation (Long idle)   | 0.66   | 0.7                 | 0.81                |
| Sleep  | 0.66   | 0.7                 | 0.81                |
| Off  | 0.2  | 0.24                | 0.2                 |
|  | <p><b>NOTE:</b><br/>Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>  |                     |                     |
| <b>Heat Dissipation*</b>   | <b>115VAC, 60Hz</b>  | <b>230VAC, 50Hz</b> | <b>100VAC, 50Hz</b> |
| Normal Operation (Short idle)  | 16.6 BTU/hr  | 17.4 BTU/hr         | 17.2 BTU/hr         |
| Normal Operation (Long idle)   | 2.3 BTU/hr   | 2.4 BTU/hr          | 2.8 BTU/hr          |
| Sleep  | 2.3 BTU/hr   | 2.4 BTU/hr          | 2.8 BTU/hr          |
| Off  | 0.7 BTU/hr   | 0.8 BTU/hr          | 0.7 BTU/hr          |
|  | <p><b>*NOTE:</b> Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>  |                     |                     |

### Technical Specifications

| Declared Noise Emissions<br>(in accordance with<br>ISO 7779 and ISO 9296) | Sound Power<br>(L <sub>WAd</sub> , bels)   | Sound Pressure<br>(L <sub>pAm</sub> , decibels) |       |
|---|--|---|-------|
| Typically Configured – Idle   | 2.6  | 13.6  |       |
| Fixed Disk – Random writes  | 2.8  | 16.5  |       |
| Optical Drive – Sequential reads  | 3.4  | 29.2  |       |
| <b>Longevity and Upgrading</b>  | This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.  |   |       |
| <b>Additional Information</b>   | <ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product is 93.2% recycle-able when properly disposed of at end of life.</li> </ul>   |   |       |
| <b>Packaging Materials</b>  | <b>External:</b>   | PAPER/Corrugated                                | 230 g |
|   |  | PAPER/Paperboard                                | 51 g  |
|   |  | Paper/Molded Pulp                               | 61 g  |
|   | <b>Internal:</b>   | PLASTIC/Polyethylene low density-LDPE           | 9 g   |
|   | The plastic packaging material contains at least 0.0% recycled content.  |   |       |
|   | The corrugated paper packaging materials contains at least 57.0% recycled content.   |   |       |
| <b>RoHS Compliance</b>  | <p>HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.</p> <p>We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.</p> <p>We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.</p> <p>To obtain a copy of the HP RoHS Compliance Statement, see <a href="#">HP RoHS position statement</a>.</p> |   |       |
| <b>Material Usage</b>   | <p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html">http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> <li>Chlorinated Hydrocarbons</li> <li>Chlorinated Paraffins</li> <li>Bis(2-Ethylhexyl) phthalate (DEHP)</li> </ul>   |   |       |

### Technical Specifications

|   |  |
|---|--|
|   | <ul style="list-style-type: none"> <li>• Benzyl butyl phthalate (BBP)</li> <li>• Dibutyl phthalate (DBP)</li> <li>• Diisobutyl phthalate (DIBP)</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBEBs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul> |
| <b>Packaging Usage</b>                              | <p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>  |
| <b>End-of-life Management and Recycling</b>         | <p>HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>  |
| <b>HP, Inc. Corporate Environmental Information</b> | <p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications<br/> <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:<br/> <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a><br/> and<br/> <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>   |

### Technical Specifications

|                  |   |
|------------------|---|
| <b>footnotes</b> | <ul style="list-style-type: none"><li>• Percentage of ocean-bound plastic contained in each component varies by product</li><li>• Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.</li><li>• External power supplies, WWAN modules, power cords, cables and peripherals excluded.</li><li>• 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</li><li>• Fiber cushions made from 100% recycled wood fiber and organic materials.</li><li>• Plastic cushions are made from &gt;90% recycled plastic.</li><li>• Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams</li></ul> |
|------------------|---|

### COUNTRY OF ORIGIN

China

---

### Options and Accessories (Sold separately and availability may vary by country)

#### DOCKING (Sold Separately)

|  |   |
|--|---|
| <b>Docking station model #1</b>  | HP Thunderbolt 120W G4 Dock   |
| <b>Total number of supported displays (incl. the notebook display)</b> | 4   |
| <b>Max. resolutions supported</b>                                      | Quad 4K @60Hz<br>Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode |
| <b>Dock Connectors</b>   | 2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode  |
| <b>Technical limitations</b>   | Maximum resolution and display support is dependent on the maximum capability of the notebook.        |

#### Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

#### Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.

|  |   |
|--|---|
| <b>Docking station model #2</b>  | HP Thunderbolt 280W G4 Dock   |
| <b>Total number of supported displays (incl. the notebook display)</b> | 4   |
| <b>Max. resolutions supported</b>                                      | Quad 4K @60Hz<br>Dual 8K single cable@30 for TB hosts or USB-C hosts DP 1.4 with DSC in high res mode |
| <b>Dock Connectors</b>   | 2xDP, 1xHDMI, 1xTB, 1xUSB-C Alt Mode  |
| <b>Technical limitations</b>   | Maximum resolution and display support is dependent on the maximum capability of the notebook.        |

#### Thunderbolt Hosts:

Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.

Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz

#### Non-Thunderbolt hosts:

The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is

(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port

Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.



### Options and Accessories (Sold separately and availability may vary by country)

|   |  |
|---|--|
| <p><b>Docking station model #3</b></p> <p><b>Total number of supported displays (incl. the notebook display)</b></p> <p><b>Max. resolutions supported</b></p> <p><b>Dock Connectors</b></p> <p><b>Technical limitations</b></p> | <p>HP USB-C G5 Dock</p> <p>3</p> <p>Dual 5K@ 30Hz + (1) 4K UHD (multi-function mode)</p> <p>1xHDMI, 2xDP</p> <p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode.</p> <p>Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode</p> <p>The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.</p> |
| <p><b>Docking station model #4</b></p> <p><b>Total number of supported displays (incl. the notebook display)</b></p> <p><b>Max. resolutions supported</b></p> <p><b>Dock Connectors</b></p> <p><b>Technical limitations</b></p> | <p>HP USB-C/A Universal G2 Dock</p> <p>3</p> <p>Dual 4K @ 60Hz</p> <p>Single 5K @ 60Hz</p> <p>1xHDMI, 2xDP</p> <p>Maximum resolution and display support is dependent on the maximum capability of the notebook.</p> <p>The best resolution for dual or triple displays is 4K UHD@ 60Hz.</p> <p>For use with the USB-A adapter that comes in the box the maximum number of displays supported is (2) 4k x 60 Hz on the Type-A Gen 1 connection from the host.</p>  |
| <p><b>Docking station model #5</b></p> <p><b>Total number of supported displays (incl. the notebook display)</b></p> <p><b>Max. resolutions supported</b></p> <p><b>Dock Connectors</b></p> <p><b>Technical limitations</b></p> | <p>HP USB-C G5 Essential Dock</p> <p>3</p> <p>For hosts that support DisplayPort 1.4 with Display Stream Compression:</p> <p>3x FHD @ 60 Hz</p> <p>3x QHD @ 60 Hz</p> <p>3x 4K @ 60 Hz</p> <p>For hosts that support DisplayPort 1.3/1.4:</p> <p>3x FHD @ 60 Hz</p> <p>3x QHD @ 60 Hz</p> <p>2x 4K @ 60 Hz</p> <p>1 x HDMI, 2 x DP</p> <p>Video resolution depends on the capability of the host machine. This dock provides up to 65W of power delivery to the host machine.</p>  |

### Options and Accessories (Sold separately and availability may vary by country)

| Type                             | Description                            | Part Number |
|----------------------------------|--|-------------|
| <b>Audio</b>                     | HP Wired USB-A Stereo Headset          | 428K6AA     |
|                                  | HP Wired 3.5mm Stereo Headset          | 428K7AA     |
|                                  | HP 365 BT Speaker                      | 567D3AA#ACJ |
| <b>Video</b>                     | HP 325 FHD USB-A Webcam                | 53X27AA     |
|                                  | HP 965 4K USB-A STR Webcam             | 695J5AA     |
| <b>Cases</b>                     | HP Prelude G2 15.6 Backpack            | 1E7D6AA     |
|                                  | HP Prelude G2 15.6 Top Load            | 1E7D7AA     |
|                                  | HP Prelude Pro Recycled 15.6 Backpack  | 1X644AA     |
|                                  | HP Prelude Pro Recycled 15.6 Top Load  | 1X645AA     |
|                                  | HP Renew 14 Laptop Sleeve              | 2E6U9AA     |
|                                  | HP Renew Business 14.1 Laptop Bag      | 3E5F9AA     |
|                                  | HP Renew Business 14.1 Laptop Sleeve   | 3E2U7AA     |
|                                  | HP Renew Business 15.6 Laptop Bag      | 3E5F8AA     |
|                                  | HP Renew Business 17.3 Laptop Backpack | 3E2U5AA     |
|                                  | HP Renew Business 17.3 Laptop Bag      | 3E2U6AA     |
|                                  | HP Renew Executive 14.1 Laptop Sleeve  | 6B8Y3AA     |
|                                  | HP Renew Executive 16 Laptop Backpack  | 6B8Y1AA     |
| HP Renew Executive 16 Laptop Bag | 6B8Y2AA                                |             |
| <b>Docking</b>                   | HP USB-C 120W G5 Dock                  | 5TW10AA     |
|                                  | HP USB-C/A 120W G2 Universal Dock      | 5TW13AA     |
|                                  | HP Thunderbolt 120W G4 Dock            | 4J0A2AA     |
|                                  | HP Thunderbolt 280W G4 Dock            | 4J0G4AA     |
| <b>Hub</b>                       | HP 4K USB-C Multiport Hub              | 6G842AA     |
|                                  | HP Universal USB-C Multiport Hub       | 50H55AA     |
|                                  | HP USB-C Travel Dock G2                | 7PJ38AA     |
|                                  | HP USB-C to USB-A Hub                  | Z6A00AA     |
| <b>Adapter</b>                   | HP USB-C to RJ45 Adapter G2            | 4Z527AA     |
|                                  | HP USB 3.0 to Gigabit RJ45 Adapter G2  | 4Z7Z7AA     |
|                                  | HP HDMI to VGA Adapter                 | H4F02AA     |
|                                  | HP USB-C to DisplayPort Adapter        | N9K78AA     |
|                                  | HP USB-C to HDMI 2.0 Adapter           | 1WC36AA     |
|                                  | HP USB-C to USB 3.0 Adapter            | N2Z63AA     |
|                                  | HP USB-C to VGA Adapter                | N9K76AA     |

### Options and Accessories (Sold separately and availability may vary by country)

|  |  |             |
|--|--|-------------|
| <b>Keyboard/Combo</b>                                    | HP 125 WD USB Keyboard   | 266C9AA     |
|  | HP 320K WD USB Keyboard  | 9SR37AA     |
|  | HP 355 Compact Multi-Device BT Keyboard  | 692S9AA     |
|  | HP 455 Programmable Wireless Keyboard  | 4R177AA     |
|  | HP 975 USB+BT Dual-Mode Wireless Keyboard  | 3Z726AA     |
|  | HP 155 Wired Mouse and Keyboard Combo  | 5B8C0AA#ACJ |
|  | HP 225 Wired Mouse and Keyboard Combo  | 286J4AA     |
|  | HP 235 Wireless Mouse and Keyboard Combo   | 1Y4D0AA     |
|  | HP 655 Wireless Keyboard and Mouse Combo   | 4R009AA     |
|  | HP Wired Desktop 320MK Mouse and Keyboard  | 9SR36AA     |
| HP Wireless Rechargeable 950MK Mouse and Keyboard        | 3M165AA  |             |
| <b>Mouse</b>   | HP 125 USB-A Wired Mouse   | 265A9AA     |
|  | HP 128 USB Laser Wired Mouse   | 265D9AA     |
|  | HP 155 USB-A Wired Mouse   | 5B8B7AA#ACJ |
|  | HP 235 Wireless 2.4GHz Slim Wireless Mouse                                       | 4E407AA     |
|  | HP 320M USB-A Wired Mouse  | 9VA80AA     |
|  | HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse               | 3B4Q5AA     |
|  | HP 715 Rechargeable Multi-Device Bluetooth 5.0 + Wireless 2.4GHz Bluetooth Mouse | 6E6F0AA     |
|  | HP 925 Ergonomic Vertical Bluetooth 5.0 + Wireless 2.4GHz Wireless Mouse         | 6H1A5AA     |
|  | HP Creator USB-A+Bluetooth 935 Wireless Mouse Black                              | 1D0K8AA     |
|  | HP USB Premium Wireless Mouse  | 1JR31AA     |
| HP USB-A+Bluetooth Multi-Device 635 Wireless Mouse Black | 1D0K2AA  |             |
| HP USB-A+Bluetooth Travel Bluetooth Mouse                | 6SP30AA  |             |
| <b>Power</b>   | HP 65W 4.5 mm Smart AC Power Adapter   | H6Y89AA     |
|  | HP 65W GaN USB-C Laptop Charger  | 600Q7AA     |
|  | HP 65W USB-C Laptop Charger  | 671R3AA     |
|  | HP 65W USB-C LC AC Power Adapter   | 1P3K6AA     |
|  | HP 90W 4.5 mm Smart AC Power Adapter   | H6Y90AA     |
| <b>Commodity</b>   | HP USB DVD-Writer EXT ODD  | F2B56AA     |
|  | HP Nano Keyed Cable Lock   | 1AJ39AA     |
|  | HP Nano Master Keyed Cable Lock  | 1AJ40AA     |
|  | HP SureKey Standard/Nano/Wedge Cable Lock  | 6UW42AA     |
|  | HP Combination Nano Cable Lock   | 63B28AA     |
|  | HP Essential Combination Nano Cable Lock   | 63B31AA     |

### Change Log

| <b>Date of change:</b> | <b>Version History:</b> |         | <b>Description of change:</b>         |
|------------------------|-------------------------|---------|---------------------------------------|
| March 2, 2023          | V1 to V2                | Updated | Techspecs                             |
| March 9, 2023          | V2 to V3                | Added   | Docking station                       |
| March 30, 2023         | V3 to V4                | Updated | At a Glance section                   |
| April 4, 2023          | V4 to V5                | Updated | DisplayPort™ in Display section       |
| April 24, 2023         | V5 to V6                | Updated | WWAN CAT in At a Glance section       |
| May 18, 2023           | V6 to V7                | Updated | Storage and Drives section            |
| May 25, 2023           | V7 to V8                | Updated | Networking and Communications section |
| June 5, 2023           | V8 to V9                | Updated | Storage and Drives section            |
| August 1, 2023         | V9 to V10               | Added   | Environmental Data                    |
| September 15, 2023     | V10 to V11              | Updated | Battery life section                  |
|                        | V11 to V12              |         |                                       |
|                        |                         |         |                                       |
|                        |                         |         |                                       |

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. SDXC is a registered trademark of SD-3C in the United States, other countries, or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency.