

### Technical Specifications

#### HP ProBook 455 G7 Notebook PC



#### Left

- |   |  |
|---|--|
| 1. Internal Microphones (2)                     | 7. SD Card Reader                                      |
| 2. Webcam                                       | 8. Thermal Vent  |
| 3. Privacy Shutter (Only available with webcam) | 9. USB 2.0 Port  |
| 4. Webcam LED                                   | 10. Standard Security Lock Slot (Lock sold separately) |
| 5. Clickpad                                     | 11. Power Button                                       |
| 6. Hard Drive LED                               |  |

### Technical Specifications



#### Right

- |                                   |                                       |
|-----------------------------------|---------------------------------------|
| 1. Power Connector                | 5. USB 3.1 Gen 1 Port                 |
| 2. USB Type-C® 3.1 Gen 2 Port     | 6. USB 3.1 Gen 1 Port                 |
| 3. Ethernet Port (RJ-45)          | 7. Headphone / Microphone Combo Jack  |
| 4. HDMI Port (Cable not included) | 8. Fingerprint Sensor (select models) |

### Technical Specifications

#### At a Glance

- Preinstalled Windows 10 versions or FreeDOS
- Choice of AMD Ryzen™ 4000 series mobile processors, R7, R5 and R3
- Display include your choice of 39.62 cm (15.6") diagonal HD, Ultra Wide Viewing Angle FHD, And Privacy Panel option
- Enhanced security features including TPM2.0, HP Sure Sense, HP Sure Start, HP BIOSphere, Hardware enforced Firmware Protection, optional Fingerprint sensor (select models)<sup>4</sup>, optional IR camera, and optional Privacy Panel
- Designed to pass 19 MIL-STD 810H testing<sup>1</sup>
- Weight starting at 4.41 lb (2.0kg) (Weight will vary by configuration)
- HP Long-Life Rechargeable battery, with HP Fast Charge Technology recharges 50% in 30 minutes<sup>2</sup>
- Up to 512 GB Solid State Drives and 1 TB Hard Drive
- Up to 32 GB total system memory
- 720p HD webcam, IR camera for face authentication with Windows Hello
- Spill-resistant and optional backlit keyboard<sup>3</sup>, and Clickpad with multi-touch gestures enabled, taps enabled as default

1. MIL-STD-810H testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

3. Backlit keyboard is an optional feature that must be configured at purchase

4. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.

**NOTE:** See important legal disclosures for all listed specs in their respective features sections.



### Technical Specifications

#### PRODUCT NAME

HP ProBook 455 G7 Notebook PC

#### OPERATING SYSTEMS

<b>Preinstalled</b>	Windows 10 Pro 64 <sup>1</sup> Windows 10 Pro 64 (National Academic only) <sup>2</sup> Windows 10 Home 64 <sup>1</sup> Windows 10 Home Single Language 64 <sup>1</sup> Windows® 10 Enterprise 64 (Web Support) <sup>1</sup> FreeDOS
---------------------	--

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

#### PROCESSORS

AMD Ryzen™ 3 4300U APU with Renoir™ Vega 6 Graphics (2.7 GHz base clock, up to 3.7 GHz max boost clock, 4 MB L3 cache, four-cores)<sup>3,4,5,6</sup>  
AMD Ryzen™ 5 4500U APU with Renoir™ Vega 8 Graphics (2.3 GHz base clock, up to 4.0 GHz max boost clock, 4 MB L3 cache, six-cores)<sup>3,4,5,6</sup>  
AMD Ryzen™ 7 4700U APU with Renoir™ Vega 10 Graphics (2.0 GHz base clock, up to 4.1 GHz max boost clock, 4 MB L3 cache, eight-cores)<sup>3,4,5,6</sup>  
AMD Ryzen™ 5 PRO 4650U APU with Radeon™ Graphics (2.1 GHz base clock, up to 4 GHz max boost clock, 8 MB L3 cache, 6 cores)<sup>3,4,5</sup>  
AMD Ryzen™ 7 PRO 4750U APU with Radeon™ Graphics (1.7 GHz base clock, up to 4.1 GHz max boost clock, 8 MB L3 cache, 8 cores)<sup>3,4,5</sup>

##### Processors Family

AMD Ryzen™ 4000 Series Mobile processors<sup>6</sup>

3. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
4. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.
5. AMD Max Burst frequency performance varies depending on hardware, software and overall system configuration.
6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.



### Technical Specifications

#### CHIPSET

Chipset is integrated with processor

---

#### GRAPHICS

##### Integrated

AMD Radeon™ Graphics<sup>7</sup>

**Note:** View processor section for details.

##### Supports

Support HD decode, DX12, HDMI 1.4

[7. HD content required to view HD images.](#)

---

#### DISPLAY

##### Internal

##### Non-Touch

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m<sup>2</sup>, 45% NTSC (1366 x 768)<sup>7,8</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m<sup>2</sup>, 45% NTSC for HD camera (1366 x 768)<sup>7,8</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED backlit slim, 220 cd/m<sup>2</sup>, 45% NTSC for HD + IR camera (1366 x 768)<sup>7,8</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit slim, 250 cd/m<sup>2</sup>, 45% NTSC (1920 x 1080)<sup>7,8</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit slim, 250 cd/m<sup>2</sup>, 45% NTSC for HD camera (1920 x 1080)<sup>7,8</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit slim, 250 cd/m<sup>2</sup>, 45% NTSC for HD + IR camera (1920 x 1080)<sup>7,8</sup>

39.6 cm (15.6") diagonal FHD eDP+PSR anti-glare LED-backlit flat, 1000 cd/m<sup>2</sup>, 72% NTSC for HD Webcam Privacy (1920x1080)<sup>7,8</sup>

Supports narrow bezel

##### HDMI

HDMI 1.4b, up to 4K 30Hz

[7. HD content required to view HD images.](#)

[8. Resolutions are dependent upon monitor capability, and resolution and color depth settings.](#)

---



### Technical Specifications

Docking station model	Total number of supported displays (incl. the notebook display)	Max. resolutions supported	Dock Connectors	Technical limitations
HP Thunderbolt Dock 120W G2	3	Dual 4k @60Hz	2xDP, 1xVGA, 1xTB, 1xUSB-C alt-mode	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP USB-C Dock G4	3	Dual 2K @ 60Hz Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP USB-C Universal Dock	3	Dual 4K @ 60Hz Single 5K @ 60Hz	2xDP	
HP USB-C Travel Dock	2	Single 2K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 4K @ 30Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time
HP USB-C/A Universal Dock G2	3	Dual 2.5K @ 60Hz	2xDP, 1xHDMI	
HP USB-C Dock G5	3	Dual 2.5K @ 60Hz or 4K @ 60Hz + FHD @ 60Hz	2xDP, 1xHDMI	



### Technical Specifications

#### STORAGE AND DRIVES

**Primary Storage**

500 GB 7200 rpm SATA<sup>9</sup>

1 TB 5400 rpm SATA<sup>9</sup>

**Primary M.2 Storage**

128 GB SATA TLC Solid State Drive<sup>9</sup>

256 GB PCIe® NVMe™ Value Solid State Drive<sup>9</sup>

512 GB PCIe® NVMe™ TLC Solid State Drive<sup>9</sup>

512 GB PCIe® NVMe™ Value Solid State Drive<sup>9</sup>

9. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

#### MEMORY

**Maximum Memory**

32 GB DDR4-3200 SDRAM<sup>11</sup>

**Memory**

32 GB DDR4-3200 SDRAM (2 x 16 GB)<sup>11</sup>

16 GB DDR4-3200 SDRAM (2 x 8 GB)<sup>11</sup>

16 GB DDR4-3200 SDRAM (1 x 16 GB)<sup>11</sup>

12 GB DDR4-3200 SDRAM (1 x 4 GB and 1 x 8 GB)<sup>11</sup>

8 GB DDR4-3200 SDRAM (1 x 8 GB)<sup>11</sup>

8 GB DDR4-3200 SDRAM (2 x 4 GB)<sup>11</sup>

4 GB DDR4-3200 SDRAM (1 x 4 GB)<sup>11</sup>

**Memory Slots**

2 SODIMM

Both slots are customer accessible / upgradeable by IT or self-maintainers only

DDR4 PC4 SODIMMS, system runs at 3200

Supports Dual Channel Memory

10. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

#### NETWORKING/COMMUNICATIONS

**WLAN**

Realtek RTL8822CE 802.11 a/b/g/n/ac (2x2) Wi-Fi® + Bluetooth® 5 Combo<sup>11</sup>

Intel® Dual Band Wi-Fi® 6 AX200 802.11ax (2x2) and Bluetooth® 5 Combo, non-vPro™<sup>11</sup>

Intel® Dual Band Wireless-AC 9260 802.11 a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, non-vPro™<sup>11</sup>

**Ethernet**

Realtek RTL8111EP 10/100/1000 NIC<sup>12</sup>

11. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported



### Technical Specifications

12. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

#### AUDIO/MULTIMEDIA

##### Audio

Integrated microphone (Mono or Dual Array)  
2 Integrated stereo speakers

##### Camera

720p HD camera<sup>7</sup>  
720p HD + IR camera<sup>7,13</sup>

7. HD content required to view HD images.

13. IR camera is an optional feature that must be configured at purchase.

---

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

##### Keyboard

HP Premium Keyboard, spill resistant with numeric keypad and optional backlit<sup>14</sup>

##### Pointing Device

Clickpad with multi-touch gesture support

##### Function Keys

F1 - Display Switching  
F2 - Blank or SureView On/Off  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - Blank  
F11 - Wireless  
F12 - Sleep

##### Hidden Functions

Fn+R - Break  
Fn+S - Sys Rq  
Fn+C - Scroll Lock

14. Backlit keyboard is an optional feature that must be configured at purchase.

---

#### SOFTWARE AND SECURITY

##### BIOS

HP BIOSphere Gen5<sup>15</sup>  
HP Drive Lock & Automatic Drive Lock<sup>16</sup>





### Technical Specifications

BIOS Update via Network  
Master Boot Record Security  
Power On Authentication  
Secure Erase<sup>17</sup>  
Absolute Persistence Module<sup>18</sup>  
Pre-boot Authentication

#### Software

HP Connection Optimizer  
HP Image Assistant  
HP Hotkey Support  
HP JumpStarts  
HP Support Assistant<sup>19</sup>  
HP Noise Cancellation Software  
Buy Office (sold separately)

#### Manageability Features

HP Driver Packs<sup>20</sup>  
HP System Software Manager (SSM)  
HP BIOS Config Utility (BCU)  
HP Client Catalog  
HP Manageability Integration Kit Gen3<sup>21</sup>

#### Client Security Software

HP Client Security Manager Gen5<sup>22</sup>  
Windows Defender<sup>23</sup>  
HP Fingerprint Sensor<sup>24</sup>

#### Security Management

Pre-boot Authentication  
TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)<sup>25</sup>  
USB enable/disable (via BIOS)  
Power-on password (via BIOS)  
Setup password (via BIOS)  
Support for chassis padlocks and cable lock devices  
HP Fingerprint Sensor<sup>24</sup>  
HP Sure Sense<sup>26</sup>  
HP Sure Click<sup>27</sup>  
HP Sure Start Gen5<sup>28</sup>

15. HP BIOSphere Gen5 is available on select HP Pro and Elite PCs. See product specifications for details. Features may vary depending on the platform and configurations.

16. HP Drive Lock & Automatic Drive Lock is not supported on NVMe drives

17. For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

18. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.

19. HP Support Assistant requires Windows and Internet access.

20. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

21. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.

22. HP Client Security Manager Gen5 requires Windows and is available on the select HP Pro and Elite PCs. See product specifications for details.



### Technical Specifications

- 23. Windows Defender Opt in and internet connection required for updates.
- 24. HP Fingerprint Sensor is an optional feature and requires configuration at purchase.
- 25. Firmware TPM is version 2.0.
- 26. HP Sure Sense requires Windows 10. See product specifications for availability. On HP Elite x2 G4 units with WWAN shipping to China, HP Sure Sense is only available via Softpaq download.
- 27. HP Sure Click is available on select HP platforms and supports Microsoft Internet Explorer, Google Chrome™, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode, when Microsoft Office or Adobe Acrobat are installed.
- 28. HP Sure Start Gen5 is available on select HP PCs with Intel processors. See product specifications for availability.

### POWER

#### Power Supply

- HP Smart 65 W External AC power adapter<sup>29</sup>
- HP Smart 65 W EM External AC power adapter<sup>29</sup>
- HP Smart 65 W USB Type-C® adapter<sup>29</sup>
- HP Smart 45 W External AC power adapter<sup>29</sup>
- HP Smart 45 W USB Type-C® adapter<sup>29</sup>

#### Power Cord

- 3-wire plug - 1.8 m<sup>29</sup>
- 3-wire plug - 1.0 m<sup>29</sup>
- 2-wire plug - 1.0 m<sup>29</sup>
- Duckhead power cord - 1.0 m<sup>29</sup>
- Duckhead power cord - 1.8 m<sup>29</sup>

#### Primary Battery

- HP Long Life 3-cell, 45 Wh Li-ion polymer<sup>30</sup>

#### Battery Life

- 14 hours<sup>31</sup>

#### Battery Weight

- 0.22 kg
- 0.49 lb

- 29. Availability may vary by country.
- 30. Battery is internal and not replaceable by customer. Serviceable by warranty.
- 31. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details..



### Technical Specifications

#### WEIGHTS & DIMENSIONS

**Weight**

Starting at 4.41 lb<sup>32</sup>

Starting at 2.0 kg<sup>32</sup>

**Dimensions (w x d x h)**

14.37 x 10.11 x 0.75 in

36.49 x 25.69 x 1.89 cm

32. Weight will vary by configuration. Does not include power adapter.

---

#### PORTS/SLOTS

**Ports**

1 USB 3.1 Type-C® Gen 2 (Power delivery, DisplayPort™ 1.2)

2 USB 3.1 Gen 1

1 USB 2.0 (powered port)

1 HDMI 1.4<sup>33</sup>

1 RJ-45

1 AC power

1 stereo headphone/microphone combo jack

**Expansion Slots**

1 SD

Supports SD, SDHC, SDXC

33. HDMI cable sold separately.

---



### Technical Specifications

#### SYSTEM UNIT

##### Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	8.1 W
Integrated graphics	Yes (AMD Radeon™ Graphics)
Max Operating Power	Discrete < 65 W UMA < 45 W

##### Temperature

Operating	32° to 95° F (0° to 35° C) (Not writing optical)
Non-operating	-4° to 140° F (-20° to 60° C) (Writing optical)

##### Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

##### Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

##### Random Vibration

Operating	0.75 grms
Non-operating	1.50 grms

##### Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

##### Planned Industry Standard Certifications

UL	Yes
CSA	Yes
FCC Compliance	Yes
Energy Star®	Selected models <sup>35</sup>
EPEAT® 2019	Yes, Gold in U.S. <sup>36</sup>
ICES	Yes
Australia	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes



### Technical Specifications

Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes

35. Configurations of the HP ProBook 455 G7 that are ENERGY STAR® qualified are identified as HP ProBook 455 G7 ENERGY STAR® on HP websites and on <http://www.energystar.gov>.

36. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

### DISPLAYS

**NOTE:** All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

<b>Panel LCD 15.6 inch diagonal HD (1366 x 768)</b> <b>Anti-Glare WLED SVA 45%</b> <b>NTSC 220 nits eDP 1.2 w/o PSR slim NB non-touch</b>	<b>Outline Dimensions (W x H x D)</b>	350.96 x 216.75 (max.)
	<b>Active Area</b>	344.16 x 193.59 (typ.)
	<b>Weight</b>	<370g max.
	<b>Diagonal Size</b>	15.6"
	<b>Thickness</b>	3.2mm max.
	<b>Interface</b>	eDP 1.2
	<b>Surface Treatment</b>	Anti-glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	300:1 (typ)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	220 nits typical (Panel Only)
	<b>Pixel Resolution</b>	1366 x 768 (HD)
	<b>Format of LCD Pixel Arrangement</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	45% of NTSC
	<b>Color Depth</b>	6 bits + Hi FRC
	<b>Viewing Angle</b>	SVA 40/40/15/30

<b>Panel LCD 15.6 inch diagonal FHD (1920 x 1080)</b> <b>Anti-Glare WLED UWVA 45%</b> <b>NTSC 250 nits eDP 1.2 w/o PSR slim NWBZ</b>	<b>Outline Dimensions (W x H x D)</b>	350.96 x 216.65 mm (max)
	<b>Active Area</b>	344.16 x 193.59 mm (typ.)
	<b>Weight</b>	370 g (max)
	<b>Diagonal Size</b>	15.6 inch
	<b>Thickness</b>	3.2 mm (max)
	<b>Interface</b>	eDP 1.2 (2 lane)
	<b>Surface Treatment</b>	Anti-Glare
	<b>Touch Enabled</b>	No
	<b>Contrast Ratio</b>	600:1 (typ.)
	<b>Refresh Rate</b>	60 Hz



### Technical Specifications

<b>Brightness</b>	250 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format of LCD Pixel Arrangement</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	45% of NTSC
<b>Color Depth</b>	6 bits
<b>Viewing Angle</b>	UWVA 85/85/85/85

**Panel LCD 15.6 inch  
diagonal FHD (1920 x 1080)  
Anti-Glare WLED UWVA 72%  
NTSC 1000 nits eDP  
1.4+PSR2 flat Privacy**

<b>Outline Dimensions (W x H x D)</b>	349.52 x 204.79 mm (max)
<b>Active Area</b>	344.16 x 193.59 mm (typ.)
<b>Weight</b>	350 g (max)
<b>Diagonal Size</b>	15.6 inch
<b>Thickness</b>	2.6 mm (max)
<b>Interface</b>	eDP 1.4 + PSR2 (4 lane)
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	2000:1 (typ.)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	1000 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format of LCD Pixel Arrangement</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	72% of NTSC
<b>Color Depth</b>	8 bits
<b>Viewing Angle</b>	UWVA 85/85/85/85



### Technical Specifications

#### STORAGE AND DRIVES

**NOTE:** For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software

<b>500 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.20 lbs (92 g) ~ 0.21 lbs (95 g)
	<b>Rotation speed</b>	7200 rpm
	<b>Cache Buffer</b>	Up to 32 MB
	<b>Height</b>	0.28 in (7 mm)
	<b>Width</b>	2.75 in (69.85 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	600 MB/s
	<b>Seek Time</b>	Single Track: 2 ~ 1.5 ms Average: 11 ~ 13 ms Maximum: 18 ~ 22 ms
	<b>Logical Blocks</b>	976,773,168
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [top cover temp]
	<b>Security Features</b>	ATA Security
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA

<b>1 TB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.21 lbs (94 g)
	<b>Rotation speed</b>	5400 rpm
	<b>Cache Buffer</b>	Up to 32 MB
	<b>Height</b>	0.28 in (7.2 mm)
	<b>Width</b>	2.75 in (69.85 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	600 MB/s
	<b>Seek Time</b>	Single Track: 2 ms Average: 12 ~ 13 ms Maximum: 18 ~ 22 ms
	<b>Logical Blocks</b>	1,953,525,168
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [top cover temp]
	<b>Security Features</b>	ATA Security
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA



### Technical Specifications

#### SSD 128 GB 2280 M2 SATA-3 TLC

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	128 GB
<b>NAND Type</b>	TLC
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Weight</b>	0.02 lb (10 g)
<b>Interface</b>	ATA-8, SATA 3.0
<b>Maximum Sequential Read</b>	Up To 520 MB/s
<b>Maximum Sequential Write</b>	Up To 450 MB/s
<b>Logical Blocks</b>	250,069,680
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	DIPM; TRIM; DEVSLP

#### 256 GB 2280 PCIe NVMe Value Solid State Drive

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	256 GB
<b>NAND Type</b>	TLC
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	PCIe NVMe Gen3
<b>Maximum Sequential Read</b>	Up To 1700 MB/s
<b>Maximum Sequential Write</b>	Up To 1300 MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2

#### 512 GB 2280 M2 PCIe NVMe TLC Solid State Drive

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	512 GB
<b>NAND Type</b>	TLC
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	PCIe NVMe Gen3X4
<b>Maximum Sequential Read</b>	Up To 2600 MB/s
<b>Maximum Sequential Write</b>	Up To 1400 MB/s
<b>Logical Blocks</b>	1,000,215,216
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2





## Technical Specifications

512 GB 2280 PCIe NVMe Value Solid State Drive	Form Factor	M.2 2280
	Capacity	512 GB
	NAND Type	Value
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	Up To 1500 ~ 1700 MB/s
	Maximum Sequential Write	Up To 860 ~ 1500 MB/s
	Logical Blocks	1,000,215,216
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	ATA Security, TRIM; L1.2



### Technical Specifications

#### NETWORKING/COMMUNICATIONS

**Intel® Wi-Fi 6<sup>1</sup> AX200 and Bluetooth® 5.0 802.11ax (2x2), non-vPro, supporting gigabit file transfer speeds non-vPro**

IEEE 802.11a  
IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n  
IEEE 802.11ac  
IEEE 802.11ax  
IEEE 802.11d  
IEEE 802.11e  
IEEE 802.11h  
IEEE 802.11i  
IEEE 802.11k  
IEEE 802.11r  
IEEE 802.11v

**Interoperability**  
**Frequency Band**

Wi-Fi CERTIFIED™  
•802.11b/g/n/ax  
2.402 – 2.482 GHz  
•802.11a/n/ac/ax  
4.9 – 4.95 GHz (Japan)  
5.15 – 5.25 GHz  
5.25 – 5.35 GHz  
5.47 – 5.725 GHz  
5.825 – 5.850 GHz

**Data Rates**

• 802.11b: 1, 2, 5.5, 11 Mbps  
• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)  
• 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)  
• 802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)

**Modulation**

Direct Sequence Spread Spectrum  
OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM

**Security<sup>3</sup>**

• IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only  
• AES-CCMP: 128 bit in hardware  
• 802.1x authentication  
• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.  
• WPA2 certification  
• IEEE 802.11i  
• WAPI

**Network Architecture Models**

Ad-hoc (Peer to Peer)  
Infrastructure (Access Point Required)

**Roaming**

IEEE 802.11 compliant roaming between access points

**Output Power<sup>2</sup>**

• 802.11b: +18.5dBm minimum  
• 802.11g: +17.5dBm minimum  
• 802.11a: +18.5dBm minimum  
• 802.11n HT20(2.4GHz): +15.5dBm minimum  
• 802.11n HT40(2.4GHz): +14.5dBm minimum  
• 802.11n HT20(5GHz): +15.5dBm minimum



### Technical Specifications

	<ul style="list-style-type: none"> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ac VHT160(5GHz): +11.5dBm minimum</li> <li>• 802.11ax HT40(2.4GHz): +10dBm minimum</li> <li>• 802.11ax VHT160(5GHz): +10dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10 mW</li> <li>• Radio disabled 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b, 1Mbps: -93.5dBm maximum</li> <li>• 802.11b, 11Mbps: -84dBm maximum</li> <li>• 802.11a/g, 6Mbps: -86dBm maximum</li> <li>• 802.11a/g, 54Mbps: -72dBm maximum</li> <li>• 802.11n, MCS07: -67dBm maximum</li> <li>• 802.11n, MCS15: -64dBm maximum</li> <li>• 802.11ac, MCS0: -84dBm maximum</li> <li>• 802.11ac, MCS9: -59dBm maximum</li> <li>• 802.11ax, MCS11(HT40): -59dBm maximum</li> <li>• 802.11ax, MCS11(VHT160): -58.5dBm maximum</li> </ul>
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230 : 2.8 g 2. Type 126: 1.3 g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating            Operating: 14° to 158° F (–10° to 70° C) Non-operating      Non-operating: –40° to 176° F (–40° to 80° C)
<b>Humidity</b>	Operating            Operating: 10% to 90% (non-condensing) Non-operating      Non-operating: 5% to 95% (non-condensing)
<b>Altitude</b>	Operating            Operating: 0 to 10,000 ft (3,048 m) Non-operating      Non-operating: 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF LED OFF – Radio ON
<b>HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1 Wireless Technology</b>	
<b>Bluetooth® Specification</b>	4.0/4.1/4.2/5.0/5.1 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate<sup>4</sup></b>	Legacy: 3 Mbps Signaling Data Rate 2.17 Mbps



### Technical Specifications

	BLE: 1 Mbps Signaling Data Rate 0.2 Mbps <a href="#">1. Actual throughput may vary.</a>
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<b>Bluetooth Software Supported Link Topology</b>	Microsoft Windows Bluetooth Software
<b>Power Management Certifications</b>	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Bluetooth Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



### Technical Specifications

#### Intel® 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5.0 Combo<sup>1</sup> Non-vPro

	<ul style="list-style-type: none"> <li>IEEE 802.11a</li> <li>IEEE 802.11b</li> <li>IEEE 802.11g</li> <li>IEEE 802.11n</li> <li>IEEE 802.11ac</li> <li>IEEE 802.11d</li> <li>IEEE 802.11e</li> <li>IEEE 802.11h</li> <li>IEEE 802.11i</li> <li>IEEE 802.11k</li> <li>IEEE 802.11r</li> <li>IEEE 802.11v</li> </ul>
<b>Interoperability</b>	Wi-Fi CERTIFIED™
<b>Frequency Band</b>	<ul style="list-style-type: none"> <li>•802.11b/g/n 2.402 – 2.482 GHz</li> <li>•802.11a/n/ac 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz</li> </ul>
<b>Data Rates</b>	<ul style="list-style-type: none"> <li>•802.11b: 1, 2, 5.5, 11 Mbps</li> <li>•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz &amp; 160MHz)</li> </ul>
<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>•IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>•AES-CCMP: 128 bit in hardware</li> <li>•802.1x authentication</li> <li>•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>•WPA2 certification</li> <li>•IEEE 802.11i</li> <li>•WAPI</li> </ul>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +18.5dBm minimum</li> <li>• 802.11g: +17.5dBm minimum</li> <li>• 802.11a: +18.5dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +14.5dBm minimum</li> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ac VHT160(5GHz): +11.5dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>•Transmit mode 2.0 W</li> <li>•Receive mode 1.6 W</li> <li>•Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>•Idle mode 50 mW (WLAN unassociated)</li> <li>•Connected Standby/Modern Standby: 10mW</li> <li>•Radio disabled 8 mW</li> </ul>



### Technical Specifications

<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
<b>Antenna type</b>	High efficiency antenna. One embedded dual band 2.4/5 GHz antenna is provided to the card to support WLAN communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	Type 2230: 2.3 x 22.0 x 30.0 mm Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	Type 2230: 2.8 g Type 126: 1.3 g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
<b>Altitude</b>	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF LED OFF – Radio ON
<b>HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology</b>	
<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate</b>	Legacy: 3 Mbps Signaling Data Rate 2.17 Mbps BLE: 1 Mbps Signaling Data Rate 0.2 Mbps <a href="#">1. Actual throughput may vary.</a>
<b>Transmit Power</b>	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<b>Electrical Interface</b>	USB 2.0 compliant
<b>Bluetooth Software Supported</b>	Microsoft Windows Bluetooth Software
<b>Link Topology</b>	



### Technical Specifications

<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support
<b>Certifications</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<b>Power Management</b>	ETS 300 328, ETS 300 826
<b>Certifications</b>	Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Bluetooth Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

<b>802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5.0</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	<b>Interoperability</b>	Wi-Fi CERTIFIED™
	<b>Frequency Band</b>	•802.11b/g/n 2.402 – 2.482 GHz •802.11a/n/ac 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz



### Technical Specifications

	5.825 – 5.850 GHz
<b>Data Rates</b>	<ul style="list-style-type: none"> <li>•802.11b: 1, 2, 5.5, 11 Mbps</li> <li>•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz &amp; 80MHz)</li> </ul>
<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>•IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>•AES-CCMP: 128 bit in hardware</li> <li>•802.1x authentication</li> <li>•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>•WPA2 certification</li> <li>•IEEE 802.11i</li> <li>•WAPI</li> </ul>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +18.5dBm minimum</li> <li>• 802.11g: +17.5dBm minimum</li> <li>• 802.11a: +18.5dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +14.5dBm minimum</li> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ac VHT160(5GHz): +11.5dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>•Transmit mode: 2.0 W</li> <li>•Receive mode: 1.6 W</li> <li>•Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>•Idle mode: 50 mW (WLAN unassociated)</li> <li>•Connected Standby/Modern Standby: 10mW</li> <li>•Radio disabled: 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>4</sup></b>	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard with CNVi Interface
<b>Dimensions</b>	Type 2230: 2.3 x 22.0 x 30.0 mm Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	Type 2230: 2.8 g Type 126: 1.3 g





### Technical Specifications

<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating: 14° to 158° F (–10° to 70° C) Non-operating: –40° to 176° F (–40° to 80° C)
<b>Humidity</b>	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
<b>Altitude</b>	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF LED OFF – Radio ON

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate</b>	Legacy: 3 Mbps Signaling Data Rate 2.17 Mbps BLE: 1 Mbps Signaling Data Rate 0.2 Mbps <a href="#">1. Actual throughput may vary.</a>
<b>Transmit Power</b>	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5) The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<b>Bluetooth Software Supported Link Topology</b>	Microsoft Windows Bluetooth Software
<b>Power Management Certifications</b>	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Bluetooth Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP)



### Technical Specifications

Hands Free Profile (HFP)  
Advanced Audio Distribution Profile (A2DP)

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

<b>Realtek RTK8111HSH 10/100/1000 Integrated NIC</b>	<b>Connector</b>	RJ-45
	<b>System Interface</b>	PCIe + SMBus
	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
	<b>Manageability</b>	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	<b>Management Interface</b>	Auto MDI/MDIX Crossover cable detection



### Technical Specifications

#### POWER

<b>HP 45 W Smart AC adapter</b>	<b>Dimensions (H x W x D)</b>	3.74 x 1.57 x 1.04 in (9.5 x 4.0 x 2.65 cm)
	<b>Weight</b>	0.386 lb (175 g) max <a href="#">Not including power cord. Power cord varies by country</a>
	<b>Input</b>	90 to 265 VAC
	<b>Input Efficiency</b>	87.74% at 115 VAC and 88.4% at 230 VAC
	<b>Input frequency range</b>	47 to 63 Hz
	<b>Input AC current</b>	1.4 A at 90 VAC
	<b>Output</b>	<b>Output power</b> 45 W
		<b>DC output</b> 19.5 V
		<b>Hold-up time</b> 5 msec at 115 VAC input
		<b>Output current limit</b> <8.0 A
	<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b> 32° to 95° F (0° to 35° C)
		<b>Non-operating (storage) temperature</b> -4° to 185° F (-20° to 85° C)
		<b>Altitude</b> 0 to 16,400 ft (0 to 5,000 m)
		<b>Humidity</b> 20% to 95%
	<b>EMI and Safety Certifications</b>	<b>Storage Humidity</b> 10% to 95%
		*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

<b>HP 65 W Smart AC adapter</b>	<b>Dimensions</b>	90 x 51 x 28.5 mm
	<b>Weight</b>	220 g +/- 10 g <a href="#">Not including power cord. Power cord varies by country</a>
	<b>Input</b>	<b>Input Efficiency</b> 88% min at 115 VAC and 89.0% at 230 VAC
		<b>Input frequency range</b> 47 to 63 Hz
		<b>Input AC current</b> Max. 1.7 A at 90 VAC
	<b>Output</b>	<b>Output power</b> 65 W
		<b>DC output</b> 19.5 V
		<b>Hold-up time</b> 5 msec at 115 VAC input
		<b>Output current limit</b> <11.0 A
	<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b> 32°F to 95°F (0° to 35°C)
		<b>Non-operating (storage) temperature</b> -4°F to 185°F (-20° to 85°C)



### Technical Specifications

<b>EMI and Safety Certifications</b>	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
	*CE Mark - full compliance with LVD and EMC directives	
	* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.	
	* MTBF - over 200,000 hours at 25°C ambient condition.	

<b>HP 65 W EM Smart AC adapter</b>	<b>Dimensions</b>	102 x 55 x 30 mm	
	<b>Weight</b>	270g +/- 10g <a href="#">Not including power cord. Power cord varies by country</a>	
	<b>Input Efficiency</b>	87% min at 115V/230V	
	<b>Input frequency range</b>	47 to 63 Hz	
	<b>Input AC current</b>	1.7 A at 90 Vac and maximum load	
	<b>DC output</b>	65 W (19.5V/3.33A)	
	<b>Hold-up time</b>	5 msec at 115 VAC input	
	<b>Output current limit</b>	<11 A, Over voltage protection- 29V max automatic shutdown	
	<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
		<b>Altitude</b>	0 to 5,000 m
		<b>Humidity</b>	0% to 95%
		<b>Storage Humidity</b>	0% to 95%
	<b>EMI and Safety Certifications</b>	*CE Mark - EMC directives	
		* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.	
		*MTBF - over 200,000 hours at 25°C ambient condition.	

<b>AC Adapter 65 Watt nPFC USB Type-C®</b>	<b>Dimensions</b>	74 x 74 x 28.5 mm	
	<b>Weight</b>	245 g +/- 10 g <a href="#">Not including power cord. Power cord varies by country</a>	
	<b>Input</b>	<b>Input Efficiency</b>	81.5% min at 115 Vac/ 230Vac @ 5V/3A
			86.7% min at 115 Vac/ 230Vac @ 9V/3A
			88% min at 115 Vac/ 230Vac @ 10V/5A
			88% min at 115 Vac/ 230Vac @ 12V/5A
			89% min at 115 Vac/ 230Vac @ 15V/4.33A
	89% min at 115 Vac/ 230Vac @ 20V/3.25A		



### Technical Specifications

	<b>Input frequency range</b>	47 to 63 Hz
	<b>Input AC current</b>	1.7 A at 90 VAC and maximum load
	<b>Output power</b>	65 W
	<b>DC output</b>	5V/9V/10V/12V/15V/20V
	<b>Hold-up time</b>	5ms at 115 VAC input
	<b>Output current limit</b>	<8.0A
<b>Connector</b>	USB Type-C®	
<b>Environmental Design</b>	<b>Operating temperature</b>	32° F to 95° F (0° to 35° C)
	<b>Non-operating (storage) temperature</b>	-4° F to 185° F (-20° to 85° C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	5% to 95%
	<b>Storage Humidity</b>	5% to 95%
<b>EMI and Safety Certifications</b>	*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	

<b>AC Adapter 45 Watt nPFC USB Type-C®</b>	<b>Dimensions</b>	94.0mm x 40.0mm x 26.5mm
	<b>Weight</b>	192.5g +/-10% <a href="#">Not including power cord. Power cord varies by country</a>
	<b>Input</b>	<b>Input Efficiency</b> Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 12V : 87.41% 15V : 87.8%
		<b>Input frequency range</b> 47 to 63 Hz
		<b>Input AC current</b> Max. 1.4 A at 90 VAC
		<b>Output power</b> 5V/15W 9V/27W 12V/36W 15V/45W
		<b>DC output</b> 5V/9V/12V/15V
		<b>Hold-up time</b> 5ms at 115 VAC input
		<b>Output current limit</b> <5.0 A
<b>Connector</b>	USB Type-C®	
<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)



### Technical Specifications

<b>EMI and Safety Certifications</b>	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
	*CE Mark - full compliance with LVD and EMC directives	
	* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.	
	* MTBF - over 200,000 hours at 25°C ambient condition.	

<b>3 Cell WHr 45 Long Life - Polymer HP Fast Charge Technology<sup>1</sup></b>	<b>Dimensions (H x W x L)</b>	6.0 x 184.7 x 88.9 mm
	<b>Weight</b>	0.22 kg (0.48 lb)
	<b>Cells/Type</b>	3cell Lithium-Ion
	<b>Voltage</b>	11.55 V
	<b>Amp-hour capacity</b>	3.900 Ah
	<b>Watt-hour capacity</b>	45 Wh
	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
	<b>Optional Travel Battery Available</b>	No

1. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 50% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.



### Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part Number
<b>Cases</b>	HP Essential Top Load Case	H2W17AA
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP 17.3 Business Backpack	2SC67AA
<b>Docking</b>	HP USB-C Mini Dock	1PM64AA
	HP Thunderbolt Dock 120W G2	2UK37AA
	HP TB Dock G2 w/ Combo Cable	3TR87AA
	HP TB Dock 120W G2 w/Audio	3YE87AA
	HP TB Dock 120W G2 Cable	3XB94AA
	HP TB Dock G2 Combo Cable	3XB96AA
	HP TB Dock G2 Audio Module	3AQ21AA
	HP USB-C/A Universal Dock G2	5TW13AA
	HP USB-C Dock G5	5TW10AA
<b>Input / Output</b>	HP USB Essential Keyboard and Mouse	H6L29AA
	HP Bluetooth Travel Mouse	6SP30AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP HDMI to DVI Adapter	F5A28AA
	HP Elite USB-C Hub	4WX89AA
	HP USB-C Travel Hub G2	7PJ38AA
<b>Power</b>	HP 45W Smart AC Adapter 4.5mm	H6Y88AA
	65W Smart Power Adapter (w/ 4.5mm to 7.5mm DC dongle)	H6Y89AA
	HP 65W Slim AC Adapter	H6Y82AA
	HP 65W USB-C Slim Power Adapter	3PN48AA
	HP 65W USB-C Power Adapter	1HE08AA
	HP 45W USB-C Power Adapter	1HE07AA
	HP Power Bank	N9F71AA
	HP USB-C Power Bank	2NA10AA
<b>Storage</b>	HP External USB Optical Drive	F2B56AA
<b>Security</b>	HP Keyed Cable Lock 10mm	T1A62AA
	HP Sure Key Cable Lock	6UW42AA



Options and Accessories (sold separately and availability may vary by country)

Displays	HP E223d Docking Monitor (Santino)	5VT82A8/5VT82AA
	HP E243d Docking Monitor (Sonny)	1TJ76AA
	HP E273d Docking Monitor (Vito)	5WN63A8/5WN63AA
	HP EliteDisplay E244d Monitor (Sand Dollar)	6PA50A8/6PA50AA
	HP EliteDisplay E274d Monitor (Glomar)	6PA56A8/6PA56AA





### Summary of Changes

Date of change:	Version History:		Description of change:
April 29, 2020	V1 to V2	Updated	MIL-STD 810G to MIL-STD 810H
May 7, 2020	V2 to V3	Updated	Ethernet Section
May 28, 2020	V3 to V4	Updated	Ports and Memory Section
August 31, 2020	V4 to V5	Updated	Processor Section
September 22, 2020	V5 to V6	Updated	Display Section

Copyright © 2020 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

AMD, Ryzen and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. SD, SDHC and SDXC are registered trademarks of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Wi-Fi® and Wi-Fi CERTIFIED™ are trademarks or registered trademarks of Wi-Fi Alliance®.

