

### Overview

#### HP ProBook 455 G8 Notebook PC



#### Left

- |  |  |
|--|--|
| 1. Internal Microphones (2)                    | 5. Clickpad  |
| 2. Webcam LED (Optional)                       | 6. SuperSpeed USB Type-A 5Gbps signaling rate Port |
| 3. HD and IR Camera (Optional)                 | 7. Ethernet Port (RJ-45)                           |
| 4. Camera Shutter (Only available with webcam) | 8. Nano Security Lock Slot (Lock sold separately)  |
| 5. IR Camera LED (Optional)                    |  |

### Overview



#### Right

- |  |   |
|--|---|
| 1. Power Connector   | 6. Audio Combo Jack                         |
| 2. SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) | 7. Micro SD Card Reader                     |
| 3. SuperSpeed USB Type-A 5Gbps signaling rate Charging Port                            | 8. Touch Fingerprint Sensor (Select models) |
| 4. SuperSpeed USB Type-A 5Gbps signaling rate Port                                     |   |
| 5. HDMI Port 1.4b (Cable not included)   |   |

### Overview

#### AT A GLANCE

- A new compact design with lift-anywhere edge and configurable all metal chassis
- Choice of AMD Cezanne™ 5000 series mobile processors, R7, R5 and R3
- Preinstalled with Windows 10 versions or FreeDOS
- Integrated AMD Radeon™ Vega graphics
- Fast and upgradeable dual channel DDR4 SODIMM memory up to 32 GB
- Choice of 39.62 cm (15.6") diagonal HD, Ultra-Wide Viewing Angle FHD, Touch or Non-Touch screen, and Privacy Panel option
- Features redesigned quiet and responsive HP Keyboard with the HP Programmable key and backlit options
- Choice of solid state drives up to 1 TB
- Multi-layered security with HP SureStart Gen6, HP Privacy Camera, HP Sure View Gen3 , HP Sure Sense, HP Sure Click, and optional Touch Fingerprint sensor
- Supports wireless options for connectivity on the go including gigabit-speed Wi-Fi 6
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support optional HP docking solutions including the HP Universal Dock G5
- Undergoes MIL-STD 810H tests <sup>1</sup>
- Battery Life TBD

1. MIL-STD 810H is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

### Technical Specifications

#### PRODUCT NAME

HP ProBook 455 G8 Notebook PC

#### OPERATING SYSTEM

**Preinstalled** Windows 10 Pro 64 – HP recommends Windows 10 Pro for business <sup>1</sup>  
Windows 10 Pro 64 (National Academic License) <sup>2</sup>  
Windows 10 Home 64 <sup>1</sup>  
Windows 10 Home Single Language 64 <sup>1</sup>  
Windows 10 Pro (Windows 10 Enterprise available with a Volume Licensing Agreement) <sup>1</sup>  
Windows 10 Enterprise 64<sup>1</sup> (Web support)  
FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

Note: HP tested Windows 10, version 1909 on this platform. For testing information on newer versions of Windows 10, please see <https://support.hp.com/document/c05195282>.

#### PROCESSORS

AMD Ryzen™ 3 5400U APU with AMD Radeon™ Graphics (2.6 GHz base clock, up to 4.0 GHz max boost clock, 8 MB L3 cache, 4 cores)<sup>3,4,5,6</sup>

AMD Ryzen™ 5 5600U APU with AMD Radeon™ Graphics (2.3 GHz base clock, up to 4.2 GHz max boost clock, 16MB L3 cache, 6 cores)<sup>3,4,5,6</sup>

AMD Ryzen™ 7 5800U APU with AMD Radeon™ Graphics (1.9 GHz base clock, up to 4.4 GHz max boost clock, 16 MB L3 cache, 8 cores)<sup>3,4,5,6</sup>

##### Processor Family

AMD Cezanne™ 5000 Series Mobile Processors <sup>6</sup>

3. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

4. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.

5. AMD Max Burst frequency performance varies depending on hardware, software and overall system configuration.

6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

### Technical Specifications

---

#### GRAPHICS

##### Integrated

AMD Radeon™ Graphics

##### Supports

Supports HD decode, DX12, HDMI 1.4 <sup>7</sup>

7. HDMI cable not included.

---

#### DISPLAY

##### Non-Touch

39.6 cm (15.6") diagonal HD SVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1366 x 768) <sup>9,10</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD camera (1366 x 768) <sup>9,10</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD+IR camera (1366 x 768) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP+PSR anti-glare, low power narrow bezel bent, 400 nits, 100% sRGB for HD camera (1920 x 1080) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP+PSR anti-glare, low power narrow bezel bent, 400 nits, 100% sRGB for HD+IR camera (1920 x 1080) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC (1920 x 1080) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD camera (1920 x 1080) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP anti-glare, narrow bezel bent, 250 nits, 45% NTSC for HD + IR camera (1920 x 1080) <sup>9,10</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP+PSR anti-glare, narrow bezel bent with HP Sure View Gen3 Integrated Privacy Screen, 1000 nits, 100% sRGB for HD camera (1920 x 1080) <sup>9,10,11,12</sup>

39.6 cm (15.6") diagonal FHD UWVA eDP+PSR anti-glare, narrow bezel bent with HP Sure View Gen3 Integrated Privacy Screen, 1000 nits, 100% sRGB for HD+IR camera (1920 x 1080) <sup>9,10,11,12</sup>

##### HDMI <sup>8</sup>

HDMI 1.4 up to 4K 30Hz

8. HDMI cable not included.

9. FHD/HD content required to view FHD/HD images.

10. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

11. Actual brightness will be lower with touchscreen or Sure View.

12. HP Sure View integrated privacy screen is an optional feature that must be configured at purchase and is designed to function in landscape orientation.

---

### Technical Specifications

#### STORAGE AND DRIVES

##### Primary M.2 Storage

- 128 GB PCIe® NVMe™ M.2 TLC Solid State Drive <sup>13</sup>
- 256 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13</sup>
- 1 TB PCIe® NVMe™ M.2 TLC Solid State Drive <sup>13</sup>
- 512 GB PCIe® NVMe™ M.2 Value Solid State Drive <sup>13</sup>

<sup>13</sup>. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

---

#### MEMORY

##### Maximum Memory

- 32 GB DDR4-3200 SDRAM <sup>14</sup>

##### Memory

- 32 GB DDR4-3200 SDRAM (2 x 16 GB) <sup>14</sup>
- 16 GB DDR4-3200 SDRAM (1 x 16 GB) <sup>14</sup>
- 12 GB DDR4- 3200 SDRAM (1 x 4 GB + 1 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (1 x 8 GB) <sup>14</sup>
- 8 GB DDR4-3200 SDRAM (2 x 4 GB) <sup>14</sup>
- 4 GB DDR4-3200 SDRAM (1 x 4 GB) <sup>14</sup>

##### Memory Slots

- 2 SODIMM
- Both slots are accessible/upgradeable by IT or self-maintainers only.
- DDR4 PC4 SODIMMS, system runs at 3200
- Supports Dual Channel Memory

<sup>14</sup>. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

---

### Technical Specifications

#### NETWORKING/COMMUNICATIONS

##### WLAN

Realtek 802.11ac (2x2) WLAN and Bluetooth® 5 Combo <sup>15</sup>

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) WLAN and Bluetooth® 5 Combo, non-vPro® <sup>15</sup>

Intel® Dual Band Wi-Fi 6 AX201 802.11a/b/g/n/ac/ax (2x2) WLAN and Bluetooth® 5 Combo, non-vPro® <sup>17</sup>

##### Ethernet

Realtek 10/100/1000 GbE NIC <sup>16</sup>

15. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.

16. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

17. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11 ax) is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax WLAN devices. Only available in countries where 802.11ax is supported.

---

#### AUDIO/MULTIMEDIA

##### Audio

2 Integrated stereo speakers

Integrated microphone (Dual Array)

##### Speaker Power

2W/4ohm per speaker

##### Camera

720p HD camera <sup>9</sup>

720p HD camera+IR Camera <sup>9,18</sup>

9.FHD/HD content required to view FHD/HD images.

18. Sold separately or as an optional feature.

### Technical Specifications

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

##### Keyboard

HP Premium Keyboard, spill resistant and optional Durakeys and backlit

##### Pointing Device

Clickpad with multi-touch gesture support

##### Function Keys

F1 - Display Switching  
F2 - Blank or SureView On/Off  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Audio Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Blank or Backlit Toggle  
F10 - Insert  
F11 - Airplane Mode  
F12 - Programmable key  
Print Screen  
Power Button (with LED)

##### Hidden Function Keys

Fn+R - Break  
Fn+S - Sys Rq  
Fn+C - Scroll Lock

---

#### SOFTWARE AND SECURITY

##### BIOS

HP BIOSphere Gen6 <sup>19</sup>  
HP Drive Lock & Automatic Drive Lock  
BIOS Update via Network  
HP Secure Erase <sup>20</sup>  
Absolute Persistence Module <sup>21</sup>  
HP LAN-Wireless Protection  
USB enable/disable (via BIOS)

##### Software

HP Connection Optimizer <sup>22</sup>  
HP Hotkey Support  
myHP  
HP Support Assistant<sup>23</sup>  
HP QuickDrop<sup>24</sup>  
HP PC Hardware Diagnostics Windows  
HP Noise Cancellation Software



## Technical Specifications

Touchpoint Customizer for Commercial  
HP Notifications  
HP Privacy Settings  
HP Wireless Button Driver  
HP Power Manager  
HP WorkWell  
Buy Microsoft Office (Sold separately)  
Microsoft Defender <sup>25</sup>

### Manageability Features

HP Driver Packs (download) <sup>26</sup>  
HP Manageability Integration Kit Gen4 (download) <sup>27</sup>  
HP Client Catalog (download)  
HP Client Management Script Library (download)  
HP Image Assistant (download)  
Ivanti Management Suite (download)

### Security Management

HP Pro Security Edition (Select models)<sup>28</sup>  
HP Fingerprint Sensor (Select models) <sup>29</sup>  
HP Sure Click <sup>30</sup>  
HP Sure Sense <sup>31</sup>  
HP Sure Admin <sup>32</sup>  
Secured-core PC Enable<sup>33</sup>  
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified)(FIPS 140-2 Level 2 Certified)

19. HP BIOSphere Gen6 requires Windows 10 and is available on select HP Pro and Elite PCs. Features may vary depending on the platform and configurations

20. HP Secure Erase For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

21. Absolute firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit:

<https://www.absolute.com/about/legal/agreements/absolute/>

22. HP Connection Optimizer requires Windows 10.

23. HP Support Assistant requires Windows and Internet access.

24. HP Quick Drop requires Internet access and Windows 10 PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

25. Microsoft Defender Opt in and internet connection required for updates.

26. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

27. HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.

28. HP Pro Security Edition is available preloaded on select HP PCs and includes HP Sure Click Pro and HP Sure Sense Pro. 3-year license required. The HP Pro Security Edition software is licensed under the license terms of the HP End User License Agreement (EULA) that can be found at: [https://h30670.www3.hp.com/e-commerce/common/disclaimer.do#EN\\_US](https://h30670.www3.hp.com/e-commerce/common/disclaimer.do#EN_US) as modified by the following: "7. Term. Unless otherwise terminated earlier pursuant to the terms contained in this EULA, the license for the HP Pro Security Edition (HP Sure Sense Pro and HP Sure Click Pro) is effective upon activation and will continue for thirty-six (36) months thereafter ("Initial Term"). At the end of the Initial Term you may either (a) purchase a renewal license for the HP Pro Security Edition from HP.com, HP Sales or an HP Channel Partner, or (b) continue using the standard

### Technical Specifications

versions of HP Sure Click and HP Sure Sense at no additional cost with no future software updates or HP Support.” HP Pro Security Edition is optimized for the SMB environment and ships pre-configured - manageability is optional. The HP Pro Security Edition supports a limited tool set that can be used by the HP Manageability Integration Kit which can be downloaded from <http://www.hp.com/go/clientmanagement>.

29. HP Fingerprint sensor is an optional feature that must be configured at purchase.

30. HP Sure Click requires Windows 10 Pro or Enterprise. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

31. HP Sure Sense is available on select HP PCs and is not available with Windows 10 Home.

32. HP Sure Admin requires Windows 10, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

33. Requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC functionality can be enabled from the factory.

---

## POWER

### Power Supply

HP Smart 65 W External AC power adapter <sup>34</sup>

HP Smart 65 W EM External AC power adapter <sup>34</sup>

HP Smart 65 W USB Type-C adapter <sup>34</sup>

HP Smart 45 W External AC power adapter <sup>34</sup>

HP Smart 45 W USB Type-C adapter <sup>34</sup>

### Power Cord

3-wire plug - 1m <sup>34</sup>

2-wire plug - 1m <sup>34</sup>

### Primary Battery

HP Long Life 3-cell, 45 Wh Polymer <sup>35,36</sup>

### Battery Life

Up to TBD hours and TBD minutes <sup>37</sup>

### Battery Weight

0.42 lb

190 g

34. Availability may vary by country.

35. Battery is internal and not replaceable by customer. Serviceable by warranty.

36. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

37. Windows 10 MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See [www.bapco.com](http://www.bapco.com) for additional details.

### Technical Specifications

#### WEIGHTS & DIMENSIONS

**Product Weight**

Starting at 3.83 lb <sup>38</sup>

Starting at 1.74 kg <sup>38</sup>

**Product Dimensions (w x d x h)**

35.94 x 23.39 x 1.99 cm 14.15 x 9.21 x 0.78 in

[38. Weight will vary by configuration.](#)

---

#### PORTS/SLOTS

1 SuperSpeed USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

3 SuperSpeed USB Type-A 5 Gbps signaling rate Port (1 Charging, 1 powered port)

1 HDMI 1.4b <sup>39</sup>

1 RJ-45

1 Headphone/microphone combo jack

1 AC power

**Expansion Slots**

1 micro SD

Supports SD, SDHC, SDXC

[39. HDMI cable sold separately.](#)

---

#### SERVICE AND SUPPORT

1-year or 3-year limited warranty and 90 day software limited warranty options depending on country.

Batteries have a default one year limited warranty except for HP Long Life batteries which will follow the one or three year warranty of the platform. Refer to <http://www.hp.com/support/batterywarranty/>

for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at:

<http://www.hp.com/go/cpc>. <sup>40</sup>

[40. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.](#)

### Technical Specifications

#### SYSTEM UNIT

##### Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	19V
Average Operating Power	8.1W (Idle)
Integrated graphics	Yes
Discrete Graphics	N/A
	Discrete < 65W
Max Operating Power	UMA < 45W

##### Temperature

Operating	32° to 95° F (0° to 35° C)
Non-operating	-4° to 140° F (-20° to 60° C)

##### Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature

##### Shock

Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine

##### Random Vibration

Operating	0.75 grms
Non-operating	1.50 grms

##### Altitude (unpressurized)

Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)

##### Planned Industry Standard Certifications

UL	Yes
CSA	Yes
FCC Compliance	Yes
ENERGY STAR®	Select models <sup>41</sup>
EPEAT	EPEAT 2019 Gold in United States <sup>42</sup>
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes

41. Configurations of the HP ProBook 455 G8 that are ENERGY STAR® qualified are identified as HP ProBook 455 G8 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

42. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit [www.epeat.net](http://www.epeat.net) for more information.

### Technical Specifications

#### DISPLAYS

1. Actual brightness will be lower with touchscreen or sure view.

Note: all specifications represent the typical specifications provided by hp's component manufacturers; actual performance may vary either higher or lower.

**Panel LCD 15.6 inch FHD  
(1920x1080) Anti-Glare WLED  
UWVA 45percent cg 250nits eDP  
1.2 w/o PSR bent NWBZ**

<b>Outline Dimensions (W x H x D)</b>	350.96 x 205.54 mm (max)
<b>Active Area</b>	344.16 x 193.59 mm (typ.)
<b>Weight</b>	370 g (max)
<b>Diagonal Size</b>	15.6 inch
<b>Thickness</b>	3.0 mm/ 5.0 mm (w/PCB) (max)
<b>Interface</b>	eDP 1.2 (2 lane)
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	600:1 (typ.)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	250 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB Stripe
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	NTSC 45%
<b>Color Depth</b>	6 bits (Hi FRC supportive w/ condition to enable)
<b>Viewing Angle</b>	UWVA 85/85/85/85

**Panel LCD 15.6 inch FHD  
(1920x1080) Anti-Glare WLED  
UWVA sRGB 100percent cg  
400nits eDP 1.4+PSR2 bent LP  
NWBZ**

<b>Outline Dimensions (W x H x D)</b>	349.46 x 204.79 mm (max)
<b>Active Area</b>	344.16 x 193.59 mm (typ.)
<b>Weight</b>	325 g (max)
<b>Diagonal Size</b>	15.6 inch
<b>Thickness</b>	2.6mm / 4.6mm (PCB) (max)
<b>Interface</b>	eDP 1.4
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	1200:1 (typ.)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	400 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB Stripe
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	sRGB 100%
<b>Color Depth</b>	8 bit
<b>Viewing Angle</b>	UWVA 85/85/85/85

### Technical Specifications

**Panel LCD 15.6-in FHD  
(1920x1080) Anti-Glare WLED  
UWVA 72percent cg 1000nits eDP  
1.4+PSR2 PrivacyG3 NWBZ bent**

<b>Outline Dimensions (W x H x D)</b>	349.52x 205.39 mm (max)
<b>Active Area</b>	344.16 x 193.59 mm (typ.)
<b>Weight</b>	350 g (max)
<b>Diagonal Size</b>	15.6 inch
<b>Thickness</b>	2.6mm / 4.5mm Max. (PCB side)
<b>Interface</b>	eDP 1.4 + PSR (4 lane)
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	2000:1 (typ.)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	1000 nits <sup>1</sup>
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	sRGB 100%
<b>Color Depth</b>	8 bits
<b>Viewing Angle</b>	UWVA 85/85/85/85

**Panel LCD 15.6-in HD (1366x768)  
Anti-Glare WLED SVA 45percent  
cg 250nits eDP 1.2 w/o PSR  
NWBZ bent**

<b>Outline Dimensions (W x H x D)</b>	350.96 x 205.54 (mm) max
<b>Active Area</b>	344.23 x 193.54 mm (typ.)
<b>Weight</b>	370 g max
<b>Diagonal Size</b>	15.6"
<b>Thickness</b>	3.2t (panel) / 5.0t (panel+PCB) max.
<b>Interface</b>	eDP 1.2 (1 lane)
<b>Surface Treatment</b>	Anti-Glare
<b>Touch Enabled</b>	No
<b>Contrast Ratio</b>	300:1 (typ)
<b>Refresh Rate</b>	60 Hz
<b>Brightness</b>	250nits
<b>Pixel Resolution</b>	1366 x 768 (HD)
<b>Format</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	NTSC 45%
<b>Color Depth</b>	6 bits
<b>Viewing Angle</b>	SVA 45/45/15/35

### Technical Specifications

#### STORAGE<sup>1</sup>

1. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

<b>SSD 128GB 2280 PCIe-3x2 Three Layer Cell</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	128 GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.02 lb (10 g)
	<b>Interface</b>	PCIe NVMe
	<b>Maximum Sequential Read</b>	1400 ~ 2100 MB/s
	<b>Maximum Sequential Write</b>	800 ~ 1200 MB/s
	<b>Logical Blocks</b>	250,069,680
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security; DIPM; TRIM; DEVSLP
<b>SSD 1TB 2280 PCIe-3x4 NVMe Three Layer Cell single-sided</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	1 TB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.02 lb (10 g)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	3100 ~ 3500 MB/s
	<b>Maximum Sequential Write</b>	2770 ~ 3037 MB/s
	<b>Logical Blocks</b>	2,000,409,264
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security; TRIM; L1.2
<b>SSD 256GB 2280 PCIe NVMe Value</b>	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	Value
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.02 lb (10 g)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	2100 ~ 2200 MB/s
	<b>Maximum Sequential Write</b>	900 ~ 1400 MB/s
	<b>Logical Blocks</b>	500,118,192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	ATA Security (optional); TRIM; L1.2	

### Technical Specifications

<b>SSD 512GB 2280 PCIe NVMe Value</b>	<b>Capacity</b>	512 GB
	<b>NAND Type</b>	Value
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.02 lb (10 g)
	<b>Interface</b>	PCIe NVMe Gen3
	<b>Maximum Sequential Read</b>	2200 ~ 2300 MB/s
	<b>Maximum Sequential Write</b>	1000 ~ 1600 MB/s
	<b>Logical Blocks</b>	1,000,215,215
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	ATA Security (optional); TRIM; L1.2



### Technical Specifications

#### NETWORKING

<b>Intel® Wi-Fi 6 AX200 + Bluetooth® 5 (802.11ax 2x2, supporting gigabit data rate) (non-vPro)<sup>1,5</sup></b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	<b>Interoperability</b>	Features Wi-Fi 6 technology
	<b>Frequency Band</b>	802.11b/g/n/ax •2.402 – 2.482 GHz 802.11a/n/ac/ax •4.9 – 4.95 GHz (Japan) •5.15 – 5.25 GHz •5.25 – 5.35 GHz •5.47 – 5.725 GHz •5.825 – 5.850 GHz
	<b>Data Rates</b>	•802.11b: 1, 2, 5.5, 11 Mbps •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) •802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz) •802.11ax: MCS0 ~ MCS11, (1SS and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)
	<b>Modulation</b>	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	<b>Security<sup>3</sup></b>	•IEEE compliant 64 / 128-bit WEP encryption for a/b/g mode only •AES-CCMP: 128 bit in hardware •802.1x authentication •WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. •WPA2 certification •WPA3 certification •IEEE 802.11i •WAPI
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>2</sup></b>	• 802.11b: +18.5dBm minimum • 802.11g: +17.5dBm minimum • 802.11a: +18.5dBm minimum • 802.11n HT20(2.4GHz): +15.5dBm minimum • 802.11n HT40(2.4GHz): +14.5dBm minimum

### Technical Specifications

	<ul style="list-style-type: none"> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ac VHT160(5GHz): +11.5dBm minimum</li> <li>• 802.11ax HT40(2.4GHz): +10dBm minimum</li> <li>• 802.11ax VHT160(5GHz): +10dBm minimum</li> </ul>				
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode: 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>				
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode				
<b>Receiver Sensitivity<sup>4</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b, 1Mbps: -93.5dBm maximum</li> <li>• 802.11b, 11Mbps: -84dBm maximum</li> <li>• 802.11a/g, 6Mbps: -86dBm maximum</li> <li>• 802.11a/g, 54Mbps: -72dBm maximum</li> <li>• 802.11n, MCS07: -67dBm maximum</li> <li>• 802.11n, MCS15: -64dBm maximum</li> <li>• 802.11ac, MCS0: -84dBm maximum</li> <li>• 802.11ac, MCS9: -59dBm maximum</li> <li>• 802.11ax, MCS11(HT40): -59dBm maximum</li> <li>• 802.11ax, MCS11(VHT160): -58.5dBm maximum</li> </ul>				
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications				
<b>Form Factor</b>	PCI-Express M.2 MiniCard				
<b>Dimensions</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.3 x 22.0 x 30.0 mm</li> <li>2. Type 1216: 1.67 x 12.0 x 16.0 mm</li> </ol>				
<b>Weight</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.8g</li> <li>2. Type 126: 1.3g</li> </ol>				
<b>Operating Voltage</b>	3.3v +/- 9%				
<b>Temperature</b>	<table> <tbody> <tr> <td>Operating</td> <td>14° to 158° F (-10° to 70° C)</td> </tr> <tr> <td>Non-operating</td> <td>-40° to 176° F (-40° to 80° C)</td> </tr> </tbody> </table>	Operating	14° to 158° F (-10° to 70° C)	Non-operating	-40° to 176° F (-40° to 80° C)
Operating	14° to 158° F (-10° to 70° C)				
Non-operating	-40° to 176° F (-40° to 80° C)				
<b>Humidity</b>	<table> <tbody> <tr> <td>Operating</td> <td>10% to 90% (non-condensing)</td> </tr> <tr> <td>Non-operating</td> <td>5% to 95% (non-condensing)</td> </tr> </tbody> </table>	Operating	10% to 90% (non-condensing)	Non-operating	5% to 95% (non-condensing)
Operating	10% to 90% (non-condensing)				
Non-operating	5% to 95% (non-condensing)				
<b>Altitude</b>	<table> <tbody> <tr> <td>Operating</td> <td>0 to 10,000 ft (3,048 m)</td> </tr> <tr> <td>Non-operating</td> <td>0 to 50,000 ft (15,240 m)</td> </tr> </tbody> </table>	Operating	0 to 10,000 ft (3,048 m)	Non-operating	0 to 50,000 ft (15,240 m)
Operating	0 to 10,000 ft (3,048 m)				
Non-operating	0 to 50,000 ft (15,240 m)				
<b>LED Activity</b>	LED Amber – Radio OFF; LED OFF – Radio ON				

### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0/5.1 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps

### Technical Specifications

#### Transmit Power

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 9.5 dBm for BR and EDR.

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs. The specifications for Wi-Fi 6 (802.11ax) are draft and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ax devices. Only available in countries where 802.11ax is supported.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. Wi-Fi 5 or 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

**Intel® 9260  
802.11a/b/g/n/ac (2x2)  
Wi-Fi® and Bluetooth® 5.0  
Combo<sup>1</sup> (Non-vPro)**

#### Wireless LAN Standards

IEEE 802.11a  
IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n  
IEEE 802.11ac  
IEEE 802.11d  
IEEE 802.11e  
IEEE 802.11h  
IEEE 802.11i  
IEEE 802.11k  
IEEE 802.11r  
IEEE 802.11v

#### Interoperability Frequency Band

Wi-Fi CERTIFIED modules  
802.11b/g/n  
•2.402 – 2.482 GHz  
802.11a/n/ac  
•4.9 – 4.95 GHz (Japan)  
•5.15 – 5.25 GHz  
•5.25 – 5.35 GHz  
•5.47 – 5.725 GHz  
•5.825 – 5.850 GHz

#### Data Rates

•802.11b: 1, 2, 5.5, 11 Mbps  
•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)  
•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, 80MHz & 160MHz)

#### Modulation

Direct Sequence Spread Spectrum  
BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM

### Technical Specifications

<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>•IEEE compliant 64 / 128-bit WEP encryption for a/b/g mode only</li> <li>•AES-CCMP: 128 bit in hardware</li> <li>•802.1x authentication</li> <li>•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>•WPA2 certification</li> <li>•WPA3 certification</li> <li>•IEEE 802.11i</li> <li>•WAPI</li> </ul>				
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)				
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points				
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +18.5dBm minimum</li> <li>• 802.11g: +17.5dBm minimum</li> <li>• 802.11a: +18.5dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +14.5dBm minimum</li> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> <li>• 802.11ac VHT160(5GHz): +11.5dBm minimum</li> </ul>				
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>•Transmit mode: 2.0 W</li> <li>•Receive mode 1.6 W</li> <li>•Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>•Idle mode 50 mW (WLAN unassociated)</li> <li>•Connected Standby 10mW</li> <li>•Radio disabled 8 mW</li> </ul>				
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode				
<b>Receiver Sensitivity<sup>4</sup></b>	<ul style="list-style-type: none"> <li>•802.11b, 1Mbps: -93.5dBm maximum</li> <li>•802.11b, 11Mbps: -84dBm maximum</li> <li>•802.11a/g, 6Mbps: -86dBm maximum</li> <li>•802.11a/g, 54Mbps: -72dBm maximum</li> <li>•802.11n, MCS07: -67dBm maximum</li> <li>•802.11n, MCS15: -64dBm maximum</li> <li>•802.11ac, MCS0: -84dBm maximum</li> <li>•802.11ac, MCS9: -59dBm maximum</li> </ul>				
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications				
<b>Form Factor</b>	PCI-Express M.2 MiniCard				
<b>Dimensions</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.3 x 22.0 x 30.0 mm</li> <li>2. Type 1216: 1.67 x 12.0 x 16.0 mm</li> </ol>				
<b>Weight</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.8g</li> <li>2. Type 126: 1.3g</li> </ol>				
<b>Operating Voltage</b>	3.3v +/- 9%				
<b>Temperature</b>	<table> <tr> <td>Operating</td> <td>14° to 158° F (-10° to 70° C)</td> </tr> <tr> <td>Non-operating</td> <td>-40° to 176° F (-40° to 80° C)</td> </tr> </table>	Operating	14° to 158° F (-10° to 70° C)	Non-operating	-40° to 176° F (-40° to 80° C)
Operating	14° to 158° F (-10° to 70° C)				
Non-operating	-40° to 176° F (-40° to 80° C)				
<b>Humidity</b>	<table> <tr> <td>Operating</td> <td>10% to 90% (non-condensing)</td> </tr> <tr> <td>Non-operating</td> <td>5% to 95% (non-condensing)</td> </tr> </table>	Operating	10% to 90% (non-condensing)	Non-operating	5% to 95% (non-condensing)
Operating	10% to 90% (non-condensing)				
Non-operating	5% to 95% (non-condensing)				

### Technical Specifications

<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED OFF – Radio ON	

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

<b>Realtek RTL8822CE 802.11ac 2x2 Wi-Fi® + Bluetooth® 5<sup>1</sup></b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	<b>Interoperability</b>	Wi-Fi certified modules
	<b>Frequency Band</b>	802.11b/g/n •2.402 – 2.482 GHz 802.11a/n/ac •4.9 – 4.95 GHz (Japan) •5.15 – 5.25 GHz •5.25 – 5.35 GHz •5.47 – 5.725 GHz •5.825 – 5.850 GHz

### Technical Specifications

<b>Data Rates</b>	<ul style="list-style-type: none"> <li>•802.11b: 1, 2, 5.5, 11 Mbps</li> <li>•802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>•802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>•802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz &amp; 80MHz)</li> </ul>
<b>Modulation</b>	<p>Direct Sequence Spread Spectrum            BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM</p>
<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>•IEEE and Wi-Fi certified 64 / 128-bit WEP encryption for a/b/g mode only</li> <li>•AES-CCMP: 128 bit in hardware</li> <li>•802.1x authentication</li> <li>•WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>•WPA2 certification</li> <li>•WPA3 certification</li> <li>•IEEE 802.11i</li> <li>•WAPI</li> </ul>
<b>Network Architecture Models</b>	<p>Ad-hoc (Peer to Peer)            Infrastructure (Access Point Required)</p>
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +18.5dBm minimum</li> <li>• 802.11g: +17.5dBm minimum</li> <li>• 802.11a: +18.5dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +14.5dBm minimum</li> <li>• 802.11n HT20(5GHz): +15.5dBm minimum</li> <li>• 802.11n HT40(5GHz): +14.5dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +11.5dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>•Transmit mode: 2.0 W</li> <li>•Receive mode 1.6 W</li> <li>•Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>•Idle mode 50 mW (WLAN unassociated)</li> <li>•Connected Standby/Modern Standby: 10mW</li> <li>•Radio disabled 8 mW</li> </ul>
<b>Power Management</b>	<p>ACPI and PCI Express compliant power management            802.11 compliant power saving mode</p>
<b>Receiver Sensitivity<sup>4</sup></b>	<ul style="list-style-type: none"> <li>•802.11b, 1Mbps: -93.5dBm maximum</li> <li>•802.11b, 11Mbps: -84dBm maximum</li> <li>•802.11a/g, 6Mbps: -86dBm maximum</li> <li>•802.11a/g, 54Mbps: -72dBm maximum</li> <li>•802.11n, MCS07: -67dBm maximum</li> <li>•802.11n, MCS15: -64dBm maximum</li> <li>•802.11ac, MCS0: -84dBm maximum</li> <li>•802.11ac, MCS9: -59dBm maximum</li> </ul>
<b>Antenna type</b>	<p>High efficiency antenna with spatial diversity, mounted in the display enclosure            Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications</p>
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.3 x 22.0 x 30.0 mm</li> <li>2. Type 1216: 1.67 x 12.0 x 16.0 mm</li> </ol>
<b>Weight</b>	<ol style="list-style-type: none"> <li>1. Type 2230: 2.8g</li> <li>2. Type 126: 1.3g</li> </ol>

### Technical Specifications

<b>Operating Voltage</b>	3.3v +/- 9%	
<b>Temperature</b>	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
<b>Humidity</b>	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED OFF – Radio ON	

### HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0 Wireless Technology

<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0 Compliant	
<b>Frequency Band</b>	2402 to 2480 MHz	
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)	
<b>Data Rates and Throughput</b>	Legacy: 3 Mbps data rate; throughput up to 2.17 Mbps BLE: 1 Mbps data rate; throughput up to 0.2 Mbps Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)	
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.	

1. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 5 (802.11 ac) is backwards compatible with prior 802.11 specs.
2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

### Realtek RTK8111HSH 10/100/1000 Integrated NIC

<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload

### Technical Specifications

	Receiving Side Scaling Jumbo Frame 9K
<b>Manageability</b>	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
<b>Interface</b>	Auto MDI/MDIX Crossover cable detection
<b>NIC Device Driver Name</b>	Realtek PCIe GBE Ethernet Family Controller

---



### Technical Specifications

#### POWER

<b>AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.0m</b>	<b>Dimensions</b>	95x45x26.8mm
	<b>Weight</b>	unit: 200g +/- 10g
	<b>Input</b>	
	<b>Input Efficiency</b>	87.74 % at 115 Vac and 88.4 % at 230Vac
	<b>Input frequency range</b>	47 ~ 63 Hz
	<b>Input AC current</b>	Max. 1.4 A at 90 Vac
	<b>Output</b>	
	<b>Output power</b>	45W
	<b>DC output</b>	19.5V
	<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Output current limit</b>	<8.0A
	<b>Connector</b>	
	<b>Connector</b>	4.5mm Barrel Type
	<b>Environmental Design</b>	
	<b>Operating temperature</b>	32oF to 95oF (0oto 35oC)
	<b>Non-operating (storage) temperature</b>	-4oF to 185oF (-20oto 85oC)
	<b>Non-operating (storage) temperature</b>	
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	

---

<b>AC Adapter 45 Watt nPFC Standard USB type C Straight 1.0m</b>	<b>Dimensions</b>	94.0mm * 40.0mm * 26.5mm
	<b>Weight</b>	192.5g +/-10%
	<b>Input</b>	
	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%
	<b>Input frequency range</b>	47 ~ 63Hz
	<b>Input AC current</b>	Max. 1.4 A at 90 Vac
	<b>Output</b>	
		5V/15W 9V/27W 12V/36W 15V/45W
	<b>Output power</b>	

### Technical Specifications

<b>DC output</b>	5V/9V/12V/15V
<b>Hold-up time</b>	5ms at 115 Vac input
<b>Output current limit</b>	
<b>Connector</b>	USB Type-C
<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	<p>Eg:</p> <ul style="list-style-type: none"> <li>*CE Mark - full compliance with LVD and EMC directives</li> <li>* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.</li> <li>* MTBF - over 200,000 hours at 25°C ambient condition.</li> </ul>

#### AC Adapter 45 Watt Smart nPFC Standard Barrel 4.5mm Right Angle 1.0m 2prong

<b>Dimensions</b>	95x45x26.8mm
<b>Weight</b>	unit: 200g +/- 10g
<b>Input</b>	
<b>Input Efficiency</b>	87.74 % at 115 Vac and 88.4 % at 230Vac
<b>Input frequency range</b>	47 ~ 63 Hz
<b>Input AC current</b>	Max. 1.4 A at 90 Vac
<b>Output</b>	
<b>Output power</b>	45W
<b>DC output</b>	19.5V
<b>Hold-up time</b>	5ms at 115 Vac input
<b>Output current limit</b>	<8.0A
<b>Connector</b>	4.5mm Barrel Type
<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%

### Technical Specifications

#### EMI and Safety Certifications

Eg:  
 \*CE Mark - full compliance with LVD and EMC directives  
 \* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.  
 \* MTBF - over 200,000 hours at 25°C ambient condition.

#### AC Adapter 65 Watt nPFC Standard USB type C@Straight 1.0m

#### Dimensions

90.0x51x28.5mm

#### Weight

unit: 250g +/- 10g

#### Input

#### Input Efficiency

81.5% min at 115 Vac/ 230Vac @ 5V/3A  
 86.7% min at 115 Vac/ 230Vac @ 9V/3A  
 88% min at 115 Vac/ 230Vac @ 12V/5A  
 89% min at 115 Vac/ 230Vac @ 15V/4.33A  
 89% min at 115 Vac/ 230Vac @ 20V/3.25A  
 47 ~ 63 Hz

#### Input frequency range

#### Input AC current

1.6 A at 90 VAC and maximum load

#### Output

#### Output power

65W

#### DC output

5V/9V/12V/15V/20V

#### Hold-up time

5ms at 115 Vac input

#### Output current limit

8.0A Max.

#### Connector

USB Type C

#### Operating temperature

32°F to 95°F (0°to 35°C)

#### Non-operating (storage) temperature

-4°F to 185°F (-20° to 85°C)

#### Altitude

0 to 16,400 ft (0 to 5000m)

#### Humidity

20% to 95%

#### Storage Humidity

10% to 95%

#### EMI and Safety Certifications

Eg:  
 \*CE Mark - full compliance with LVD and EMC directives  
 \* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.  
 \* MTBF - over 200,000 hours at 25°C ambient condition.

### Technical Specifications

**AC Adapter 65 Watt  
Smart nPFC EM Barrel  
4.5mm New EM**

<b>Dimensions</b>	102 x 55 x 30mm
<b>Weight</b>	unit: 250g +/- 10g
<b>Input</b>	
<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
<b>Input frequency range</b>	47 ~ 63 Hz
<b>Input AC current</b>	Max. 1.7 A at 90 Vac
<b>Output</b>	
<b>Output power</b>	65W
<b>DC output</b>	19.5V
<b>Hold-up time</b>	5ms at 115 Vac input
<b>Output current limit</b>	<11.0A
<b>Connector</b>	4.5mm Barrel Type
<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

**AC Adapter 65 Watt  
Smart nPFC Standard  
Barrel 4.5mm Right  
Angle 1.0m**

<b>Dimensions</b>	90 x 51 x 28.5mm
<b>Weight</b>	unit: 230g +/- 10g
<b>Input</b>	
<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
<b>Input frequency range</b>	47 ~ 63 Hz
<b>Input AC current</b>	Max. 1.7 A at 90 Vac
<b>Output</b>	
<b>Output power</b>	65W
<b>DC output</b>	19.5V
<b>Hold-up time</b>	5ms at 115 Vac input
<b>Output current limit</b>	<11.0A
<b>Connector</b>	4.5mm Barrel Type
<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)

### Technical Specifications

<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.

<b>Battery RH 3 Cell Wh 45 Long Life -PL Fast Charge</b>	<b>Dimensions (H x W x L)</b>	6.2 x 68.7 x 249.6mm
	<b>Weight</b>	190g
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell/ 545974
	<b>Energy</b>	
	<b>Voltage</b>	11.4V
	<b>Amp-hour capacity</b>	3.950Ah
	<b>Watt-hour capacity</b>	45Wh
	<b>Temperature</b>	
	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
	<b>Fuel Gauge LED</b>	NA
	<b>Warranty</b>	Based on system offering
	<b>Optional Travel Battery Available</b>	No

### FINGERPRINT READER

Model: Elan efsa80ST (module P1515B)  
 Mobile Voltage Operation: 2.7V to 3.6V  
 Operating Temperature: -4°F – 175°F (-20° ~ +80°C)  
 Current Consumption Image: 50mA peak  
 Low Latency Wait For Finger: 900uA  
 Capture Rate: 30 frame/sec  
 ESD Resistance: +15KV  
 Detection Matrix: 80\*80 pixels/ 508 dpi / 4\*4mm sensor area  
 FRR (False Reject Rate) / FAR (False Acceptance Rate): FRR: <3% , FAR: 1/100K

### COUNTRY OF ORIGIN

### Technical Specifications

China

### Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
<b>Cases</b>	HP Prelude Pro Recycle Backpack	1X644AA
	HP Prelude Pro Recycle Top Load	1X645AA
<b>Docking</b>	HP Thunderbolt 120W Dock G2	2UK37AA
	HP Thunderbolt 120W Dock w/Audio G2	3YE87AA
	HP Thunderbolt 230W Dock w/Combo Cable G2	3TR87AA
	HP USB-C 120W G5 Dock	5TW10AA
	HP USB-C Mini Dock	1PM64AA
	HP USB-C/A 120W Universal Dock G2	5TW13AA
	HP USB-C Travel Dock G2	7PJ38AA
	HP Wired Thunderbolt Audio Module	3AQ21AA
	HP USB-C Travel Dock	4WX89AA
	<b>Input/Output</b>	HP USB-C to HDMI 2.0 Adapter
HP USB-C to RJ45 Adapter		V8Y76AA#ABB
HP USB-C to USB 3.0 Adapter		N2Z63AA
HP 320M Wired Mouse		9VA80AA
HP Travel Bluetooth Mouse		6SP30AA
HP Travel USB Mouse		G1K28AA
HP Wireless Keyboard		T6U20AA
HP Slim Wireless Keyboard and Mouse		T6L04AA
HP Wireless USB Premium Keyboard		Z9N41AA
HP Wireless Rechargeable 950MK Mouse and Keyboard		3M165AA
HP Wired Desktop 320MK Mouse and Keyboard		9SR36AA
HP 235 WL Mouse and Keyboard Combo		1Y4D0AA
HP 125 Wired Keyboard		266C9AA
HP 225 Wired Mouse and Keyboard Combo		286J4AA
<b>Power</b>		HP 45W 4.5 mm LC Smart Japan Only AC Power Adapter
	HP 45W 4.5 mm Smart AC Power Adapter	H6Y88AA#ABA
	HP 45W USB-C LC AC Power Adapter	1MZ01AA#ABA
	HP 65W 4.5 mm Smart AC Power Adapter	H6Y89AA#ABA
	HP 65W 4.5 mm w Dongle 7.4 mm Slim AC Power Adapter	H6Y82AA#ABA
	HP 65W USB-C LC AC Power Adapter	1P3K6AA#ABA
	HP 65W USB-C Slim Travel AC Power Adapter	X7W50AA#ABA
<b>Storage</b>	HP USB DVD-Writer EXT ODD	Y3T76AA
<b>Security</b>	HP Nano Cable Lock	1AJ39AA
	HP SureKey Standard/Nano/Wedge Cable Lock	6UW42AA
<b>UCC</b>	HP Stereo 3.5mm Headset	T1A66AA
	HP Wired USB-A Stereo Headset	T1A67AA

Options and Accessories (sold separately and availability may vary by country)



### Summary of Changes

Date of change:	Version History:	Updated	Description of change:
	V1 to V2		

Copyright © 2021 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum. SDXC is a registered trademark of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.